



**be tire
smart**



**play your
PART**

PRESSURE • ALIGNMENT • ROTATION • TREAD

A consumer education program of the



COOPERTIRES

2007 International Product Manual

For a digital version of this manual, please visit
www.cooperworld.net.

HIGH PERFORMANCE

Zeon 2XS	1-2
Zeon ZPT	3
Zeon Sport A/S.	4
Lifeline Touring SLE (V/H-Speed Rated)	5

PASSENGER

Lifeline Touring SLE (T-Speed Rated) ..	6
Lifeline GLS	7
Lifeline Classic II.	8
Trendsetter SE	9-10
Cobra Radial G/T	11

WINTER

Weather-Master S/T ²	13-14
Discoverer M+S	15-16

SPORT TRUCK

Zeon XST	18
----------------	----

SUV/LIGHT TRUCK

Discoverer Sport HP	19
Discoverer H/T Plus	20
Discoverer H/T	21-22
Discoverer ATR	23-24
Discoverer Radial LT	25
SRM II Radial LT	26
Discoverer AST II	27
Discoverer Radial AST	28
Discoverer S/T	29-30
Discoverer S/T-C	31
Discoverer STT	32
Super Road Service	33
Courser Traction LT	34

NOTES &

RECOMMENDATIONS	35
------------------------------	----

HIGH PERFORMANCE & PASSENGER TIRES



ZEON 2XS

High Performance
1-2

ZEON ZPT

High Performance
3

ZEON SPORT A/S

High Performance
4

LIFELINER TOURING SLE

(V/H-Speed Rated)

High Performance
5



LIFELINER TOURING SLE

(T-Speed Rated)
Passenger
6

LIFELINER GLS

Passenger
7

LIFELINER CLASSIC II

Passenger
8

TRENDSETTER SE

Passenger
9-10

COBRA RADIAL G/T

Passenger
11

ZEON 2XS



Y/W-Speed Rated
Directional Design

Racing Inspired Tread

The tread compound in the Zeon 2XS was benchmarked against our Avon race division technology.

Tapered Tread

This design feature puts deep tread in the center and slightly shallower tread in the shoulders. This puts more rubber down in the fastest wearing part of the tire, the center. The result is less weight and improved wet handling.

Rim Protector

A rubber rim protector extends beyond the rim flange and decreases the chance of rim damage that can occur if a tire/wheel assembly scuffs a curb.

TREADWEAR TRACTION TEMPERATURE

UTQG


280

AA

A



S.D.



PSI



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

ZEON 2XS black sidewall sizes: Y-Rated

W11-4KM

U	01201	225/45ZR17	91Y	(7.5) 7.0-8.5	51	1356	24.88	9.03	8.19	833	10.0	7.9	23	10.4	J874	
U	01202	235/45ZR17	94Y	(8.0) 7.5-9.0	51	1477	25.32	9.30	8.59	819	10.0	7.9	25	11.3	J974	
U	01203	215/40ZR17	83Y	(7.5) 7.0-8.5	51	1074	23.74	8.51	8.11	873	10.0	7.9	21	9.5	K774	
U	01204	235/40ZR17	90Y	(8.5) 8.0-9.5	51	1323	24.37	9.55	8.75	851	10.0	7.9	23	10.4	K974	
U	01205	245/40ZR17	91Y	(8.5) 8.0-9.5	51	1356	24.69	9.84	9.07	840	10.0	7.9	24	10.9	K074	
U	01206	255/40ZR17	94Y	(9.0) 8.5-10.0	51	1477	25.00	10.31	9.39	829	10.0	7.9	26	11.8	KX74	
U	01207	225/40ZR18RE									10.0	7.9	23	10.4	K886	
U	01208	235/40ZR18	91Y	(8.5) 8.0-9.5	51	1356	25.37	9.55	8.75	817	10.0	7.9	25	11.3	K984	
U	01209	245/40ZR18XL	97Y	(8.5) 8.0-9.5	50	1609	25.69	9.85	9.07	807	10.0	7.9	26	11.8	K086	
U	01210	215/35ZR19XL	85Y	(7.5) 7.0-8.5	50	1135	24.86	8.65	7.95	834	10.0	7.9	21	9.5	L796	
U	01211	235/35ZR19XL	91Y	(8.5) 8.0-9.5	50	1356	25.37	9.60	8.75	817	10.0	7.9	24	10.9	L996	
U	01214	245/35ZR19XL	93Y	(8.5) 8.0-9.5	50	1433	25.75	9.73	8.91	805	10.0	7.9	26	11.8	L096	
U	01215	255/35ZR19XL	96Y	(9.0) 8.5-10.0	50	1565	25.97	10.06	9.31	798	10.0	7.9	26	11.8	LX96	
U	01213	265/30ZR19XL	93Y	(9.5) 9.0-10.0	50	1433	25.31	10.67	11.72	821	10.0	7.9	26	11.8	3V96	

Notes: 1, 2, 6, 7


U - Made in the United Kingdom



ZEON 2XS



S.D.



PSI



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

ZEON 2XS black sidewall sizes: W-Rated

W11-4GM

	01220	195/55ZR15	85W	(6.0) 5.5-7.0	51	1135	23.38	7.94	6.94	887	10.0	7.9	20	9.1	G554	
	01221	205/55ZR15	88W	(6.5) 5.5-7.5	51	1235	23.84	8.49	7.42	870	10.0	7.9	21	9.5	G654	
	+01222	195/50ZR15	82W	(6.0) 5.5-7.0	51	1047	22.67	7.95	7.24	914	10.0	7.9	20	9.1	H554	
	+01223	205/50ZR15	86W	(6.5) 5.5-7.5	51	1168	23.05	8.34	7.35	899	10.0	7.9	20	9.1	H654	
U	01224	205/55ZR16	91W	(6.5) 5.5-7.5	51	1356	24.85	8.49	7.42	834	10.0	7.9	22	10.0	G664	
U	01225	215/55ZR16	93W	(7.0) 6.0-7.5	51	1433	25.24	8.90	7.67	821	10.0	7.9	23	10.4	G764	
U	01226	225/55ZR16	95W	(7.0) 6.0-8.0	51	1521	25.71	9.02	7.93	806	10.0	7.9	26	11.8	G864	
U	01227	205/50ZR16	87W	(6.5) 5.5-7.5	51	1201	24.06	8.34	7.35	862	10.0	7.9	20	9.1	H664	
U	01229	225/50ZR16	92W	(7.0) 6.0-8.0	51	1389	24.88	9.12	8.32	833	10.0	7.9	26	11.8	H864	
	01231	245/50ZR16	97W	(7.5) 7.0-8.5	51	1609	25.64	9.86	8.95	809	10.0	7.9	28	12.7	H064	
U	+01230	205/45ZR16	83W	(7.0) 6.5-7.5	51	1074	23.19	8.12	7.39	894	10.0	7.9	20	9.1	J664	
	+01232	205/40ZR16RE	83W	(7.5) 7.0-8.0	50	1074	22.40	8.49	7.80	926	10.0	7.9	20	9.1	K666	
	01257	205/50ZR17XL	93W	(6.5) 5.5-7.5	50	1433	25.08	8.34	7.35	827	10.0	7.9	23	10.4	H676	
	01258	205/45ZR17XL	88W	(7.0) 6.5-7.5	50	1235	24.21	8.12	7.39	856	10.0	7.9	21	9.5	J676	
U	01233	215/45ZR17	87W	(7.0) 7.0-8.0	51	1201	24.73	8.30	7.96	838	10.0	7.9	23	10.4	J774	
U	01234	225/45ZR17	91W	(7.5) 7.0-8.5	51	1356	24.88	9.03	8.19	833	10.0	7.9	23	10.4	J874	
U	01235	235/45ZR17	94W	(8.0) 7.5-9.0	51	1477	25.32	9.30	8.59	819	10.0	7.9	25	11.3	J974	
	01236	245/45ZR17	95W	(8.0) 7.5-9.0	51	1521	25.62	9.61	8.91	809	10.0	7.9	26	11.8	J074	
	01237	255/45ZR17	98W	(8.5) 8.0-9.5	51	1653	26.03	10.12	9.35	796	10.0	7.9	29	13.2	JX74	
U	01238	205/40ZR17RE	84W	(7.5) 7.0-8.0	50	1102	23.42	8.49	7.80	885	10.0	7.9	19	8.6	K676	
U	+01239	215/40ZR17	83W	(7.5) 7.0-8.5	51	1074	23.74	8.51	8.11	873	10.0	7.9	22	10.0	K774	
U	+01240	235/40ZR17	90W	(8.5) 8.0-9.5	51	1323	24.37	9.55	8.75	851	10.0	7.9	24	10.9	K974	
U	01241	245/40ZR17	91W	(8.5) 8.0-9.5	51	1356	24.69	9.84	9.07	840	10.0	7.9	25	11.3	K074	
U	01242	255/40ZR17	94W	(9.0) 8.5-10.0	51	1477	25.00	10.31	9.39	829	10.0	7.9	28	12.7	KX74	
	01243	275/40ZR17	98W	(9.5) 9.0-11.0	51	1653	25.64	11.06	10.02	809	10.0	7.9	28	12.7	KY74	
	01259	285/40ZR17	100W	(10.0) 9.5-11.0	51	1764	25.95	11.61	10.50	799	10.0	7.9	32	14.5	KR74	
	01250	225/45ZR18RE	95W	(7.5) 7.0-8.5	50	1521	25.89	9.03	8.19	801	10.0	7.9	24	10.9	J886	
	01251	245/45ZR18RE	100W	(8.5) 7.5-9.0	50	1764	26.62	9.81	8.91	779	10.0	7.9	27	12.2	J086	
U	01244	225/40ZR18	88W	(8.0) 7.5-9.0	51	1235	25.04	9.26	8.43	828	10.0	7.9	24	10.9	K884	
U	01245	235/40ZR18	91W	(8.5) 8.0-9.5	51	1356	25.37	9.55	8.75	817	10.0	7.9	25	11.3	K984	
U	01246	245/40ZR18RE	97W	(8.5) 8.0-9.5	50	1609	25.69	9.85	9.07	807	10.0	7.9	26	11.8	K086	
	01261	275/40ZR18	99W	(9.5) 9.0-11.0	51	1709	26.64	11.06	10.04	778	10.0	7.9	29	13.2	KY84	
	01247	215/35ZR18RE	84W	(7.5) 7.0-8.5	50	1102	23.86	8.56	7.95	869	10.0	7.9	21	9.5	L786	
	01268	255/35ZR18XL	94W	(9.0) 8.5-10.0	50	1477	24.96	10.06	9.31	831	10.0	7.9	25	11.3	LX86	
	01248	265/35ZR18	93W	(9.5) 9.0-10.5	51	1433	25.28	10.72	9.71	820	10.0	7.9	26	11.8	LV84	
	01249	275/35ZR18	95W	(9.5) 9.0-11.0	51	1521	25.54	10.70	9.94	812	10.0	7.9	26	11.8	LY84	
	01260	255/40ZR19XL	100W	(9.0) 8.5-10.0	50	1764	27.01	10.31	9.39	768	10.0	7.9	28	12.7	KX96	
	01264	215/35ZR19XL	85W	(7.5) 7.0-8.5	50	1135	24.86	8.65	7.95	834	10.0	7.9	21	9.5	L796	
	01265	225/35ZR19XL	88W	(8.0) 7.5-9.0	50	1235	25.18	9.13	8.35	823	10.0	7.9	22	10.0	L896	
	01266	235/35ZR19XL	91W	(8.5) 8.0-9.5	50	1356	25.37	9.60	8.75	817	10.0	7.9	24	10.9	L996	
	01263	245/35ZR19XL	93W	(8.5) 8.0-9.5	50	1433	25.75	9.73	8.91	805	10.0	7.9	26	11.8	L096	
	01269	255/35ZR19XL	96W	(9.0) 8.5-10.0	50	1565	25.97	10.06	9.31	798	10.0	7.9	26	11.8	LX96	
	01256	275/30ZR19XL	96W	(9.5) 9.0-10.0	50	1565	25.52	10.84	10.18	813	10.0	7.9	27	12.2	3Y96	
	01270	245/40ZR20	95W	(8.5) 8.0-9.5	51	1521	27.70	9.85	9.07	749	10.0	7.9	28	12.7	K004	
	01262	245/35ZR20XL	95W	(8.5) 8.0-9.5	50	1521	26.76	9.68	8.91	775	10.0	7.9	26	11.8	L006	
	01267	255/35ZR20XL	97W	(9.0) 8.5-10.0	50	1609	26.97	10.06	9.31	798	10.0	7.9	27	12.2	LX06	
	01255	275/30ZR20XL	97W	(9.5) 9.0-10.0	50	1609	26.52	10.79	10.18	782	10.0	7.9	28	12.7	3Y06	

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability

U - Made in the United Kingdom



ZEON ZPT



H-Speed Rated Directional Design

All-Season

With a deep tread depth and high void ratio, this all season design provides excellent traction in all types of weather conditions throughout the year.

Performance Engineered Package

This performance radial combines spiral wound nylon overwrap, steel belts and a polyester cord body in a solid, high tech construction package to meet car enthusiasts' demands for responsive handling.

Rim Protector

A rubber rim protector extends beyond the rim flange and decreases the chance of rim damage that can occur if a tire/wheel assembly scuffs a curb.

M+S Rated

TREADWEAR TRACTION TEMPERATURE
UTQG 380 A A



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price			
ZEON ZPT black sidewall sizes:											W11-2HM				
01852	195/50R15	82H (6.0)	5.5-7.0	44	1047	22.77	7.95	7.26	911	10.0	7.9	19	8.6	H554	
01853	205/50R15	86H (6.5)	5.5-7.5	44	1168	23.15	8.34	7.37	896	10.0	7.9	20	9.1	H654	
01857	205/50R16	87H (6.5)	5.5-7.5	44	1201	24.06	8.34	7.35	862	10.0	7.9	21	9.5	H664	
01859	225/50R16	92H (7.0)	6.0-8.0	44	1389	24.98	9.12	8.32	830	10.0	7.9	26	11.8	H864	
01861	245/50R16	97H (7.5)	7.0-8.5	44	1609	25.74	9.86	8.95	805	10.0	7.9	29	13.2	H064	
01860	205/45R16	83H (7.0)	6.5-7.5	44	1074	23.29	8.12	7.39	890	10.0	7.9	20	9.1	J664	
01862	205/40R16RE	83H (7.5)	7.0-8.0	50	1074	22.50	8.49	7.81	921	10.0	7.9	20	9.1	K666	
01863	215/45R17	87H (7.0)	7.0-8.0	44	1201	24.75	8.30	7.97	838	10.0	7.9	23	10.4	J774	
01864	225/45R17	91H (7.5)	7.0-8.5	44	1356	24.91	9.03	8.20	832	10.0	7.9	25	11.3	J874	
01865	235/45R17	94H (8.0)	7.5-9.0	44	1477	25.35	9.30	8.60	818	10.0	7.9	26	11.8	J974	
01866	245/45R17	95H (8.0)	7.5-9.0	44	1521	25.65	9.61	8.92	808	10.0	7.9	26	11.8	J074	
01868	205/40R17RE	84H (7.5)	7.0-8.0	50	1102	23.45	8.43	7.81	884	10.0	7.9	20	9.1	K676	
01869	215/40R17	83H (7.5)	7.0-8.5	44	1074	23.77	8.51	8.12	872	10.0	7.9	20	9.1	K774	
01878	215/45R18	89H (7.0)	7.0-8.0	44	1279	25.67	8.30	7.97	801	10.5	8.3	23	10.4	J784	
01874	225/40R18	88H (8.0)	7.5-9.0	44	1235	25.07	9.03	8.44	827	10.0	7.9	24	10.9	K884	
01875	235/40R18	91H (8.5)	8.0-9.5	44	1356	25.40	9.55	8.76	816	10.0	7.9	26	11.8	K984	
01876	245/40R18RE	97H (8.5)	8.0-9.5	50	1609	25.72	9.84	9.08	806	10.0	7.9	27	12.2	K086	
01877	215/35R18RE	84H (7.5)	7.0-8.5	50	1102	23.88	8.56	7.96	868	10.0	7.9	21	9.5	L786	

Notes: 1, 2, 6, 7



ZEON SPORT A/S



W-Speed Rated
Directional Design

Coupled Silica Tread Compound
Allows for excellent wet traction.

Continuous Center Rib
Increases footprint rigidity and steering response, while allowing rapid water expulsion to reduce hydroplaning.

All-weather Design
Matches the performance requirements of today's original equipment needs.

M+S Rated

TREADWEAR	TRACTION	TEMPERATURE
UTQG	400	AA
		A



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

ZEON SPORT A/S black sidewall sizes:

W11-2PM

25501	205/55ZR16	91W	(6.5) 5.5-7.5	51	1356	24.87	8.49	7.46	834	10.0	7.9	22	10.0	G664	
25515	215/55ZR16	93W	(7.0) 6.0-7.5	51	1433	25.27	8.90	7.70	821	10.0	7.9	24	10.9	G764	
25502	225/55ZR16	95W	(7.0) 6.0-8.0	51	1521	25.79	9.02	7.97	805	10.0	7.9	27	12.2	G864	
25505	225/50ZR16	92W	(7.0) 6.0-8.0	51	1389	24.91	9.12	8.32	832	10.0	7.9	27	12.2	H864	
25516	245/50ZR16	97W	(7.5) 7.0-8.5	51	1609	25.66	9.86	8.96	808	10.0	7.9	29	13.2	H064	
25518	215/55ZR17	94W	(7.0) 6.0-7.5	51	1477	26.29	8.90	7.63	789	10.0	7.9	25	11.3	G774	
25526	225/55ZR17	97W	(7.0) 6.0-8.0	51	1609	26.74	9.11	7.95	775	10.5	8.3	29	13.2	G874	
25503	235/55ZR17	99W	(7.5) 6.5-8.5	51	1709	27.13	9.67	8.52	764	10.0	7.9	30	13.6	G974	
25520	205/50ZR17XL	93W	(6.5) 5.5-7.5	50	1433	25.11	8.34	7.37	826	10.0	7.9	23	10.4	H676	
25504	215/50ZR17	91W	(7.0) 6.0-7.5	51	1356	25.50	8.82	7.77	813	10.0	7.9	25	11.3	H774	
25506	225/50ZR17	94W	(7.0) 6.0-8.0	51	1477	25.90	9.12	8.34	801	10.0	7.9	29	13.2	H874	
25507	235/50ZR17	96W	(7.5) 6.5-8.5	51	1565	26.29	9.55	8.60	789	10.0	7.9	30	13.6	H974	
25521	205/45ZR17	84W	(7.0) 6.5-7.5	51	1102	24.24	8.12	7.40	855	10.0	7.9	21	9.5	J674	
25522	215/45ZR17XL	91W	(7.0) 7.0-8.0	50	1356	24.75	8.30	7.97	838	10.0	7.9	23	10.4	J776	
25510	225/45ZR17XL	94W	(7.5) 7.0-8.5	50	1477	24.91	9.03	8.20	832	10.0	7.9	24	10.9	J876	
25512	235/45ZR17	94W	(8.0) 7.5-9.0	51	1477	25.35	9.30	8.60	818	10.0	7.9	25	11.3	J974	
25508	245/45ZR17	95W	(8.0) 7.5-9.0	51	1521	25.65	9.61	8.92	808	10.0	7.9	26	11.8	J074	
25525	275/40ZR17	98W	(9.5) 9.0-11.0	51	1653	25.66	11.06	10.04	808	10.0	7.9	31	14.1	KY74	
25519	235/55ZR18	100W	(7.5) 6.5-8.5	51	1764	28.13	9.67	8.52	737	10.0	7.9	31	14.1	G984	
25511	225/45ZR18	91W	(7.5) 7.0-8.5	51	1356	25.91	9.03	8.20	800	10.0	7.9	25	11.3	J884	
25509	245/45ZR18	96W	(8.5) 7.5-9.0	51	1565	26.65	9.81	8.92	778	10.0	7.9	28	12.7	J084	
*25523	255/45ZR18XL	103W	(8.5) 8.0-9.5	50	1929	27.03	9.80	9.36	767	10.0	7.9	29	13.2	JX86	
25514	225/40ZR18XL	92W	(8.0) 7.5-9.0	50	1389	25.07	9.19	8.44	827	10.0	7.9	24	10.9	K886	
25524	235/40ZR18XL	95W	(8.5) 8.0-9.5	50	1524	25.36	9.33	8.60	817	10.0	7.9	25	11.3	K986	
25513	245/40ZR18XL	97W	(8.5) 8.0-9.5	50	1609	25.72	9.84	9.08	806	10.0	7.9	26	11.8	K086	
25517	275/40ZR18	99W	(9.5) 9.0-11.0	51	1709	26.66	11.06	10.04	778	10.0	7.9	30	13.6	KY84	
*25527	265/50ZR20XL	111W	(8.5) 7.5-9.5	50	2403	30.42	10.74	9.44	682	10.5	8.3			HV06	
25528	245/45ZR20	99W	(8.0) 7.5-9.0	51	1709	28.61	9.59	8.86	725	10.5	8.3	30	13.6	J004	
*25529	255/45ZR20	101W	(8.5) 8.0-9.5	51	1819	29.04	10.05	9.36	714	10.5	8.3			JX04	

Notes: 1, 2, 6, 7
* Availability To Be Announced




LIFELINER TOURING SLE



M+S Rated



S.D.



PSI



V/H/T-Speed Rated

Optimized Bead Contour

For more uniform fit to rim and improved ride quality.

Computer-Aided Noise Optimization

Delivers quiet ride.

Offset Shoulder Slots

Breaks up tire pitch harmonics, allowing for a quiet ride.

	SERIES	TREADWEAR	TRACTION	TEMPERATURE
UTQG	V-RATED	360	A	A
	H-RATED	420	A	A
	T-RATED	620	A	B

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
LIFELINER TOURING SLE black sidewall sizes: V-Rated												W11-2EE
00953	205/65R15	94V (6.0) 5.5-7.5	44	1477	25.41	8.37	6.46	817	11.0 8.7	23 10.4	F654	
00955	195/60R15	88V (6.0) 5.5-7.0	44	1235	24.20	8.06	6.28	858	11.0 8.7	20 9.1	E554	
00956	195/55R15	85V (6.0) 5.5-7.0	44	1135	23.43	7.92	6.52	887	11.0 8.7	20 9.1	G554	
00961	205/60R16	92V (6.0) 5.5-7.5	44	1389	25.65	8.40	6.55	809	11.0 8.7	23 10.4	E664	
00962	215/60R16	95V (6.5) 6.0-7.5	44	1521	26.10	8.95	7.13	795	11.0 8.7	25 11.3	E764	
00963	225/60R16	98V (6.5) 6.0-8.0	44	1653	26.56	9.15	7.16	782	11.0 8.7	26 11.8	E864	
00964	205/55R16	91V (6.5) 5.5-7.5	44	1356	24.86	8.95	7.17	836	11.0 8.7	22 10.0	G664	
00965	215/55R16	93V (7.0) 6.0-7.5	44	1433	25.27	8.92	7.37	822	11.0 8.7	24 10.9	G764	
00966	225/55R16	95V (7.0) 6.0-8.0	44	1521	25.77	9.36	7.59	806	11.0 8.7	26 11.8	G864	
00968	215/50R16	90V (7.0) 6.0-7.5	44	1323	24.49	8.91	7.45	851	11.0 8.7	23 10.4	H764	
00969	225/50R16	92V (7.0) 6.0-8.0	44	1389	24.89	9.15	7.69	835	11.0 8.7	24 10.9	H864	
00970	215/55R17	94V (7.0) 6.0-7.5	44	1477	26.31	9.46	7.32	789	11.0 8.7	26 11.8	G774	
00975	225/55R17	97V (7.0) 6.0-8.0	44	1609	26.76	9.20	7.40	776	11.0 8.7	27 12.2	G874	
00980	215/50R17	91V (7.0) 6.0-7.5	44	1356	25.46	9.34	7.37	817	11.0 8.7	24 10.9	H774	
00981	225/50R17	94V (7.0) 6.0-8.0	44	1477	25.89	9.66	7.69	802	11.0 8.7	26 11.8	H874	
00982	235/50R17	96V (7.5) 6.5-8.5	44	1565	26.30	9.91	8.09	790	11.0 8.7	28 12.7	H974	

LIFELINER TOURING SLE black sidewall sizes: H-Rated												W11-2CJ
+00540	195/70R14	91H (6.0) 5.0-6.5	44	1356	24.80	8.02	5.97	838	11.0 8.7	20 9.1	R544	
+00541	185/65R14	86H (5.5) 5.0-6.5	44	1168	23.45	7.64	5.75	885	11.0 8.7	18 8.2	F444	
+00542	195/65R14	89H (6.0) 5.5-7.0	44	1279	23.97	8.05	6.13	866	11.0 8.7	19 8.6	F544	
00543	185/60R14	82H (5.5) 5.0-6.5	44	1047	22.73	7.48	5.90	914	11.0 8.7	18 8.2	E444	
00544	195/60R14	86H (6.0) 5.5-7.0	44	1168	23.20	7.97	6.29	894	11.0 8.7	18 8.2	E544	
00551	185/65R15	88H (5.5) 5.0-6.5	44	1235	24.45	7.83	5.75	849	11.0 8.7	19 8.6	F454	
00552	195/65R15	91H (6.0) 5.5-7.0	44	1356	24.97	8.02	6.13	831	11.0 8.7	20 9.1	F554	
00553	205/65R15	94H (6.0) 5.5-7.5	44	1477	25.41	8.34	6.46	817	11.0 8.7	22 10.0	F654	
+00554	215/65R15	96H (6.5) 6.0-7.5	44	1565	26.64	8.69	6.76	780	11.0 8.7	24 10.9	F754	
00555	195/60R15	88H (6.0) 5.5-7.0	44	1235	24.20	8.03	6.29	858	11.0 8.7	20 9.1	E554	
00556	205/60R15	91H (6.0) 5.5-7.5	44	1356	25.10	8.29	6.55	828	11.0 8.7	21 9.5	E654	
00557	215/60R15	94H (6.5) 6.0-7.5	44	1477	25.10	8.82	6.93	828	11.0 8.7	24 10.9	E754	
00558	225/60R15	96H (6.5) 6.0-8.0	44	1565	25.56	8.97	7.16	813	11.0 8.7	24 10.9	E854	
00561	205/60R16	92H (6.0) 5.5-7.5	44	1389	25.65	8.49	6.54	809	11.0 8.7	23 10.4	E664	
00562	225/60R16	98H (6.5) 6.0-8.0	44	1653	26.56	9.08	7.16	782	11.0 8.7	26 11.8	E864	
00563	235/60R16	100H (7.0) 6.5-8.5	44	1764	27.10	9.52	7.55	766	11.0 8.7	27 12.2	E964	
00564	205/55R16	91H (6.5) 5.5-7.5	44	1356	24.86	8.95	6.98	836	11.0 8.7	22 10.0	G664	
00565	215/55R16	93H (7.0) 6.0-7.5	44	1433	25.27	8.87	7.37	822	11.0 8.7	23 10.4	G764	
00566	225/55R16	95H (7.0) 6.0-8.0	44	1521	25.77	9.29	7.59	806	11.0 8.7	25 11.3	G864	
00568	205/50R16	87H (6.5) 5.5-7.5	44	1201	24.09	8.32	7.05	862	11.0 8.7	21 9.5	H664	
00572	235/55R17	99H (7.5) 6.5-8.5	44	1709	27.15	9.94	8.01	765	11.0 8.7	28 12.7	G974	
00575	225/60R18	100H (6.5) 6.0-8.0	44	1764	28.62	9.01	7.19	725	11.0 8.7	28 12.7	E884	

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability



COOPERTIRES

LIFELINER TOURING SLE



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

LIFELINER TOURING SLE black sidewall sizes: T-Rated

W11-2EG

00641	185/70R14	88T	(5.5) 4.5-6.0	44	1235	24.25	7.44	5.51	859	11.0	8.7	18	8.2	R444
00642	195/70R14	91T	(6.0) 5.0-6.5	44	1356	24.80	8.05	5.86	840	11.0	8.7	19	8.6	R544
00656	205/70R14	95T	(6.0) 5.0-7.0	44	1521	25.35	8.23	6.10	822	11.0	8.7	20	9.1	R644
00631	175/65R14	82T	(5.0) 5.0-6.0	44	1047	22.99	6.97	5.44	906	11.0	8.7	16	7.3	F344
00632	185/65R14	86T	(5.5) 5.0-6.5	44	1168	23.46	7.44	5.80	888	11.0	8.7	18	8.2	F444
^00633	195/65R14	89T	(6.0) 5.5-7.0	44	1279	24.02	7.91	6.17	868	11.0	8.7	18	8.2	F544
00643	205/70R15	96T	(6.0) 5.0-7.0	44	1565	26.34	8.23	6.10	791	11.0	8.7	22	10.0	R654
00645	215/70R15	98T	(6.0) 5.5-7.0	44	1653	26.89	8.70	6.45	775	11.0	8.7	23	10.4	R754
00634	185/65R15	88T	(5.5) 5.0-6.5	44	1235	24.45	7.44	5.86	853	11.0	8.7	19	8.6	F454
00635	195/65R15	91T	(6.0) 5.5-7.0	44	1356	25.00	7.91	6.17	834	11.0	8.7	20	9.1	F554
00636	205/65R15	94T	(6.0) 5.5-7.5	44	1477	25.47	8.23	6.42	819	11.0	8.7	21	9.5	F654
00637	215/65R15	96T	(6.5) 6.0-7.5	44	1565	26.02	8.70	6.79	801	11.0	8.7	22	10.0	F754
00621	185/60R15	84T	(5.5) 5.0-6.5	44	1102	23.76	7.44	5.86	876	11.0	8.7	19	8.6	E454
00622	195/60R15	88T	(6.0) 5.5-7.0	44	1235	24.21	7.91	6.25	860	11.0	8.7	19	8.6	E554
00623	205/60R15	91T	(6.0) 5.5-7.5	44	1356	24.69	8.23	6.50	844	11.0	8.7	20	9.1	E654
00624	215/60R15	94T	(6.5) 6.0-7.5	44	1477	25.16	8.70	6.87	829	11.0	8.7	23	10.4	E754
00613	205/55R15	88T	(6.5) 5.5-7.5	44	1235	23.90	8.43	6.99	872	11.0	8.7	21	9.5	G654
00630	205/65R16	95T	(6.0) 5.5-7.5	44	1521	26.47	8.30	6.42	783	11.0	8.7	23	10.4	F664
00638	215/65R16	98T	(6.5) 6.0-7.5	44	1653	27.01	8.70	6.79	772	11.0	8.7	25	11.3	F764
00601	235/65R16	103T	(7.0) 6.5-8.5	44	1929	27.93	9.56	7.37	742	11.0	8.7	27	12.2	F964
00625	215/60R16	95T	(6.5) 6.0-7.5	44	1521	26.14	8.70	6.87	797	11.0	8.7	24	10.9	E764
00626	225/60R16	98T	(6.5) 6.0-8.0	44	1653	26.61	8.98	7.09	783	11.0	8.7	25	11.3	E864
00628	235/60R16	100T	(7.0) 6.5-8.5	44	1764	27.09	9.45	7.46	769	11.0	8.7	27	12.2	E964
00614	205/55R16	91T	(6.5) 5.5-7.5	44	1356	24.88	8.43	6.99	837	11.0	8.7	23	10.4	G664
00620	215/65R17	99T	(6.5) 6.0-7.5	44	1709	28.01	8.93	6.91	740	11.0	8.7	26	11.8	F774
00617	215/60R17	96T	(6.5) 6.0-7.5	44	1565	27.14	9.03	6.77	764	11.0	8.7	25	11.3	E774
00619	235/60R17	102T	(7.0) 6.5-8.5	44	1874	28.09	9.53	7.36	738	11.0	8.7	28	12.7	E974
U 00618	225/55R17	97T	(7.0) 6.0-8.0	44	1609	26.76	9.20	7.40	776	11.0	8.7	27	12.2	G874
U 00615	225/55R18	98T	(7.0) 6.0-8.0	44	1653	27.79	9.11	7.40	746	11.0	8.7	34	15.4	G884

LIFELINER TOURING SLE white sidewall (.65") sizes: T-Rated

W81-2EG

+00639	185/70R14	88T	(5.5) 4.5-6.0	44	1235	24.25	7.44	5.51	859	11.0	8.7	18	8.2	R444
+00640	195/70R14	91T	(6.0) 5.0-6.5	44	1356	24.80	8.05	5.86	840	11.0	8.7	20	9.1	R544
+00657	215/70R14	96T	(6.5) 5.5-7.0	44	1565	25.91	8.70	6.45	804	11.0	8.7	23	10.4	R744

LIFELINER TOURING SLE white sidewall (.75") sizes: T-Rated

WK1-2EG

00644	205/70R15	96T	(6.0) 5.0-7.0	44	1565	26.34	8.23	6.10	791	11.0	8.7	22	10.0	R654
00648	235/70R15	103T	(7.0) 6.0-8.0	44	1929	27.99	9.55	7.00	745	11.0	8.7	27	12.2	R954

LIFELINER TOURING SLE white sidewall (.43") sizes: T-Rated

W61-2EG

00646	215/70R15	98T	(6.5) 5.5-7.0	44	1653	26.89	8.70	6.45	775	11.0	8.7	24	10.9	R754
00647	225/70R15	100T	(6.5) 6.0-7.5	44	1764	27.44	8.98	6.65	760	11.0	8.7	25	11.3	R854
00627	225/60R16	98T	(6.5) 6.0-8.0	44	1653	26.61	8.98	7.09	783	11.0	8.7	25	11.3	E864
00603	225/60R17	99T	(6.5) 6.0-8.0	44	1709	27.62	9.14	6.99	751	11.0	8.7	27	12.2	E874

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability

^ Limited Availability

U - Made in the United Kingdom



LIFELINER GLS



T-Speed Rated

Quiet-Riding Design

The five-rib, all season design employs a computer enhanced sound quality system that optimizes the tread patterns pitch sequence for a quiet ride.

Even-Wearing Design

A notched, solid center rib, along with a refined tread element shape, helps provide even treadwear. Shoulder slotting is also designed for resistance to irregular wear while providing solid, all-season performance.

Four Circumferential Grooves

Designed to propel water out and away from the tread contact area, the grooves combined with the high sipe density and variable shoulder slots, help provide superior all weather traction.

M+S Rated

TREADWEAR TRACTION TEMPERATURE

UTQG **540 A B**



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

LIFELINER GLS black sidewall sizes:

W11-1HE

01611	175/70R13	82T	(5.0) 4.5-6.0	44	1047	22.68	6.89	5.10	914	10.0	7.9	15	6.8	R334
01612	175/70R14	84T	(5.0) 4.5-6.0	44	1102	23.68	6.89	5.10	876	10.0	7.9	16	7.3	R344
01613	185/70R14	88T	(5.5) 4.5-6.0	44	1235	24.23	7.40	5.30	856	10.0	7.9	17	7.7	R444
01614	195/70R14	91T	(6.0) 5.0-6.5	44	1356	24.78	7.80	5.60	837	10.0	7.9	18	8.2	R544
01603	175/65R14	82T	(5.0) 5.0-6.0	44	1047	22.95	6.85	5.20	903	10.0	7.9	16	7.3	F344
01604	185/65R14	86T	(5.5) 5.0-6.5	44	1168	23.40	7.35	5.55	886	10.0	7.9	17	7.7	F444
01605	185/65R15	88T	(5.5) 5.0-6.5	44	1235	24.40	7.35	5.55	852	10.0	7.9	18	8.2	F454
01606	195/65R15	91T	(6.0) 5.5-7.0	44	1356	24.90	7.80	5.85	832	10.0	7.9	20	9.1	F554
01607	205/65R15	94T	(6.0) 5.5-7.5	44	1400	25.26	8.16	6.05	821	10.5	8.3	21	9.5	F654
01608	215/65R15	96T	(6.5) 6.0-7.5	44	1510	25.81	8.65	6.50	803	10.5	8.3	23	10.4	F754
01609	215/65R16	98T	(6.5) 6.0-7.5	44	1653	26.81	8.65	6.50	773	10.5	8.3	25	11.3	F764
01601	215/60R16	95T	(6.5) 6.0-7.5	44	1477	25.93	8.55	6.55	800	10.5	8.3	24	10.9	E764
01602	225/60R16	98T	(6.5) 6.0-8.0	44	1609	26.37	8.80	6.80	786	10.5	8.3	24	10.9	E864
01610	205/55R16	91T	(6.5) 5.5-7.5	44	1279	24.64	8.30	7.00	841	10.0	7.9	23	10.4	G664

LIFELINER GLS white sidewall (.65") sizes:

W81-1HE

01615	205/70R14	95T	(6.0) 5.0-7.0	44	1521	25.28	8.11	5.80	822	10.5	8.3	20	9.1	R644
01616	215/70R14	96T	(6.5) 5.5-7.0	44	1565	25.78	8.58	6.10	804	10.5	8.3	22	10.0	R744

LIFELINER GLS white sidewall (.75") sizes:

WK1-1HE

01617	205/70R15	96T	(6.0) 5.0-7.0	44	1499	26.18	8.11	5.80	792	10.5	8.3	21	9.5	R654
01618	215/70R15	98T	(6.5) 5.5-7.0	44	1620	26.68	8.58	6.10	777	10.5	8.3	22	10.0	R754

Notes: 1, 2, 6, 7



LIFELINER CLASSIC II

S-Speed Rated



All-Season Tread

"See through" grooves and wide, lateral traction slots carve out a modern 5 rib tread design to provide excellent all season performance. Elongated siping in the shoulder elements enhances the tire's gripping ability in diverse weather conditions.

Long-Wearing Tread

A specially formulated tread compound helps provide a combination of long, even treadwear and excellent traction. This tire rates an A for traction in UTQG grading.

Poly/Steel Body

A strong foundation of two polyester plies and two steel belts creates a durable tire body for long, dependable service.

M+S Rated

	TREADWEAR	TRACTION	TEMPERATURE
UTQG	520	A	B



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
LIFELINER CLASSIC II black sidewall size:											W11-007	
+00789	P235/75R15XL 108S	(6.5) 6.0-8.0	41	2183	28.85	9.40	6.95	720	11.0 8.7	31 14.1	W956	
LIFELINER CLASSIC II white sidewall (.65") sizes:											W81-007	
+00781	P185/75R14 89S	(5.0) 4.5-6.0	35	1290	24.97	7.40	5.35	830	11.0 8.7	19 8.6	W444	
+00782	P195/75R14 92S	(5.5) 5.0-6.5	35	1400	25.50	7.90	5.70	815	11.0 8.7	21 9.5	W544	
+00783	P205/75R14 95S	(5.5) 5.0-7.0	35	1532	26.15	8.15	5.95	793	11.0 8.7	22 10.0	W644	
LIFELINER CLASSIC II white sidewall (.75") sizes:											WK1-007	
+00784	P205/75R15 97S	(5.5) 5.0-7.0	35	1598	27.15	8.15	5.95	763	11.0 8.7	23 10.4	W654	
+00785	P215/75R15 100S	(6.0) 5.5-7.0	35	1742	27.80	8.70	6.35	746	11.0 8.7	26 11.8	W754	
+00786	P225/75R15 102S	(6.0) 6.6-7.5	35	1874	28.30	8.95	6.55	732	11.0 8.7	27 12.2	W854	
+00787	P235/75R15 105S	(6.5) 6.0-8.0	35	2028	28.85	9.40	6.95	720	11.0 8.7	29 13.2	W954	
00788	P235/75R15XL 108S	(6.5) 6.0-8.0	41	2183	28.85	9.40	6.95	720	11.0 8.7	31 14.1	W956	
LIFELINER CLASSIC II raised white letter size:											W31-007	
00790	P235/75R15XL 108S	(6.5) 6.0-8.0	41	2183	28.85	9.40	6.95	720	11.0 8.7	31 14.1	W956	

Notes: 2, 6, 7

+ Discontinued - Limited Availability



TRENDSETTER SE



M+S Rated

Dual Compound Tread

Specially designed high-mileage tread cap compound is supported by a highly resilient base compound. Working in tandem, this cap-base system promotes excellent durability and low rolling resistance.

Variable Pitch Elements

Computer-designed to reduce noise, the different sized elements work to provide a quiet-running tire at highway speeds.

All-Season Block Tread Design

Squared-off tread elements form an effective gripping edge for excellent year-round traction. This modern-looking radial will perform well in wet and dry weather.

TREADWEAR TRACTION TEMPERATURE

UTQG **440** **A** **B**



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

TRENDSETTER SE black sidewall size:

W11-013

^01314	P235/75R15XL STD	(6.5) 6.0-8.0	41	2183	28.65	9.10	6.30	724	11.0	8.7	29	13.2	W956
--------	------------------	---------------	----	------	-------	------	------	-----	------	-----	----	------	------

TRENDSETTER SE black sidewall sizes:

W11-029

C	02907	P175/70R13	82S	(5.0) 4.5-6.0	35	1036	22.68	6.89	4.90	914	10.0	7.9	14	6.4	U334
	02908	P185/70R13	85S	(5.5) 4.5-6.0	35	1135	23.23	7.40	5.10	893	10.0	7.9	15	6.8	U434
	02926	P175/70R14	84S	(5.0) 4.5-6.0	35	1102	23.18	6.89	4.90	896	10.0	7.9	16	7.3	U344
C	02909	P185/70R14	87S	(5.5) 4.5-6.0	35	1201	24.23	7.40	5.10	856	10.0	7.9	17	7.7	U444
C	02910	P195/70R14	90S	(6.0) 5.0-6.5	35	1312	24.78	7.80	5.40	837	10.0	7.9	17	7.7	U544
C	02914	P205/70R14	93S	(6.0) 5.0-7.0	35	1433	25.28	8.11	5.60	822	10.0	7.9	18	8.2	U644
	02918	P175/65R14	81S	(5.0) 5.0-6.0	35	1019	22.90	6.85	5.00	907	10.0	7.9	15	6.8	S344
C	02919	P185/65R14	85S	(5.5) 5.0-6.5	35	1124	23.35	7.35	5.35	889	10.0	7.9	16	7.3	S444
	02911	P205/70R15	95S	(6.0) 5.0-7.0	35	1499	26.28	8.11	5.60	790	10.0	7.9	20	9.1	U654
	02915	P195/65R15	89S	(6.0) 5.5-7.0	35	1279	24.90	7.80	5.70	839	10.0	7.9	18	8.2	S554
C	02916	P205/65R15	92S	(6.0) 5.5-7.5	35	1400	25.25	8.16	5.85	823	10.0	7.9	20	9.1	S654
	02917	P215/65R15	95S	(6.5) 6.0-7.5	35	1510	25.88	8.65	6.38	807	10.0	7.9	22	10.0	S754
	02935	P215/60R16	94S	(6.5) 6.0-7.5	35	1477	26.10	8.55	6.40	801	10.0	7.9	22	10.0	T764
	02936	P225/60R16	97S	(6.5) 6.0-8.0	35	1609	26.52	8.80	6.60	788	10.0	7.9	23	10.4	T864
	02932	P205/55R16	89S	(6.5) 5.5-7.5	35	1279	24.75	8.30	7.10	844	10.0	7.9	22	10.0	C664

Notes: 2, 6, 7

^ Limited Availability

C - Made in China



TRENDSETTER SE



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

TRENDSETTER SE white sidewall (.50") sizes:

WH1-013

01301	P155/80R13	STD	(4.5) 4.0-5.0	35	959	22.75	6.10	3.90	911	9.5	7.5	13	5.9	X134	
+01302	P165/80R13	STD	(4.5) 4.0-5.5	35	1069	23.3	6.45	4.10	890	10.0	7.9	13	5.9	X234	
+01303	P175/80R13	STD	(5.0) 4.5-6.0	35	1179	24	6.85	4.40	864	10.0	7.9	14	6.4	X334	
+01304	P185/80R13	STD	(5.0) 4.5-6.0	35	1301	24.5	7.20	4.60	846	10.0	7.9	16	7.3	X434	

TRENDSETTER II A/W STEEL BELTED RADIAL white sidewall (.65") size:

W81-002

^00205	P175/75R14	STD	(5.0) 4.5-6.0	35	1168	24.2	6.85	4.40	857	10.0	7.9	15	6.8	W344	
--------	------------	-----	---------------	----	------	------	------	------	-----	------	-----	----	-----	------	--

TRENDSETTER SE white sidewall (.65") sizes:

W81-013

01305	P185/75R14	STD	(5.0) 4.5-6.0	35	1290	24.8	7.20	4.60	836	10.0	7.9	17	7.7	W444	
01306	P195/75R14	STD	(5.5) 5.0-6.5	35	1400	25.4	7.60	4.90	816	10.0	7.9	18	8.2	W544	
01307	P205/75R14	95	(5.5) 5.0-7.0	35	1532	25.95	7.95	5.10	799	10.5	8.3	19	8.6	W644	
01308	P215/75R14	STD	(6.0) 5.5-7.0	35	1664	26.55	8.40	5.40	781	10.5	8.3	20	9.1	W744	
+01309	P225/75R14	STD	(6.0) 6.0-7.5	35	1797	27.05	8.70	5.60	766	10.5	8.3	23	10.4	W844	

TRENDSETTER SE white sidewall (.65") sizes:

W81-029

+02901	P185/70R14	87S	(5.5) 4.5-6.0	35	1201	24.23	7.40	5.10	856	10.0	7.9	17	7.7	U444	
+02902	P195/70R14	90S	(6.0) 5.0-6.5	35	1312	24.78	7.80	5.40	837	10.0	7.9	18	8.2	U544	
+02903	P205/70R14	93S	(6.0) 5.0-7.0	35	1433	25.28	8.11	5.60	822	10.0	7.9	19	8.6	U644	
02904	P215/70R14	96S	(6.5) 5.5-7.0	35	1554	25.78	8.58	5.90	804	10.0	7.9	21	9.5	U744	

TRENDSETTER SE white sidewall (.75") sizes:

WK1-013

01310	P205/75R15	STD	(5.5) 5.0-7.0	35	1598	26.95	7.95	5.10	769	10.5	8.3	20	9.1	W654	
01311	P215/75R15	100	(6.0) 5.5-7.0	35	1742	27.55	8.40	5.40	753	10.5	8.3	22	10.0	W754	
01312	P225/75R15	STD	(6.0) 6.0-7.5	35	1874	28.05	8.70	5.60	739	10.5	8.3	24	10.9	W854	
01313	P235/75R15	105	(6.5) 6.0-8.0	35	2028	28.65	9.10	5.90	724	11.0	8.7	25	11.3	W954	

TRENDSETTER SE white sidewall (.75") sizes:

WK1-029

02905	P205/70R15	95S	(6.0) 5.0-7.0	35	1499	26.28	8.11	5.60	790	10.0	7.9	20	9.1	U654	
02906	P215/70R15	97S	(6.5) 5.5-7.0	35	1620	26.78	8.58	5.90	774	10.0	7.9	22	10.0	U754	
02912	P225/70R15	100S	(6.5) 6.0-7.5	35	1753	27.28	8.85	6.15	760	10.0	7.9	24	10.9	U854	

Notes: 2, 6, 7

+ Discontinued - Limited Availability

^ Limited Availability



COBRA RADIAL G/T

T/S-Speed Rated



Performance Tread

The void ratio in this new performance radial has been re-distributed for increased tire-to-road contact which leads to improvements in treadwear and handling.

Even-Wearing Design

A notched, solid center rib, along with a refined tread element shape, helps provide even treadwear. Shoulder slotting is also designed for resistance to irregular wear while providing solid, all-season performance.


Quiet Ride

Pitch sequence has been optimized to reduce tread related tire noise for increased consumer riding comfort.

M+S Rated



S.D.



PSI



	SERIES	TREADWEAR	TRACTION	TEMPERATURE
UTQG	50 SERIES	440	A	C
	OTHERS	440	A	B

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

COBRA RADIAL G/T black sidewall sizes:

W11-396

39620	P185/60R14	82T	(5.5) 5.0-6.5	44	1047	22.80	7.15	6.00	912	10.5	8.3	17	7.7	T444
39621	P195/60R14	85T	(6.0) 5.5-7.0	44	1135	23.28	7.62	6.40	893	10.5	8.3	18	8.2	T544
39622	P195/60R15	87T	(6.0) 5.5-7.0	44	1190	24.30	7.60	6.40	856	10.5	8.3	19	8.6	T554
39623	P205/60R15	90T	(6.0) 5.5-7.5	44	1301	24.73	7.83	6.50	841	10.5	8.3	20	9.1	T654
39624	P225/60R15	95T	(6.5) 6.0-7.5	44	1521	25.67	8.63	7.20	810	10.5	8.3	23	10.4	T854
39617	P195/50R15	81S	(6.0) 5.5-7.0	35	1019	22.78	7.64	6.45	913	10.5	8.3	18	8.2	Z554
39618	P205/50R15	84S	(6.5) 5.5-7.5	35	1113	23.15	8.18	6.85	898	10.5	8.3	20	9.1	Z654
^39619	P225/50R15	90S	(7.0) 6.0-8.0	35	1301	23.90	8.94	7.45	870	10.5	8.3	22	10.0	Z854
39648	P215/55R16	91T	(7.0) 6.0-7.5	44	1356	25.25	8.83	7.30	821	10.5	8.3	22	10.0	C764
39650	P235/55R16	96T	(7.5) 6.5-8.5	44	1565	26.15	9.65	7.95	793	10.5	8.3	24	10.9	C964

COBRA RADIAL G/T raised white letter sizes:

W31-396

+39626	P175/70R13	82T	(5.0) 4.5-6.0	44	1036	22.7	6.74	5.70	916	10.5	8.3	16	7.3	U334
39603	P205/60R13	86T	(6.0) 5.5-7.5	44	1179	22.75	7.86	6.50	914	10.5	8.3	18	8.2	T634
+39630	P185/70R14	87T	(5.5) 4.5-6.0	44	1201	24.27	7.35	5.90	857	10.5	8.3	18	8.2	U444
+39631	P195/70R14	90T	(6.0) 5.0-6.5	44	1312	24.75	7.85	6.30	840	10.5	8.3	19	8.6	U544
39632	P205/70R14	93T	(6.0) 5.0-7.0	44	1433	25.3	8.21	6.50	822	10.5	8.3	21	9.5	U644
39633	P215/70R14	96T	(6.5) 5.5-7.0	44	1554	25.76	8.66	7.00	807	10.5	8.3	22	10.0	U744
39634	P225/70R14	98T	(6.5) 6.0-7.5	44	1675	26.27	8.92	7.20	792	10.5	8.3	24	10.9	U844
+39604	P195/60R14	85T	(6.0) 5.5-7.0	44	1135	23.28	7.62	6.40	893	10.5	8.3	18	8.2	T544
39606	P215/60R14	91T	(6.5) 6.0-7.5	44	1345	24.16	8.42	7.00	861	10.5	8.3	21	9.5	T744
+39607	P225/60R14	94T	(6.5) 6.0-7.5	44	1455	24.57	8.70	7.20	846	10.5	8.3	22	10.0	T844
39608	P235/60R14	96T	(7.0) 6.5-8.0	44	1565	25.06	9.11	7.60	830	10.5	8.3	24	10.9	T944
+39609	P245/60R14	98T	(7.0) 7.0-8.0	44	1675	25.50	9.41	8.00	815	10.5	8.3	26	11.8	T044
39635	P215/70R15	97T	(6.5) 5.5-7.0	44	1620	26.71	8.71	7.00	778	10.5	8.3	23	10.4	U754
39636	P225/70R15	100T	(6.5) 6.0-7.5	44	1753	27.37	8.71	7.20	760	10.5	8.3	25	11.3	U854
39637	P235/70R15	102T	(7.0) 6.0-8.0	44	1896	27.90	9.46	7.60	745	10.5	8.3	27	12.2	U954
39638	P255/70R15	108T	(7.5) 6.5-8.5	44	2183	28.95	10.40	8.20	718	10.5	8.3	31	14.1	UX54
39616	P215/65R15	95T	(6.5) 6.0-7.5	44	1510	26.00	8.38	6.80	799	10.5	8.3	22	10.0	S754
+39610	P195/60R15	87T	(6.0) 5.5-7.0	44	1190	24.30	7.60	6.40	856	10.5	8.3	19	8.6	T554
39611	P215/60R15	93T	(6.5) 6.0-7.5	44	1411	25.16	8.44	7.00	827	10.5	8.3	22	10.0	T754
39612	P235/60R15	98T	(7.0) 6.5-8.0	44	1642	26.11	9.15	7.60	796	10.5	8.3	25	11.3	T954
39613	P245/60R15	100T	(7.0) 7.0-8.0	44	1753	26.55	9.47	8.00	783	10.5	8.3	27	12.2	T054
39614	P255/60R15	102T	(7.5) 7.0-8.5	44	1885	27.01	9.73	8.20	769	10.5	8.3	28	12.7	TX54
39615	P275/60R15	107T	(8.0) 7.5-9.0	44	2149	28.06	10.70	8.90	741	10.5	8.3	31	14.1	TY54
39601	P265/50R15	99S	(8.5) 7.5-9.5	35	1720	25.63	10.51	8.80	811	10.5	8.3	27	12.2	ZV54
39602	P295/50R15	105S	(9.5) 8.0-10.0	35	2061	26.80	11.77	10.10	775	10.5	8.3	32	14.5	ZZ54
39605	P295/50R16	107S	(9.5) 8.0-10.0	44	2149	27.69	11.93	10.05	752	10.5	8.3	36	16.3	ZZ64
39629	P275/60R17	110T	(8.0) 7.5-9.5	44	2337	29.98	11.02	8.95	694	10.5	8.3	37	16.8	TY74

Notes: 2, 6, 7

+ Discontinued - Limited Availability

^ Limited Availability



COOPERTIRES

WINTER TIRES



WEATHER-MASTER S/T²

Winter
13-14



DISCOVERER M+S

Winter
15-16

WEATHER-MASTER S/T²

T/S-Speed Rated
Studdable



High Traction Tread Design

The intricate tread pattern balances winter traction and a smooth, quiet ride. The deep lateral and notched circumferential grooves provide excellent evacuation of water and slush from the tread contact patch.

Patented "Snow-Groove" Design

Provides biting edges for excellent snow and ice traction without reducing element stiffness. Enhances the retention of snow in the outer circumferential grooves to capitalize on the higher traction characteristics of snow on snow versus snow on rubber.


Enhanced Studded Performance

A new stud pin hole design improves stud retention and the number has been increased allowing for the use of a greater number of studs for better traction on ice. The stud size is conveniently molded into the sidewall for easy reference.

M+S Rated



S.D.



PSI



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
WEATHER-MASTER S/T² white sidewall (.50") size:											WH1-3ET		
02601	155/80R13 79S	(4.5) 4.0-5.0	35	963	23.00	6.10	4.10	901	13 10.3	12 9-11	14 6.4	M134	
WEATHER-MASTER S/T² white sidewall (.65") sizes:											W81-3ET		
02605	185/75R14 89S	(5.0) 4.5-6.0	35	1279	25.10	7.20	5.00	826	13.5 10.7	12 9-11	18 8.2	V444	
02606	195/75R14 92S	(5.5) 5.0-6.5	35	1389	25.65	7.60	5.20	808	13.5 10.7	12 9-11	19 8.6	V544	
02607	205/75R14 95S	(5.5) 5.0-7.0	35	1521	26.20	7.95	5.60	791	14 11.1	13 9-11	21 9.5	V644	
+02608	215/75R14 100S	(6.0) 5.5-7.0	35	1764	26.80	8.40	5.80	774	14 11.1	13 9-11	23 10.4	V744	
02614	205/70R14 95S	(6.0) 5.0-7.0	35	1521	25.40	8.05	5.80	816	13 10.3	12 9-11	20 9.1	R644	
02615	215/70R14 96S	(6.5) 5.5-7.0	35	1565	25.90	8.50	6.15	801	13 10.3	12 9-11	22 10.0	R744	
WEATHER-MASTER S/T² white sidewall (.75") sizes:											WK1-3ET		
02609	205/75R15 97S	(5.5) 5.0-7.0	35	1609	27.20	7.95	5.60	762	14 11.1	13 9-11	22 10.0	V654	
02610	215/75R15 100S	(6.0) 5.5-7.0	35	1764	27.80	8.40	5.80	746	14 11.1	13 9-11	24 10.9	V754	
02611	225/75R15 102S	(6.0) 6.0-7.5	35	1874	28.30	8.70	6.10	733	14 11.1	13 9-11	26 11.8	V854	
02612	235/75R15 105S	(6.5) 6.0-8.0	35	2039	28.90	9.10	6.40	717	14.5 11.5	13 9-11	27 12.2	V954	
02616	205/70R15 96S	(6.0) 5.0-7.0	35	1565	26.40	8.00	5.80	785	13 10.3	12 9-11	21 9.5	R654	
02617	215/70R15 98S	(6.5) 5.5-7.0	35	1653	26.90	8.40	6.15	771	13 10.3	12 9-11	23 10.4	R754	
02618	225/70R15 100S	(6.5) 6.0-7.5	35	1764	27.40	8.70	6.40	757	13 10.3	12 9-11	25 11.3	R854	

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability



WEATHER-MASTER S/T²



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	---------------	---------------	-------------	---------------	----------------------------------	--------------------	-----------------------	-----------	-------

WEATHER-MASTER S/T² black sidewall sizes:

W11-3ET

02625	155/70R13	75S	(4.5) 4.0-5.0	44	853	21.67	5.96	4.95	960	13.0	10.3	12	9-11	14	6.4	R134
02620	175/70R13	82S	(5.0) 4.5-6.0	35	1047	22.90	6.80	5.05	905	13.0	10.3	12	9-11	15	6.8	R334
+02621	185/70R13	86S	(5.5) 4.5-6.0	35	1168	23.45	7.30	5.30	884	13.0	10.3	12	9-11	16	7.3	R434
+02613	175/80R14	88S	(5.0) 4.5-6.0	44	1235	25.01	7.04	5.37	830	13.0	10.3	12	9-11	19	8.6	M344
02622	175/70R14	84S	(5.0) 4.5-6.0	35	1102	23.90	6.80	5.05	867	13.0	10.3	12	9-11	17	7.7	R344
02623	185/70R14	88S	(5.5) 4.5-6.0	35	1235	24.45	7.45	5.30	848	13.0	10.3	12	9-11	18	8.2	R444
02624	195/70R14	91S	(6.0) 5.0-6.5	35	1356	25.00	7.75	5.60	829	13.0	10.3	12	9-11	18	8.2	R544
02627	165/65R14	79T	(5.0) 4.5-6.0	44	963	22.39	6.67	5.25	927	13.0	10.3	12	9-11	19	8.6	F244
02641	175/65R14	82T	(5.0) 5.0-6.0	44	1047	23.10	6.85	5.20	898	13.0	10.3	12	9-11	16	7.3	F344
02642	185/65R14	86T	(5.5) 5.0-6.5	44	1168	23.55	7.35	5.57	880	13.0	10.3	12	9-11	17	7.7	F444
+02643	195/65R14	89T	(6.0) 5.5-7.0	44	1279	24.00	7.85	5.95	864	13.0	10.3	12	9-11	18	8.2	F544
+02631	185/60R14	82T	(5.5) 5.0-6.5	44	1047	22.85	7.30	5.70	907	13.0	10.3	12	9-11	18	8.2	E444
02632	195/60R14	86T	(6.0) 5.5-7.0	44	1168	23.30	7.82	6.05	890	13.0	10.3	12	9-11	19	8.6	E544
02651	185/65R15	88T	(5.5) 5.0-6.5	44	1235	24.51	7.55	5.77	846	13.0	10.3	12	9-11	19	8.6	F454
02652	195/65R15	91T	(6.0) 5.5-7.0	44	1356	25.00	7.85	6.09	829	13.0	10.3	12	9-11	20	9.1	F554
02629	195/65R15RE	95T	(6.0) 5.5-7.0	50	1521	25.00	7.85	6.09	829	13.0	10.3	12	9-11	22	10.0	F556
02653	205/65R15	94T	(6.0) 5.5-7.5	44	1477	25.45	8.02	6.05	815	13.0	10.3	12	9-11	22	10.0	F654
02630	205/65R15RE	99T	(6.0) 5.5-7.5	50	1709	25.45	8.02	6.05	815	13.0	10.3	12	9-11	23	10.4	F656
02654	215/65R15	96T	(6.5) 6.0-7.5	44	1565	25.98	8.55	6.50	798	13.0	10.3	12	9-11	24	10.9	F754
02634	185/60R15	84T	(5.5) 5.0-6.5	44	1102	23.88	7.44	5.75	871	13.0	10.3	12	9-11	19	8.6	E454
02635	195/60R15	88T	(6.0) 5.5-7.0	44	1235	24.30	7.80	6.05	853	13.0	10.3	12	9-11	21	9.5	E554
02636	205/60R15	91T	(6.0) 5.5-7.5	44	1356	24.75	8.15	6.35	838	13.0	10.3	12	9-11	22	10.0	E654
02637	215/60R15	94T	(6.5) 6.0-7.5	44	1477	25.21	8.60	6.70	822	13.0	10.3	12	9-11	23	10.4	E754
+02663	185/55R15	82T	(6.0) 5.0-6.5	44	1047	23.28	7.57	6.14	893	13.0	10.3	12	9-11	19	8.6	G454
02664	195/55R15	85T	(6.0) 5.5-7.0	44	1135	23.75	7.91	6.13	876	13.0	10.3	12	9-11	20	9.1	G554
02665	205/55R15	88T	(6.5) 5.5-7.5	44	1235	24.14	8.38	6.68	861	13.0	10.3	12	9-11	21	9.5	G654
02646	205/65R16	95T	(6.0) 5.5-7.5	44	1521	26.45	8.02	6.20	790	13.0	10.3	12	9-11	23	10.4	F664
02655	215/65R16	98T	(6.5) 6.0-7.5	44	1653	26.98	8.55	6.50	768	13.0	10.3	12	9-11	26	11.8	F764
*02648	235/65R16	103T	(7.0) 6.5-8.5	44	1929	27.94	9.56	7.37	742	13.0	10.3	12	9-11	27	12.2	F964
02660	205/60R16	92T	(6.0) 5.5-7.5	44	1389	25.77	8.33	6.48	807	13.0	10.3	12	9-11	23	10.4	E664
02639	215/60R16	95T	(6.5) 6.0-7.5	44	1521	26.15	8.50	6.50	793	13.0	10.3	12	9-11	24	10.9	E764
02640	225/60R16	98T	(6.5) 6.0-8.0	44	1653	26.57	8.75	6.70	780	13.0	10.3	12	9-11	25	11.3	E864
02644	235/60R16	100T	(7.0) 6.5-8.5	44	1764	26.96	9.45	7.28	771	13.0	10.3	12	9-11	28	12.7	E964
02661	205/55R16	91T	(6.5) 5.5-7.5	44	1356	24.80	8.35	7.00	836	13.0	10.3	12	9-11	23	10.4	G664
02662	215/55R16RE	97T	(7.0) 6.0-7.5	44	1609	25.35	8.90	7.39	819	13.0	10.3	12	9-11	25	11.3	G766
02667	205/50R16	87T	(6.5) 5.5-7.5	44	1201	24.27	8.34	6.96	856	13.0	10.3	12	9-11	21	9.5	H664
02668	225/50R16	92T	(7.0) 6.0-8.0	44	1389	25.10	9.17	7.89	827	13.0	10.3	12	9-11	25	11.3	H864
*02647	215/65R17	99T	(6.5) 6.0-7.5	44	1709	27.72	9.14	6.78	751	13.0	10.3	12	9-11	28	12.7	F774
*02628	215/60R17	96T	(6.5) 6.0-7.5	44	1565	27.24	9.03	6.96	762	13.0	10.3	12	9-11	26	11.8	E774
*02633	225/60R17	99T	(6.5) 6.0-8.0	44	1709	27.72	9.14	7.18	751	13.0	10.3	12	9-11	28	12.7	E874
*02649	215/55R17	94T	(7.0) 6.0-7.5	44	1477			7.39		13.0	10.3					G774
02675	225/55R17	97T	(7.0) 6.0-8.0	44	1609	26.88	9.20	7.49	774	13.0	10.3	12	9-11	28	12.7	G874
02676	235/55R17	99T	(7.5) 6.5-8.5	44	1709	27.22	9.79	7.83	764	13.0	10.3	12	9-11	31	14.1	G974
02666	215/50R17	91T	(7.0) 6.0-7.5	44	1356	25.69	8.82	7.35	808	13.0	10.3	12	9-11	25	11.3	H774
02669	225/45R17RE	94T	(7.5) 7.0-8.5	50	1477	25.09	9.03	7.78	828	13.0	10.3	12	9-11	27	12.2	J876
02670	235/45R17	94T	(8.0) 7.5-9.0	44	1477	25.53	9.30	8.17	814	13.0	10.3	12	9-11	28	12.7	J974
*02645	225/60R18	100T	(6.5) 6.0-8.0	44	1764	26.57	8.75	7.18	780	13.0	10.3	12	9-11	24	10.9	E884

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability

* Availability Winter Season '07



DISCOVERER M+S



S-Speed Rated
Studdable

"D-Squared" Sipe Technology

Further enhances winter performance while maintaining excellent wet traction. The sipes are deep and dense to provide performance benefits throughout the life of the tire.

Patented "Snow-Groove" Design

Provides biting edges for excellent snow and ice traction without reducing element stiffness. Enhances the retention of snow in the outer circumferential grooves to capitalize on the higher traction characteristics of snow on snow versus snow on rubber.


Sawtooth Center Circumferential Rib & Blocky Tread

Enhances stability and even treadwear in all types of weather conditions.

M+S Rated



s.D.



PSI



P



LT



Overall Diam.



Section Width



Tread Width



Rev. Per Mile



Tread Depth



Stud Size



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------------	-----------------	---------------	---------------	-------------	---------------	----------------------------------	--------------------	-----------------------	-----------	-------

DISCOVERER M+S black sidewall sizes:

W11-3CT

50471	225/70R14 99S	(6.5) 6.0-7.5	35	1709	1554	26.25	9.10	7.00	790	15.0	11.9	13	9-12	27	12.2	R844	
50444	235/75R15 105S	(6.5) 6.0-8.0	35	2039	1854	29.00	9.60	7.20	717	15.0	11.9	13	9-12	32	14.5	V954	
50445	235/75R15RE 109S	(6.5) 6.0-7.5	41	2271	2065	29.00	9.40	7.20	717	15.0	11.9	13	9-12	33	15.0	V956	
50447	265/75R15 112S	(7.5) 7.0-9.0	35	2469	2245	30.60	10.65	8.10	679	15.0	11.9	13	9-12	37	16.8	VV54	
50475	235/70R15 103S	(7.0) 6.0-7.5	35	1929	1754	28.00	9.65	7.40	746	15.0	11.9	13	9-12	30	13.6	R954	
50478	265/70R15 112S	(8.0) 7.0-9.0	35	2469	2245	29.43	10.45	8.00	707	15.0	11.9	13	9-12	35	15.9	RV54	
+50443	215/75R16 103S	(6.0) 5.5-7.0	44	1929	1754	28.66	8.47	6.80	725	15.0	11.1	13	9-12	31	14.1	V764	
50448	225/75R16 104S	(6.0) 6.0-7.5	35	1984	1804	29.18	8.65	6.80	713	15.0	11.9	13	9-12	31	14.1	V864	
50449	235/75R16 108S	(6.5) 6.0-8.0	35	2205	2005	29.85	9.30	7.00	697	15.0	11.9	13	9-12	34	15.4	V964	
50450	245/75R16 111S	(7.0) 6.5-8.0	35	2403	2185	30.40	9.60	7.40	683	15.0	11.9	13	9-12	35	15.9	V064	
50451	265/75R16 116S	(7.5) 7.0-9.0	35	2756	2505	31.60	10.60	8.10	658	15.0	11.9	13	9-12	39	17.7	VV64	
50480	215/70R16 100S	(6.5) 5.5-7.0	35	1764	1604	27.75	8.80	7.20	753	15.0	11.9	13	9-12	30	13.6	R764	
50481	225/70R16 102S	(6.5) 6.0-7.5	35	1874	1704	28.30	9.00	7.00	733	15.0	11.9	13	9-12	30	13.6	R864	
50482	235/70R16 106S	(7.0) 6.0-7.5	35	2094	1904	28.85	9.40	7.40	719	15.0	11.9	13	9-12	32	14.5	R964	
50483	245/70R16 107S	(7.0) 6.5-8.0	35	2149	1954	29.50	9.85	7.70	705	15.0	11.9	13	9-12	34	15.4	R064	
50484	255/70R16 111S	(7.5) 6.5-8.0	35	2403	2185	29.90	10.30	8.00	693	15.0	11.9	13	9-12	35	15.9	RX64	
50485	265/70R16 112S	(8.0) 7.0-9.0	35	2469	2245	30.40	10.80	8.00	682	15.0	11.9	13	9-12	39	17.7	RV64	
50486	245/70R17 110S	(7.0) 6.5-8.0	44	2337	2125	30.50	9.85	7.70	681	14.0	11.1	13	9-12	35	15.9	R074	
50488	265/70R17 115S	(8.0) 7.0-9.0	35	2679	2435	31.40	10.65	8.30	660	15.0	11.9	13	9-12	40	18.1	RV74	
50495	255/60R17 106S	(7.5) 7.0-9.0	44	2094	1904	29.06	10.29	8.80	715	14.0	11.1	13	9-12	36	16.3	EX74	
50498	255/55R18RE 109S	(8.0) 7.0-9.0	50	2271	2065	29.12	10.36	8.90	713	14.0	11.1	13	9-12	41	18.6	GX86	
50499	275/60R20RE 119S	(8.5) 8.0-9.5	50	2998	2725	33.08	12.69	9.22	628	14.0	11.1	13	9-12	50	22.7	EY06	

DISCOVERER M+S outline white letter sizes:

WL1-3CT

50490	255/65R16 109S	(7.5) 7.0-9.0	35	2271	2065	29.18	10.24	8.25	718	14.0	11.1	13	9-12	36	16.3	FX64	
50493	235/65R17 104S	(7.0) 6.5-8.5	35	1984	1804	29.11	9.45	7.65	716	14.0	11.1	13	9-12	33	15.0	F974	
50494	245/65R17 107S	(7.0) 7.0-8.5	35	2149	1954	29.52	9.82	9.27	708	14.0	11.1	13	9-12	36	16.3	F074	
50496	275/60R17 110S	(8.0) 7.5-9.5	35	2337	2125	30.10	11.20	9.02	699	14.0	11.1	13	9-12	39	17.7	EY74	

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability



DISCOVERER M+S



M+S Rated

**Q-Speed Rated
Studdable**

"D-Squared" Sipe Technology

Further enhances winter performance while maintaining excellent wet traction. The sipes are deep to provide performance benefits throughout the life of the tire.

Patented "Snow-Groove" Design

Provides biting edges for excellent snow and ice traction without reducing element stiffness. Enhances the retention of snow in the outer circumferential grooves to capitalize on the higher traction characteristics of snow on snow versus snow on rubber.

Sawtooth Center Circumferential Rib & Blocky Tread

Enhances stability and even treadwear in all types of weather conditions.



S.D.



PSI



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	--------------------	-----------------------	-----------	-------

DISCOVERER M+S black sidewall sizes:

W11-5AK

50410	LT235/75R15 C 104/101Q	(6.5) 6.0-7.0	50	1820	1985	28.82	9.00	7.20	10.8	715	17	13.5	15.0	9-13	34	15.4	W956	
50414	31X10.50R15LT C 109Q	(8.5) 7.0-9.0	50	---	2270	30.25	10.50	8.20	---	685	19	15.1	15.0	9-13	40	18.1	3056	
50422	LT215/85R16 E 115/112Q	(6.0) 5.5-7.0	80	2470	2680	30.28	9.10	5.90	9.9	684	17	13.5	15.0	9-13	38	17.2	Y760	
50424	LT235/85R16 E 120/116Q	(6.5) 6.0-7.0	80	2778	3042	31.78	9.31	6.94	10.8	654	17	13.5	15.0	9-13	43	19.5	Y960	
50431	LT225/75R16 E 115/112Q	(6.0) 6.0-7.0	80	2470	2680	29.30	8.95	6.70	10.2	710	17	13.5	15.0	9-13	39	17.7	W860	
50434	LT245/75R16 C 108/104Q	(7.0) 6.5-7.5	50	2006	2205	30.44	9.57	7.45	11.3	680	17	13.5	15.0	9-13	41	18.6	W066	
50432	LT245/75R16 E 120/116Q	(7.0) 6.5-7.5	80	2778	3042	30.44	9.57	7.45	11.3	680	18	14.3	15.0	9-13	45	20.4	W060	
50435	LT265/75R16 C 112/109Q	(7.5) 7.0-8.0	50	2270	2470	31.54	10.33	8.14	12.2	654	17	13.5	15.0	9-13	44	20.0	W166	
50437	LT265/75R16 E 123/120Q	(7.5) 7.0-8.5	80	3085	3415	31.54	10.50	8.14	12.2	654	17	13.5	15.0	9-13	49	22.2	W160	
50419	LT235/80R17 E 120/117Q	(6.5) 6.0-8.0	80	2835	3085	31.85	9.40	7.00	10.8	652	17	13.5	15.0	9-13	45	20.4	X970	
50416	LT245/70R17 E 119/116Q	(7.0) 6.5-8.0	80	2755	3000	30.45	9.40	7.45	10.8	652	17	13.5	15.0	9-13	44	20.0	U070	
50417	LT265/70R17 E 121/118Q	(8.0) 7.0-9.0	80	2910	3195	31.65	11.03	8.40	12.4	656	17	13.5	15.0	9-13	50	22.7	U170	
50418	LT275/70R17 C 114/110Q	(8.0) 7.0-9.0	50	2335	2600	32.20	11.32	8.80	12.8	645	17	13.5	15.0	9-13	48	21.8	UY76	

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 2, 3, 5, 6, 7



SUV/LIGHT TRUCK TIRES



ZEON XST
Sport Truck
18

DISCOVERER SPORT HP
SUV/Light Truck
19

DISCOVERER H/T PLUS
SUV/Light Truck
20

DISCOVERER H/T
SUV/Light Truck
21-22

DISCOVERER ATR
SUV/Light Truck
23-24



DISCOVERER RADIAL LT
SUV/Light Truck
25

SRM II RADIAL LT
SUV/Light Truck
26

DISCOVERER AST II
SUV/Light Truck
27

DISCOVERER RADIAL AST
SUV/Light Truck
28



DISCOVERER S/T
SUV/Light Truck
29-30

DISCOVERER ST-C
SUV/Light Truck
31

DISCOVERER STT
SUV/Light Truck
32

SUPER ROAD SERVICE
SUV/Light Truck
33

COURSER TRACTION LT
SUV/Light Truck
34

ZEON XST



V/H-Speed Rated Directional Design

Performance Reinforced Tread Compound

The tread compound is specifically engineered to optimize all-around tire performance. This compound's unique polymer system provides solid wet and dry traction and allows ample snow capability.

Performance Apex

The hardened rubber compound, or bead filler, above the bead minimizes sidewall flex in cornering. The result is crisp handling.

Rim Protector

A rubber rim protector extends beyond the rim flange and decreases the chance of rim damage that can occur if a tire/wheel assembly scuffs a curb.

M+S Rated

	TREADWEAR	TRACTION	TEMPERATURE
UTQG	420	A	A



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{hds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

ZEON XST black sidewall sizes: V-Rated

W11-4JY

04058	285/60R18	116V	(8.5) 8.0-10.0	44	2756	31.33	11.73	9.66	644	12.0	9.5	45	20.4	ER84
04061	255/55R18XL	109V	(8.0) 7.0-9.0	50	2271	29.00	10.20	8.85	696	12.0	9.5	42	19.1	GX86
04066	285/55R18	113V	(9.0) 8.0-10.0	44	2535	30.20	11.25	9.94	668	12.0	9.5	44	20.0	GR84
04097	275/45R22XL	112V	(9.0) 8.5-10.0	50	2469	31.64	10.97	10.71	657	12.0	9.5	46	20.9	JY26
04076	285/45R22XL	114V	(9.5) 9.0-10.0	50	2601	32.09	11.22	11.15	609	12.0	9.5	48	21.8	JR26
04088	305/45R22XL	118V	(10.0) 9.5-11.0	50	2910	32.80	11.93	10.74	636	12.0	9.5	52	23.6	JA26
04089	305/40R22XL	114V	(11.0) 10.0-12.0	50	2601	31.61	12.32	11.17	657	12.0	9.5	48	21.8	KA26
+04091	325/40R22XL	118V	(12.0) 11.0-13.0	50	2910	32.24	13.23	12.17	645	12.0	9.5	55	24.9	KC26
04078	245/35R22XL	97V	(8.5) 8.0-9.5	50	1609	28.78	9.76	9.10	722	12.0	9.5	32	14.5	L026
04077	265/35R22XL	102V	(9.5) 9.0-10.0	50	1874	29.33	10.67	10.84	708	12.0	9.5	36	16.3	LV26
04075	295/30R22XL	103V	(10.0) 10.0-12.0	50	1929	29.02	11.65	10.56	719	12.0	9.5			3Z26
+04090	305/40R23XL	115V	(11.0) 10.0-12.0	50	2679	32.60	12.32	11.21	638	12.0	9.5	53	24.0	KA36
+04093	305/35R23XL	111V	(11.0) 10.0-12.0	50	2403	31.42	12.32	11.33	662	12.0	9.5	50	22.7	LA36
04092	295/40R24XL	114V	(11.0) 10.0-12.0	50	2601	33.31	11.65	10.60	624	12.0	9.5	52	23.6	KZ46
04096	295/35R24XL	110V	(11.0) 10.0-12.0	50	2337	32.13	11.65	10.60	611	12.0	9.5	48	21.8	LZ46
04094	305/35R24XL	112V	(11.0) 10.0-12.0	50	2469	32.30	12.81	11.33	644	12.0	9.5	48	21.8	LA46
04095	315/35R24XL	114V	(11.0) 10.0-12.0	50	2601	32.68	12.60	11.47	636	12.0	9.5	52	23.6	LB46
*04074	285/30R24XL	103V												3R46

ZEON XST black sidewall sizes: H-Rated

W11-4FX

^04005	265/60R18RE	114H	(8.0) 7.5-9.5	50	2601	30.40	10.65	8.99	664	12.0	9.5	45	20.4	EV86
04021	285/50R20RE	116H	(9.0) 8.0-10.0	50	2756	31.13	11.92	9.93	648	12.0	9.5	49	22.2	HR06
04023	305/50R20RE	120H	(9.5) 8.5-11.0	50	3086	31.92	12.69	10.57	632	12.0	9.5	54	24.5	HA06
04032	275/45R20RE	110H	(9.0) 8.5-10.0	50	2337	29.64	10.97	9.25	680	12.0	9.5	44	20.0	JY06
04034	295/45R20RE	114H	(10.0) 9.5-11.0	50	2601	30.35	11.88	9.91	665	12.0	9.5	49	22.2	JZ06
04035	305/45R20RE	116H	(10.0) 9.5-11.0	50	2756	30.66	12.17	10.26	658	12.0	9.5	49	22.2	JA06

Notes: 1, 2, 6, 7

+ Discontinued - Limited Availability

^ Limited Availability

* Availability To Be Announced



DISCOVERER SPORT HP



V/H-Speed Rated
Directional Design

Cool Running Under Tread
Minimizes heat in the belts.

Tall Sidewall Stiffener
Reduces the wallowing feeling often felt on corners by drivers of 4 x 4 vehicles, together with quicker steering response.

Opti-Noise Technology
Total noise produced at highway speed is reduced by design of the tire pattern.

M+S Rated

TREADWEAR	TRACTION	TEMPERATURE
UTQG	260	AA
		A



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER SPORT HP black sidewall sizes: V-Rated

W11-4FN

03020	235/65R17	104V	(7.0) 6.5-8.5	44	1984	29.20	9.65	7.70	712	12.0	9.5	34	15.4	F974	
03025	275/55R17	109V	(8.5) 7.5-9.5	44	2271	29.05	10.88	9.50	716	12.0	9.5	38	17.2	GY74	

DISCOVERER SPORT HP black sidewall sizes: H-Rated

W11-4EE

^03037	225/70R15	100H	(6.5) 6.0-7.5	44	1764	27.33	9.16	7.18	738	12.0	9.5	30	13.6	R854	
03039	265/70R15	112H	(8.0) 7.0-9.0	44	2469	29.53	10.92	8.89	683	12.0	9.5	37	16.8	RV54	
02705	215/70R16	100H	(6.5) 5.5-7.0	44	1764	28.00	8.90	6.91	743	12.0	9.5	29	13.2	R764	
03041	235/70R16	106H	(7.0) 6.0-8.0	44	2094	28.86	9.64	7.65	699	12.0	9.5	34	15.4	R964	
03042	245/70R16	107H	(7.0) 6.5-8.0	44	2149	29.41	9.96	7.91	686	12.0	9.5	35	15.9	R064	
03044	265/70R16	112H	(8.0) 7.0-9.0	44	2469	30.51	10.92	8.89	661	12.0	9.5	40	18.1	RV64	
03045	275/70R16	114H	(8.0) 7.0-9.0	44	2601	31.06	11.20	9.12	649	12.0	9.5	41	18.6	RY64	
02710	215/65R16	98H	(6.5) 6.0-7.5	44	1653	27.19	8.86	7.09	766	12.0	9.5	29	13.2	F764	
03015	255/65R16	109H	(7.5) 7.0-9.0	44	2271	28.94	10.44	8.69	697	12.0	9.5	36	16.3	FX64	
02715	235/60R16	100H	(7.0) 6.5-8.5	44	1764	27.23	9.36	7.85	764	12.0	9.5	29	13.2	E964	
^02720	235/65R17	104H	(7.0) 6.5-8.5	44	1984	29.20	9.65	7.70	712	12.0	9.5	34	15.4	F974	
^02725	275/55R17	109H	(8.5) 7.5-9.5	44	2271	29.05	10.88	9.50	716	12.0	9.5	38	17.2	GY74	

Notes: 1, 2, 6, 7
^ Limited Availability



DISCOVERER H/T PLUS

*T/S-Speed Rated



Optimized Pitch Sequence

Industry-wide, typically, the same pitch sequence is applied throughout a tire line. But the Discoverer H/T Plus varies the number of shoulder elements based on tire size, which reduces noise frequency, allowing a quiet ride in large diameter sizes.

All-Weather Tread

"See-through" grooves, wide, lateral traction slots and high sipe density provide excellent all-weather performance.

Rim Protector

A rubber rim protector extends beyond the rim flange and decreases the chance of rim damage that can occur if a tire/wheel assembly scuffs a curb.

M+S Rated

TREADWEAR **460** TRACTION **A** TEMPERATURE **B**



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------	------------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER H/T PLUS black sidewall sizes:

W11-4GX

#19910	265/60R18RE	114S	(8.0) 7.5-9.5	50	2601	30.39	10.92	8.99	664	12.0	9.5	44	20.0	EV86
#19913	285/60R18	116S	(8.5) 8.0-10.0	44	2756	31.33	11.73	9.66	644	12.0	9.5	44	20.0	ER84
#19915	255/55R18RE	109S	(8.0) 7.0-9.0	50	2271	28.99	10.36	8.85	698	12.0	9.5	41	18.6	GX86
+19918	285/55R18	113S	(9.0) 8.0-10.0	44	2535	30.23	11.93	9.94	667	12.0	9.5	42	19.1	GR84
#19920	275/60R20RE	119S	(8.0) 7.5-9.5	50	2998	32.99	10.98	9.22	632	12.0	9.5	48	21.8	EY06
#19922	275/55R20RE	117S	(8.5) 7.5-9.5	50	2833	31.95	11.00	9.50	652	12.0	9.5	47	21.3	GY06
#19924	285/50R20RE	116S	(9.0) 8.0-10.0	50	2756	31.13	11.92	9.93	648	12.0	9.5	47	21.3	HR06
#19926	305/50R20RE	120S	(9.5) 8.5-11.0	50	3086	32.05	12.44	10.57	648	12.0	9.5	52	23.6	HA06
#19927	275/45R20RE	110S	(9.0) 8.5-10.0	50	2337	29.64	10.97	9.25	680	12.0	9.5	41	18.6	JY06
+19928	295/45R20RE	114S	(10.0) 9.5-11.0	50	2601	30.35	11.88	9.91	665	12.0	9.5	47	21.3	JZ06
+19929	305/45R20RE	116S	(10.0) 9.5-11.0	50	2756	30.66	12.17	10.26	658	12.0	9.5	48	21.8	JA06

DISCOVERER H/T PLUS black sidewall sizes:

W11-4KX

*19931	265/60R18XL	114T	(8.0) 7.5-9.5	50	2601	30.39	10.92	8.99	664	12.0	9.5	44	20.0	EV86
*19930	285/60R18	116T	(8.5) 8.0-10.0	44	2756	31.33	11.73	9.66	644	12.0	9.5	44	20.0	ER84
*19934	255/55R18XL	109T	(8.0) 7.0-9.0	50	2271	28.99	10.36	8.85	698	12.0	9.5	41	18.6	GX86
*19932	275/60R20XL	119T	(8.0) 7.5-9.5	50	2998	32.99	10.98	10.54	632	12.0	9.5	48	21.8	EY06
*19935	275/55R20XL	117T	(8.5) 7.5-9.5	50	2833	31.95	11.00	9.50	652	12.0	9.5	47	21.3	GY06
*19937	285/50R20XL	116T	(9.0) 8.0-10.0	50	2756	31.13	11.92	9.93	648	12.0	9.5	47	21.3	HR06
*19936	305/50R20XL	120T	(9.5) 8.5-11.0	50	3086	32.05	12.44	10.57	648	12.0	9.5	52	23.6	HA06
*19939	275/45R20XL	110T	(9.0) 8.5-10.0	50	2337	29.64	10.97	9.25	680	12.0	9.5	41	18.6	JY06

Notes: 1, 2, 6, 7

To be replaced by T-Rated

+ Discontinued - Limited Availability

* Availability To Be Announced



DISCOVERER H/T

H/T/S-Speed Rated



Four Wide, Notched Circumferential Grooves

Offers resistance to hydroplaning, while improving snow traction.

High-Density "Zig-Zag" Sipes

Enhances wet traction and winter performance on snow and ice.

Semi-closed Shoulder Design

Delivers greater rubber density on the road, reducing shoulder wear and noise.

M+S Rated

UTQG

SERIES TREADWEAR TRACTION TEMPERATURE

H-RATED	440	A	A
OTHER	520	A	B



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------------	-----------------	---------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER H/T black sidewall sizes: H-Rated

W11-4GA

50500	255/65R16 109H	(7.5) 7.0-9.0	44	2271	2065	29.06	10.24	8.25	715	12.0	9.5	32	14.5	FX64	
50501	235/65R17 104H	(7.0) 6.5-8.5	44	1984	1804	29.06	9.45	7.65	715	12.0	9.5	31	14.1	F974	

DISCOVERER H/T black sidewall sizes: S-Rated

W11-3AX

50525	265/70R15 112S	(8.0) 7.0-9.0	35	2469	2245	29.43	10.45	8.00	707	14.0	11.1	35	15.9	RV54	
50539	225/75R16 104S	(6.0) 6.0-7.5	35	1984	1804	29.15	8.65	6.40	711	13.0	10.3	30	13.6	V864	
50544	P245/75R16 109S	(7.0) 6.5-7.5	35	2271	2065	30.35	9.60	7.00	683	13.5	10.7	34	15.4	W064	
50545	215/70R16 100S	(6.5) 5.5-7.0	35	1764	1604	27.75	8.80	7.20	753	13.0	10.3	29	13.2	R764	
50546	245/70R16 107S	(7.0) 6.5-8.0	35	2149	1954	29.40	9.90	7.70	705	13.0	10.3	33	15.0	R064	
50549	265/70R16 112S	(8.0) 7.0-9.0	35	2469	2245	30.40	10.80	8.00	682	13.5	10.7	38	17.2	RV64	
50504	275/65R17 115S	(8.0) 7.5-9.5	44	2679	2435	30.90	11.20	9.30	672	12.0	9.5	39	17.7	FY74	

DISCOVERER H/T outline white letter sizes: T-Rated

WL1-4KE

50502	235/75R15XL 109T	(6.5) 6.0-8.0	50	2271	2065	29.00	9.40	6.85	717	13.0	10.3	33	15.0	V956	
50503	235/70R16 106T	(7.0) 6.0-7.5	44	2094	1904	28.85	9.40	7.40	719	12.5	9.9	33	15.0	R964	

DISCOVERER H/T outline white letter sizes: S-Rated

WL1-3AX

50510	P205/75R15 97S	(5.5) 5.0-6.5	35	1598	1453	27.05	8.10	5.70	764	13.0	10.3	24	10.9	W654	
50511	P215/75R15 100S	(6.0) 5.5-7.0	35	1742	1584	27.60	8.60	5.95	750	13.0	10.3	26	11.8	W754	
50512	P225/75R15 102S	(6.0) 6.0-7.0	35	1874	1704	28.20	8.95	6.20	735	13.0	10.3	27	12.2	W854	
50513	P235/75R15 105S	(6.5) 6.0-7.5	35	2028	1844	28.85	9.30	6.45	719	13.5	10.7	29	13.2	W954	
50517	P265/75R15 112S	(7.5) 7.0-8.5	35	2469	2245	30.50	10.65	7.60	680	14.0	11.1	37	16.8	WV54	
50521	P225/70R15 100S	(6.5) 6.0-7.0	35	1753	1594	27.25	9.10	7.00	761	12.0	9.5	27	12.2	U854	
50522	P235/70R15 102S	(7.0) 6.0-7.5	35	1896	1724	27.80	9.65	7.40	746	12.0	9.5	29	13.2	U954	
50523	P245/70R15 105S	(7.0) 6.5-7.5	35	2028	1844	28.40	9.95	7.60	730	12.0	9.5	30	13.6	U054	
50530	255/70R15 108S	(7.0) 6.5-8.0	44	2205	2005	29.00	10.40	8.00	715	12.0	9.5	33	15	RX54	
50518	225/75R16 104S	(6.0) 6.0-7.5	35	1984	1804	29.15	8.65	6.40	711	13.0	10.3	31	14.1	V864	
50526	P235/75R16 106S	(6.0) 6.0-8.0	35	2094	1904	29.70	9.30	6.90	700	13.5	10.7	33	15.0	W964	
50527	P245/75R16 109S	(7.0) 6.5-7.5	35	2271	2065	30.35	9.60	7.00	683	13.5	10.7	35	15.9	W064	
50529	P265/75R16 114S	(7.5) 7.0-8.5	35	2601	2365	31.50	10.60	7.60	658	14.0	11.1	40	18.1	WV64	
50532	P225/70R16 101S	(6.5) 6.0-7.0	35	1819	1654	28.30	9.00	7.00	733	13.0	10.3	30	13.6	U864	
50534	245/70R16 107S	(7.0) 6.5-8.0	35	2149	1954	29.40	9.90	7.70	705	13.0	10.3	34	15.4	R064	
50535	P255/70R16 109S	(7.5) 6.5-8.0	35	2271	2065	29.95	10.30	8.00	692	13.5	10.7	36	16.3	UX64	
50536	265/70R16 112S	(8.0) 7.0-9.0	35	2469	2245	30.40	10.80	8.00	682	13.5	10.7	38	17.2	RV64	
50528	275/70R16 114S	(8.0) 7.0-9.0	44	2601	2365	31.20	11.00	8.92	669	13.0	10.3	40	18.1	RY64	
50520	255/65R16 109S	(7.5) 7.0-9.0	35	2271	2065	29.06	10.24	8.25	715	12.0	9.5	32	14.5	FX64	
50531	245/70R17 110S	(7.0) 6.5-8.0	44	2337	2125	30.43	9.96	8.16	662	13.0	10.3	35	15.9	R074	
50538	P265/70R17 113S	(8.0) 7.0-8.5	35	2535	2305	31.40	10.65	8.30	660	13.5	10.7	40	18.1	UV74	
50519	235/65R17 104S	(7.0) 6.5-8.5	35	1984	1804	29.06	9.45	7.65	715	12.0	9.5	31	14.1	F974	
50537	245/65R17 107S	(7.0) 7.0-8.5	35	2149	1954	29.45	9.62	7.85	685	12.0	9.5	33	15.0	F074	
50516	275/60R17 110S	(8.0) 7.5-9.5	35	2337	2125	29.88	11.20	10.63	675	12.0	9.5	37	16.8	EY74	

Notes: 1, 2, 4, 6, 7



DISCOVERER H/T

R/Q-Speed Rated



M+S Rated

Four Wide, Notched Circumferential Grooves


Offers resistance to hydroplaning, while improving snow traction.

High-Density "Zig-Zag" Sipes

Enhances wet traction and winter performance on snow and ice.

Semi-Closed Shoulder Design

Delivers greater rubber density on the road, reducing shoulder wear and noise.



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER H/T black sidewall sizes:

W11-505

50594	LT215/85R16 D 110/107Q	(6.0) 5.5-7.0	65	2150	2335	30.35	8.35	6.13	9.9	683	16.0 12.7	37 16.8	Y768	
50595	LT215/85R16 E 115/112Q	(6.0) 5.5-7.0	80	2470	2680	30.26	8.21	6.13	9.9	683	16.0 12.7	39 17.7	Y760	
50597	LT235/85R16 E 120/116Q	(6.5) 6.0-7.0	80	2778	3042	31.65	9.31	6.77	10.8	654	16.0 12.7	43 19.5	Y960	
50575	LT225/75R16 D 110/107Q	(6.0) 6.0-7.0	65	2150	2335	29.35	8.95	6.60	10.2	708	16.0 12.7	37 16.8	W868	
50506	LT225/75R16 E 115/112Q	(6.0) 6.0-7.0	80	2470	2680	29.39	8.95	6.60	10.2	710	16.0 12.7	39 17.7	W860	
50580	LT245/75R16 E 120/116Q	(7.0) 6.5-7.5	80	2778	3042	30.44	9.57	7.45	11.3	680	16.0 12.7	45 20.4	W060	
50589	LT245/70R17 E 119/116R	(7.0) 6.5-8.0	80	2755	3000	30.60	9.56	7.45	11.3	679	16.0 12.7	46 20.9	U070	

DISCOVERER H/T outline white letter sizes:

WL1-505

50551	LT235/75R15 C 104/101Q	(6.5) 6.0-7.0	50	1820	1985	28.83	9.00	6.61	10.8	719	16.0 12.7	34 15.4	W956	
50552	30X9.50R15LT C 104Q	(7.5) 6.5-8.5	50	----	1985	29.25	9.75	7.46	----	708	16.0 12.7	36 16.3	3956	
50553	31X10.50R15LT C 109Q	(8.5) 7.0-9.0	50	----	2270	30.27	11.06	8.50	----	684	16.0 12.7	40 18.1	3056	
50564	LT245/75R16 C 108/104Q	(7.0) 6.5-7.5	50	2006	2205	30.44	9.57	7.45	11.3	680	16.0 12.7	42 19.1	W066	
50567	LT265/75R16 C 112/109Q	(7.5) 7.0-8.0	50	2270	2470	31.60	10.33	7.65	12.2	654	16.0 12.7	44 20.0	W166	
+50568	LT265/75R16 D 119/116Q	(7.5) 7.0-8.0	65	2755	3000	31.61	10.40	7.60	12.2	654	16.0 12.7	45 20.4	W168	
50569	LT265/75R16 E 123/120Q	(7.5) 7.0-8.0	80	3085	3415	31.61	10.40	7.60	12.2	654	16.0 12.7	48 21.8	W160	
50586	LT235/80R17 E 120/117R	(6.5) 6.0-8.0	80	2835	3085	31.65	9.40	6.85	10.8	652	16.0 12.7	44 20.0	X970	
50592	LT265/70R17 E 121/118R	(8.0) 7.0-9.0	80	2910	3195	31.60	10.65	8.50	12.4	656	16.0 12.7	51 23.1	U170	

Notes: 2, 3, 5, 6, 7

+ Discontinued - Limited Availability



DISCOVERER ATR

T/S-Speed Rated



Five-Rib, All Terrain Design

This modern five rib design features a combination of lateral slots and sawtooth circumferential grooves which are wide and deep to provide solid all-terrain performance.

V²Tech Optimized Tire Profile

Using state of the art V²Tech computer aided engineering, an optimum mold profile was designed to provide favorable balance of wear and handling characteristics.

Extensive "Zig-Zag" Siping

The extensive number of sipes on the center rib and tread elements are deep to provide for long, dependable traction in all-weather conditions while the "zig-zag" shape increases the effectiveness of the gripping edges.

M+S Rated

TREADWEAR TRACTION TEMPERATURE

UTQG

500


A

B



S.D.

PSI



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------------	-----------------	---------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER ATR outline white letter sizes:

WL1-4SU

05564	225/70R14	99S	(6.5) 6.0-7.0	44	1709	1554	26.45	8.90	7.05	795	12.5	9.9	26	11.8	R844	
05565	205/75R15	97S	(5.5) 5.0-6.5	44	1609	1463	27.10	7.90	6.00	771	13.5	10.7	24	10.9	V654	
05566	215/75R15	100S	(6.0) 5.5-7.0	44	1764	1604	27.60	8.40	6.40	757	13.5	10.7	26	11.8	V754	
05567	225/75R15	102S	(6.0) 6.0-7.0	44	1874	1704	28.33	8.70	6.65	737	13.5	10.7	27	12.2	V854	
05568	235/75R15	105S	(6.5) 6.0-7.5	44	2039	1854	28.90	9.23	7.00	723	14.0	11.1	30	13.6	V954	
05569	235/75R15XL	109S	(6.5) 6.0-8.0	41	2271	2065	28.90	9.20	7.00	723	14.0	11.1	32	14.5	V956	
05558	265/75R15	112S	(7.5) 7.0-8.5	44	2469	2245	30.69	10.50	8.00	681	14.5	11.5	37	16.8	VV54	
05570	205/70R15	96T	(6.0) 5.0-7.0	44	1565	1423	26.40	8.44	6.50	790	13.5	10.7	24	10.9	R654	
05571	225/70R15	100S	(6.5) 6.0-6.5	44	1764	1604	27.45	9.00	7.05	763	12.5	9.9	27	12.2	R854	
05572	235/70R15	103S	(7.0) 6.0-8.0	44	1929	1754	27.99	9.45	7.40	747	12.5	9.9	29	13.2	R954	
05559	255/70R15	108S	(7.5) 6.5-8.5	44	2205	2005	29.05	10.50	8.05	715	14.0	11.1	34	15.4	RX54	
05560	265/70R15	112S	(8.0) 7.0-9.0	44	2469	2245	29.60	10.60	8.45	706	14.0	11.1	36	16.3	RV54	
05573	225/75R16	104S	(6.0) 6.0-7.5	44	1984	1804	29.25	8.71	6.65	712	13.5	10.7	30	13.6	V864	
05574	235/75R16	108S	(6.5) 6.0-8.0	44	2205	2005	29.84	9.25	7.00	700	14.0	11.1	33	15.0	V964	
05575	245/75R16	111S	(7.0) 6.5-7.5	44	2403	2185	30.52	9.65	7.40	685	14.0	11.1	34	15.4	V064	
05557	265/75R16	116S	(7.5) 7.0-9.0	44	2756	2505	31.65	10.51	8.00	658	14.5	11.5	38	17.2	VV64	
05576	215/70R16	100S	(6.5) 5.5-7.0	44	1764	1604	27.87	8.70	6.85	750	13.5	10.7	29	13.2	R764	
05577	225/70R16	102S	(6.5) 6.0-7.0	44	1874	1704	28.40	8.90	7.05	736	13.5	10.7	30	13.6	R864	
05578	235/70R16	106T	(7.0) 6.0-8.0	44	2094	1904	28.99	9.46	7.43	720	13.5	10.7	33	15.0	R964	
05579	245/70R16	107S	(7.0) 6.5-8.0	44	2149	1954	29.59	9.79	7.70	707	13.5	10.7	33	15.0	R064	
05561	255/70R16	111S	(7.5) 6.5-8.5	44	2403	2185	30.10	10.24	8.00	695	14.0	11.1	36	16.3	RX64	
05555	265/70R16	112T	(8.0) 7.0-9.0	44	2469	2245	30.45	10.90	8.45	682	14.0	11.1	37	16.8	RV64	
05554	235/70R17RE	111S	(7.0) 6.0-8.0	41	2403	2185	29.99	9.46	7.43	697	14.0	11.1	35	15.9	R976	
05580	245/70R17	110S	(7.0) 6.5-8.0	44	2337	2125	30.40	10.10	7.70	683	14.0	11.1	33	15.0	R074	
05581	255/70R17	112S	(7.5) 6.5-8.5	44	2469	2246	31.10	10.24	8.00	671	14.0	11.1	38	17.2	RX74	
05556	265/70R17	115S	(8.0) 7.0-9.0	44	2679	2435	31.60	10.70	8.45	662	14.0	11.1	40	18.1	RV74	
05562	235/65R17	104T	(7.0) 6.5-8.5	44	1984	1804	29.10	9.54	7.65	716	13.5	10.7	33	15.0	F974	
05551	245/65R17	107S	(7.0) 7.0-8.5	44	2149	1954	29.63	9.59	8.00	704	13.5	10.7	34	15.4	F074	
05552	255/65R17	110S	(7.5) 7.0-9.0	44	2337	2125	30.05	9.88	8.45	695	13.5	10.7	36	16.3	FX74	
05563	265/65R17	112T	(8.0) 7.5-9.5	44	2470	2245	30.55	10.71	8.75	682	13.5	10.7	38	17.2	FV74	
05582	235/60R17	102T	(7.0) 6.5-8.5	44	1874	1705	28.40	9.54	7.65	734	14.0	11.1	33	15.0	E974	
05550	265/70R18	116S	(8.0) 7.0-9.0	44	2756	2508	32.60	10.70	8.45	636	14.0	11.1	42	19.1	RV84	
05553	275/55R20RE	117S	(8.5) 7.5-9.5	50	2833	2575	31.92	12.69	9.40	654	13.0	10.3	45	20.4	GY06	

Notes: 1, 2, 4, 6, 7



COOPERTIRES

DISCOVERER ATR

S/R-Speed Rated



M+S Rated

Five-Rib, All Terrain Design

This modern five rib design features a combination of lateral slots and sawtooth circumferential grooves which are wide and deep to provide solid all-terrain performance.

V²Tech Optimized Tire Profile

Using state of the art V²Tech computer aided engineering, an optimum mold profile was designed to provide favorable balance of wear and handling characteristics.

Extensive "Zig-Zag" Siping

The extensive number of sipes on the center rib and tread elements are deep to provide for long, dependable traction in all-weather conditions while the "zig-zag" shape increases the effectiveness of the gripping edges.



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER ATR black sidewall sizes:

W11-5LT

05510	LT215/85R16 E 115/112R	(6.0) 5.5-7.0	80	2470	2680	30.30	9.15	6.00	9.9	686	16.5 13.1	38 17.2	Y760	
05502	LT235/85R16 E 120/116R	(6.5) 6.0-7.0	80	2778	3042	31.78	9.36	6.70	10.8	660	16.5 13.1	42 19.1	Y960	
05517	LT225/75R16 D 110/107R	(6.0) 6.0-7.0	65	2150	2335	29.35	8.90	6.90	10.2	713	16.5 13.1	38 17.2	W868	
05511	LT225/75R16 E 115/112R	(6.0) 6.0-7.0	80	2470	2680	29.39	8.92	6.90	10.2	713	16.5 13.1	38 17.2	W860	
05501	LT245/75R16 E 120/116R	(7.0) 6.5-7.5	80	2778	3042	30.52	9.62	7.40	11.3	688	16.5 13.1	42 19.1	W060	

DISCOVERER ATR outline white letter sizes:

WL1-5LT

05520	LT235/75R15 C 104/101R	(6.5) 6.0-7.0	50	1820	1985	28.90	9.00	7.00	10.8	723	16.0 12.7	35 15.9	W956	
05518	30X9.50R15LT C 104R	(7.5) 6.5-8.5	50	----	1985	29.30	9.30	7.30	----	711	16.5 13.1	36 16.3	3956	
05519	31X10.50R15LT C 109R	(8.5) 7.0-9.0	50	----	2270	30.30	10.50	8.20	----	688	16.5 13.1	40 18.1	3056	
05521	LT235/85R16 E 120/116R	(6.5) 6.0-7.0	80	2778	3042	31.78	9.36	6.70	10.8	660	16.5 13.1	43 19.5	Y960	
05522	LT245/75R16 C 108/104R	(7.0) 6.5-7.5	50	2006	2205	30.52	9.62	7.40	11.3	688	16.5 13.1	42 19.1	W066	
05523	LT245/75R16 E 120/116R	(7.0) 6.5-7.5	80	2778	3042	30.52	9.62	7.40	11.3	688	16.5 13.1	43 19.5	W060	
05512	LT265/75R16 C 112/109R	(7.5) 7.0-8.0	50	2270	2470	31.60	10.33	7.80	12.2	664	16.5 13.1	46 20.9	W166	
05506	LT265/75R16 E 123/120R	(7.5) 7.0-8.0	80	3085	3415	31.81	10.57	7.80	12.2	660	16.5 13.1	48 21.8	W160	
05507	LT285/75R16 D 122/119R	(8.0) 7.5-9.0	65	3000	3305	32.93	11.47	8.80	13.1	639	17.0 13.5	51 23.1	W468	
05513	LT315/75R16 D 121R	(8.5) 8.0-10.0	50	----	3195	34.80	12.90	9.80	----	603	17.0 13.5	62 28.1	WB68	
05514	LT255/70R16 C 108/104R	(7.5) 6.5-8.0	50	1985	2205	30.08	10.38	8.10	12.3	692	16.5 13.1	43 19.5	UX66	
05504	LT305/70R16 D 118/115R	(9.0) 8.0-9.5	50	2680	2910	32.95	12.24	9.70	14.2	638	17.0 13.5	55 24.9	UA68	
05508	LT235/80R17 E 120/117R	(6.5) 6.0-7.5	80	2835	3085	31.65	9.30	6.70	10.8	657	16.5 13.1	43 19.5	X970	
05527	LT245/75R17 E 121/118S	(7.0) 6.5-7.5	80	2910	3195	31.50	9.75	7.65	11.3	660	16.5 13.1	46 20.9	W070	
05515	LT265/70R17 C 112/109R	(8.0) 7.0-8.5	50	2270	2470	31.58	10.61	8.50	12.4	662	16.5 13.1	48 21.8	U176	
05503	LT265/70R17 E 121/118R	(8.0) 7.0-8.5	80	2910	3195	31.60	10.65	8.50	12.4	659	16.5 13.1	50 22.7	U170	
05505	LT275/70R17 C 114/110R	(8.0) 7.0-8.5	50	2335	2600	32.20	11.10	8.65	12.8	647	16.5 13.1	49 22.2	UY76	
05516	LT285/70R17 D 121/118R	(8.5) 7.5-9.0	65	2910	3195	32.76	11.50	9.00	13.4	636	17.0 13.5	52 23.6	U478	
05509	LT315/70R17 D 121/118R	(9.5) 8.5-10.0	50	2910	3195	34.85	12.90	9.90	14.8	606	17.0 13.5	61 27.7	UB78	
05526	LT275/70R18 E 125/122S	(8.0) 7.0-8.5	80	3305	3640	33.15	10.95	9.00	12.8	627	16.5 13.1	54 24.5	UY80	
05525	LT275/65R18 E 123/120S	(8.0) 7.5-9.5	80	3085	3415	32.09	10.98	8.80	12.8	647	16.5 13.1	52 23.6	SY80	

Notes: 2, 3, 5, 6, 7



DISCOVERER RADIAL LT

S/Q/N-Speed Rated



M+S Rated

Wide Footprint

Offering a wider tread footprint than our previously designed LT radials. This all-season tire is designed to wear evenly.

Raised Outline White Letters

There'll be no missing these tires! The whitewall compound has been "whitened" considerably for noticeable brightness.

All-Season Tread Design

Nubby tread pattern combines shoulder lugs and tread cleats for deep biting traction and quiet running at high speeds.



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER LT black sidewall sizes:

W11-511

51150	195R15RE C 100S	(5.5) 5.0-6.0	44	----	1764	27.10	7.70	5.75	----	765	13.5	10.7	26	11.8	1956
51152	205R16C D 110/108Q	(6.0) 5.5-6.5	65	2205	2335	28.90	8.10	6.00	9.4	717	13.5	10.7	31	14.1	2068
51109	LT215/85R16 E 115/112N	(6.0) 5.5-7.0	80	2470	2680	30.30	9.10	6.10	9.9	684	16.5	13.1	39	17.7	Y760
51111	LT235/85R16 E 120/116N	(6.5) 6.0-7.0	80	2778	3042	31.75	9.21	6.36	10.8	654	17.0	13.5	42	19.1	Y960
51106	LT225/75R16 E 115/112N	(6.0) 6.0-7.0	80	2470	2680	29.42	8.68	6.35	10.2	710	16.5	13.1	38	17.2	W860
51107	LT245/75R16 E 120/116N	(7.0) 6.5-7.0	80	2778	3042	30.65	9.35	6.60	11.3	675	16.5	13.1	42	19.1	W060
+51101	7.50R16LT D 112/107N	(6.0) 5.5-7.0	65	2150	2470	31.90	9.10	5.78	10	650	16.5	13.1	37	16.8	7568

DISCOVERER LT outline white letter sizes:

WL1-511

51112	LT195/75R14 C 93/90Q	(5.5) 5.0-6.0	50	1325	1435	26.00	7.50	5.28	8.9	797	16.5	13.1	25	11.3	W546
51120	27X8.50R14LT C 95Q	(7.0) 6.0-7.5	50	----	1520	26.50	8.70	6.30	----	782	16.5	13.1	29	13.2	2746
+51113	LT215/75R15 C 100/97Q	(6.0) 5.5-7.0	50	1610	1765	27.80	8.15	5.80	9.9	746	16.5	13.1	30	13.6	W756
+51114	LT235/75R15 C 104/101Q	(6.5) 6.0-7.0	50	1820	1985	28.90	9.12	6.36	10.8	719	17.0	13.5	33	15.0	W956
51122	31X10.50R15LT C 109Q	(8.5) 7.0-9.0	50	----	2270	30.20	10.50	8.20	----	687	16.5	13.1	40	18.1	3056
51128	32X11.50R15LT C 113Q	(9.0) 8.0-10.0	50	----	2535	31.30	11.40	8.80	----	662	18.0	14.3	44	20.0	3356
51124	33X12.50R15LT C 108Q	(10.0) 8.5-11.0	35	----	2205	32.40	12.40	9.60	----	640	18.0	14.3	50	22.7	3256
^51136	LT265/75R16 D 119/116N	(7.5) 7.0-8.0	65	2755	3000	31.70	9.93	7.50	12.2	654	16.0	12.7	45	20.4	W168
51125	33X12.50R16.5LT D 118N	(9.75) 8.25-10.5	50	----	2910	32.40	12.40	9.60	----	640	18.0	14.3	55	24.9	3268

Notes: 2, 3, 5, 6, 7

+ Discontinued - Limited Availability

^ Limited Availability



SRM II RADIAL LT

Q/N-Speed Rated



M+S Rated

Aggressive Rib Elements

Three center ribs with strategically-placed cross slots combine with four wide circumferential grooves to help channel away water and slush for continuous road contact during wet highway driving.

Solid Shoulders

Solid shoulder design helps to promote a balanced tread wear pattern throughout the tire life in both free rolling and drive axle positions.

Five-Rib Tread Design

Modern five rib tread design helps this radial deliver excellent directional control for great handling and dependable highway driving.



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

SRM II RADIAL LT black sidewall sizes:

W11-643

*64305	185R14C D 102/100Q	(5.5) 5.0-6.0	65	1765	1875	25.50	7.30	5.45	8.5	813	13.0 10.3	25 11.3	1848	
*64306	195R14C D 106/104Q	(5.5) 5.0-6.0	65	1985	2095	26.20	7.70	5.75	9.0	791	13.0 10.3	27 12.2	1948	
64311	LT215/85R16 E 115/112N	(6.0) 5.5-7.0	80	2470	2680	30.26	8.21	5.93	9.9	683	14.0 11.1	39 17.7	Y760	
64310	LT235/85R16 E 120/116N	(6.5) 6.0-7.0	80	2778	3042	31.70	9.21	6.69	10.8	656	14.0 11.1	42 19.1	Y960	
64316	LT225/75R16 E 115/112N	(6.0) 6.0-7.0	80	2470	2680	29.18	8.60	6.60	10.2	711	14.0 11.1	39 17.7	W860	
64307	LT245/75R16 E 120/116N	(7.0) 6.5-7.0	80	2778	3042	30.46	9.35	6.98	11.3	680	14.0 11.1	44 20.0	W060	
64312	LT265/75R16 E 123/120N	(7.5) 7.0-8.0	80	3085	3415	31.65	10.50	8.00	12.2	663	14.0 11.1	47 21.3	W160	
64301	7.50R16LT D 112/107N	(6.0) 5.5-7.0	65	2150	2470	31.80	8.35	6.13	10.0	652	14.0 11.1	38 17.2	7568	
64302	8.00R16.5LT D 105/101N	(6.0) 6.0-6.75	65	1820	2040	28.45	7.80	6.10	9.0	728	14.0 11.1	34 15.4	8068	
64303	8.75R16.5LT D 111/106N	(6.75) 6.0-6.75	65	2095	2405	29.42	8.60	6.75	9.9	704	14.0 11.1	39 17.7	8768	
64304	9.50R16.5LT D 117/112N	(6.75) 6.75-8.25	65	2470	2835	30.43	9.15	7.15	10.7	681	14.0 11.1	40 17.7	9568	

Notes: 2, 3, 5, 6, 7

* Four-Rib Tread Design - Not M+S Rated



DISCOVERER AST II

S-Speed Rated



Value Design

Advanced engineering makes it possible to offer value performance at low initial cost.

All-Season Tread

A five rib tread design creates a pattern of gripping edges for excellent traction. Lateral grooves and shoulder slots evacuate water from the contact area for effective wet weather driving control.

Stiff, Lower Sidewall

A hard bead filler is reinforced with a rim cushion to surround the bead area with stiff support. A rigid lower sidewall enhances handling and stability.

M+S Rated

TREADWEAR TRACTION TEMPERATURE

UTQG **400 A B**



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------------	-----------------	---------------	---------------	-------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER AST II outline white letter sizes:

WL1-2EA

01910	205/75R15 97S	(5.5) 5.0-7.0	35	1609	1463	26.93	8.10	5.70	772	11.0 8.7	23 10.4	V654	
01911	215/75R15 100S	(6.0) 5.5-7.0	35	1764	1604	27.48	8.60	6.00	757	11.0 8.7	25 11.3	V754	
01912	225/75R15 102S	(6.0) 6.0-7.5	35	1874	1704	28.08	8.95	6.20	740	11.0 8.7	26 11.8	V854	
01913	235/75R15 105S	(6.5) 6.0-8.0	35	2039	1854	28.70	9.30	6.50	724	11.0 8.7	28 12.7	V954	
01914	235/75R15RE 109S	(6.5) 6.0-8.0	41	2271	2065	28.88	9.32	6.90	721	11.0 8.7	31 14.1	V956	
01917	265/75R15 112S	(7.5) 7.0-8.5	35	2469	2245	30.40	10.65	7.60	680	11.0 8.7	35 15.9	VV54	
01918	235/70R15 103S	(7.0) 6.0-7.5	44	1929	1754	27.70	9.65	7.30	750	11.0 8.7	28 12.7	R954	
01927	245/75R16 111S	(7.0) 6.5-8.0	35	2403	2185	30.20	9.60	7.10	688	11.0 8.7	33 15.0	V064	
01929	265/75R16 116S	(7.5) 7.0-8.5	35	2756	2505	31.32	10.60	7.80	664	11.0 8.7	37 16.8	VV64	
01932	225/70R16 102S	(6.5) 6.0-7.5	35	1874	1704	28.20	9.00	7.10	737	11.0 8.7	29 13.2	R864	
01933	235/70R16 106S	(7.0) 6.0-7.5	35	2094	1904	28.73	9.40	7.40	724	11.0 8.7	31 14.1	R964	
01934	245/70R16 107S	(7.0) 6.5-8.0	35	2149	1954	29.38	9.85	7.70	708	11.0 8.7	32 14.5	R064	
01935	255/70R16 111S	(7.5) 6.5-8.5	35	2403	2185	29.80	10.30	8.00	698	11.0 8.7	34 15.4	RX64	
01936	265/70R16 112S	(8.0) 7.0-9.0	44	2469	2245	30.20	10.80	7.84	687	11.0 8.7	35 15.9	RV64	

Notes: 1, 2, 4, 6, 7



DISCOVERER RADIAL AST

Q/N-Speed Rated



Value Design

Advanced engineering makes it possible to offer value performance at low initial cost.

All-Season Tread

A five rib tread design creates a pattern of gripping edges for excellent traction. Lateral grooves and shoulder slots evacuate water from the contact area for effective wet weather driving control.

Stiff, Lower Sidewall

A hard bead filler is reinforced with a rim cushion to surround the bead area with stiff support. A rigid lower sidewall enhances handling and stability.

M+S Rated



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER AST black sidewall sizes:

W11-514

51405	LT215/85R16 D 110/107N	(6.0) 5.5-7.0	65	2150	2335	30.20	8.40	5.74	9.9	687	14.0 11.1	35 15.9	Y768	
51411	LT215/85R16 E 115/112Q	(6.0) 5.5-7.0	80	2470	2680	30.20	8.40	5.74	9.9	687	10.5 8.3	37 16.8	Y760	
51406	LT235/85R16 E 120/116N	(6.5) 6.0-7.0	80	2778	3042	31.50	9.30	6.11	10.8	658	14.0 11.1	40 18.1	Y960	
51403	LT225/75R16 D 110/107N	(6.0) 6.0-7.0	65	2150	2335	29.30	8.50	6.28	10.2	713	14.0 11.1	35 15.9	W868	
51404	LT245/75R16 E 120/116N	(7.0) 6.5-8.0	80	2778	3042	30.40	9.40	6.61	11.3	682	14.0 11.1	39 17.7	W060	
51401	8.75R16.5LT D 111/106N	(6.75) 6.0-6.75	65	2095	2405	29.50	8.60	6.08	9.9	705	14.0 11.1	34 15.4	8768	
51402	9.50R16.5LT D 117/112N	(6.75) 6.75-8.25	65	2470	2835	30.30	9.20	6.70	10.7	684	14.0 11.1	38 17.2	9568	

DISCOVERER AST outline white letter sizes:

WL1-514

51407	LT235/75R15 C 104/101Q	(6.5) 6.0-7.0	50	1820	1985	28.70	8.90	6.32	10.8	722	14.0 11.1	31 14.1	W956	
51408	30X9.50R15LT C 104Q	(7.5) 6.5-8.5	50	----	1985	29.10	9.30	6.91	----	713	14.0 11.1	33 15.0	3956	
51409	31X10.50R15LT C 109Q	(8.5) 7.0-9.0	50	----	2270	30.00	10.50	7.58	----	691	14.0 11.1	37 16.8	3056	
51410	LT265/75R16 C 112/109Q	(7.5) 7.0-8.0	50	2270	2470	31.63	10.38	7.60	12.2	654	14.0 11.1	44 20.0	W166	

Notes: 2, 3, 5, 6, 7



DISCOVERER S/T



**S-Speed Rated
Studdable**

Large, Beefy Tread Elements

Designed for off-road applications while providing long, even wear in highway applications.

Beveled Treadblock Edges

Fights irregular wear and improves self-cleaning capabilities.

Deep Tread and Scalloped Shoulder Design

Maximizes traction in soft surfaces.

M+S Rated



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diam.	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
--------	---------------------------------	--------------------------------------	-----	-----------------	-----------------	---------------	---------------	-------------	---------------	----------------------------------	--------------------	-----------------------	-----------	-------

DISCOVERER S/T black sidewall size:

W11-1EP

73420	275/60R20RE 119S	(8.5) 8.0-9.5	50	2998	2725	33.04	12.69	9.10	631	15.0	11.9	13	9-12	51	23.1	EY06	
-------	------------------	---------------	----	------	------	-------	-------	------	-----	------	------	----	------	----	------	------	--

DISCOVERER S/T outline white letter sizes:

WL1-1EP

73406	235/75R15 105S	(6.5) 6.0-8.0	35	2039	1854	29.00	9.40	7.40	717	15.0	11.9	13	9-12	32	14.5	V954	
73405	235/75R15RE 109S	(6.5) 6.0-7.5	41	2271	2065	29.00	9.40	7.40	717	15.0	11.9	13	9-12	33	15.0	V956	
73409	245/75R16 111S	(7.0) 6.5-8.0	35	2403	2185	30.40	9.65	7.60	683	15.0	11.9	13	9-12	35	15.9	V064	
73410	265/75R16 116S	(7.5) 7.0-9.0	35	2756	2505	31.55	10.55	8.30	658	15.0	11.9	13	9-12	40	18.1	VV64	
73412	235/70R16 106S	(7.0) 6.0-8.0	35	2094	1904	28.90	9.50	7.40	719	15.0	11.9	13	9-12	33	15.0	R964	
73413	255/70R16 111S	(7.5) 6.5-8.5	35	2403	2185	30.10	10.15	7.80	691	15.0	11.9	13	9-12	36	16.3	RX64	
73414	265/70R16 112S	(8.0) 7.0-9.0	44	2469	2245	30.63	10.71	8.40	684	15.0	11.9	13	9-12	38	17.2	RV64	
73416	245/70R17 110S	(7.0) 6.5-8.0	44	2337	2125	30.43	9.96	7.60	683	15.0	11.9	13	9-12	36	16.3	R074	

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 1, 2, 4, 6, 7



DISCOVERER S/T



R/Q/N-Speed Rated
Studdable

Large, Beefy Tread Elements

Designed for off-road applications while providing long, even wear in highway applications.


Beveled Treadblock Edges

Fights irregular wear and improves self-cleaning capabilities.

Deep Tread and Scalloped Shoulder Design

Maximizes traction in soft surfaces.

M+S Rated



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price	
DISCOVERER S/T black sidewall sizes:															W11-734	
73430	LT215/85R16 E 115/112N	(6.0) 5.5-7.0	80	2470	2680	30.48	8.41	6.10	9.9	684	18.0 14.3	15 9-13	41 18.6	Y760		
73432	LT235/85R16 E 120/116N	(6.5) 6.0-7.0	80	2778	3042	31.90	9.29	7.00	10.8	654	18.0 14.3	15 9-13	45 20.4	Y960		
73433	LT225/75R16 E 115/112N	(6.0) 6.0-7.0	80	2470	2680	29.35	8.54	6.60	10.2	710	18.0 14.3	15 9-13	40 18.1	W860		
73434	LT245/75R16 E 120/116N	(7.0) 6.5-7.5	80	2778	3042	30.53	9.76	7.45	11.3	680	18.0 14.3	15 9-13	46 20.9	W060		

Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price	
DISCOVERER S/T outline white letter sizes:															WL1-734	
73422	LT235/75R15 C 104/101Q	(6.5) 6.0-7.0	50	1820	1985	28.62	9.14	7.20	10.8	715	18.0 14.3	15 9-13	37 16.8	W956		
73446	30X9.50R15LT C 104Q	(7.5) 6.5-8.5	50	----	1985	29.35	9.63	7.40	----	708	18.0 14.3	15 9-13	37 16.8	3956		
73447	31X10.50R15LT C 109Q	(8.5) 7.0-9.0	50	----	2270	30.47	10.71	8.20	----	687	18.0 14.3	15 9-13	41 18.6	3056		
73448	33X12.50R15LT C 108Q	(10.0) 8.5-11.0	35	----	2205	32.63	12.36	9.80	----	640	20.0 15.9	17 9-16	53 24.0	3256		
73449	35X12.50R15LT C 113Q	(10.0) 8.5-11.0	35	----	2535	34.88	12.87	10.20	----	613	20.0 15.9	17 9-16	64 29.0	3556		
73440	LT255/85R16 D 119/116N	(7.0) 6.5-8.0	65	2755	3000	33.21	10.04	7.20	11.7	628	18.0 14.3	15 9-13	48 21.8	YX68		
73443	LT265/75R16 C 112/109N	(7.5) 7.0-8.0	50	2270	2470	31.64	10.50	8.10	12.2	654	18.0 14.3	15 9-13	47 21.3	W166		
73442	LT265/75R16 D 119/116N	(7.5) 7.0-8.0	65	2755	3000	31.73	10.52	8.10	12.2	654	18.0 14.3	15 9-13	48 21.8	W168		
73444	LT265/75R16 E 123/120N	(7.5) 7.0-8.0	80	3085	3415	31.76	10.59	8.10	12.2	654	18.0 14.3	15 9-13	52 23.6	W160		
73445	LT285/75R16 D 122/119N	(8.0) 7.5-9.0	65	3000	3305	32.80	11.30	9.20	13.3	628	20.0 15.9	17 9-16	56 25.4	W468		
73455	LT315/75R16 D 121N	(8.5) 8.0-10.0	50	----	3195	34.60	12.87	10.00	----	615	20.0 15.9	17 9-16	65 29.5	WB68		
73461	LT305/70R16 D 118/115N	(9.0) 8.0-9.5	50	2680	2910	32.81	12.29	10.00	13.3	626	18.0 14.3	15 9-13	56 25.4	UA68		
73481	LT235/80R17 E 120/117Q	(6.5) 6.0-8.0	80	2835	3085	31.85	9.40	7.00	10.8	652	18.0 14.3	15 9-13	47 21.3	X970		
73468	LT245/75R17 E 121/118Q	(7.0) 6.5-8.0	80	2910	3195	31.75	10.80	7.67	11.3	654	18.0 14.3	15 9-13	49 22.2	W070		
73471	LT245/70R17 E 119/116Q	(7.0) 6.5-8.0	80	2755	3000	30.45	10.07	7.45	11.3	679	18.0 14.3	15 9-13	46 20.9	U070		
73473	LT265/70R17 C 112/109Q	(8.0) 7.0-9.0	50	2270	2470	31.65	10.71	8.40	12.4	656	18.0 14.3	15 9-13	47 21.3	U176		
73475	LT265/70R17 E 121/118Q	(8.0) 7.0-9.0	80	2910	3195	31.65	11.03	8.40	12.4	656	18.0 14.3	15 9-13	52 23.6	U170		
73478	LT275/70R17 C 114/110Q	(8.0) 7.0-9.0	50	2335	2600	32.20	11.32	8.80	12.8	645	18.0 14.3	15 9-13	50 22.7	UY76		
73480	LT285/70R17 D 121/118Q	(8.5) 7.5-9.5	65	2910	3195	32.80	12.50	9.10	13.4	634	18.0 14.3	15 9-13	55 24.9	U478		
73450	33X12.50R17LT D 114Q	(10.0) 8.5-11.0	50	----	2600	32.63	12.36	9.80	----	640	20.0 15.9	17 9-16	58 26.3	3278		
73451	35X12.50R17LT D 119Q	(10.0) 8.5-11.0	50	----	3000	34.88	12.87	10.20	----	613	20.0 15.9	17 9-16	66 29.9	3578		
73484	LT275/70R18 E 125/122Q	(8.0) 7.0-9.0	80	3305	3640	33.30	12.10	8.80	12.8	624	18.0 14.3	15 9-13	56 25.4	UY80		
73490	LT275/65R18 C 113/110R	(8.0) 7.5-9.5	50	2335	2535	32.20	10.98	8.80	12.8	645	18.0 14.3	15 9-13	52 23.6	SY86		
73424	LT275/65R18 E 123/120Q	(8.0) 7.5-9.5	80	3085	3415	32.30	11.90	8.80	12.8	643	18.0 14.3	15 9-13	55 24.9	SY80		

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 2, 3, 5, 6, 7



DISCOVERER S/T-C



M+S Rated

**Q/N-Speed Rated
Studdable**

Cut and Chip Resistant Tread Compound

Provides increased resistance to cutting, chipping and tearing commonly found in rocky, off-road and gravel conditions.

Deep Tread and Scalloped Shoulder Design

Maximizes traction in soft surfaces.

Large, Beefy Tread Elements

Designed for off-road applications while providing long, even wear in highway applications.



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size TSM Euro	Ship Weight lbs. kilo	Size Code	Price
DISCOVERER S/T-C black sidewall sizes:												W11-5BN			
52032	LT235/85R16 E 120/116N	(6.5) 6.0-7.0	80	2778	3042	31.90	9.29	7.00	10.8	654	18.0 14.3	15 9-13	45 20.4	Y960	
52034	LT245/75R16 E 120/116N	(7.0) 6.5-7.5	80	2778	3042	30.50	9.76	7.45	11.3	680	18.0 14.3	15 9-13	45 20.4	W060	
DISCOVERER S/T-C outline white letter sizes:												WL1-5BN			
52044	LT265/75R16 E 123/120N	(7.5) 7.0-8.0	80	3085	3415	31.80	10.59	8.10	12.2	654	18.0 14.3	15 9-13	50 22.7	W160	
*52045	LT285/75R16 D 122/119Q	(8.0) 7.5-9.0	65	3000	3305	32.80	11.30	9.20	13.3	628	20.0 15.9	15 9-13	56 25.4	W468	
52043	LT265/70R17 E 121/199Q	(8.0) 7.0-9.0	80	2910	3195	31.70	11.03	8.40	12.4	656	18.0 14.3	17 9-13	51 23.1	U170	

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Notes: 2, 3, 5, 6, 7

* Availability To Be Announced



DISCOVERER STT

Q/P/N-Speed Rated



Armor-Tek³ Carcass Construction

The heavy duty carcass is constructed of two radial polyester body plies and one angled polyester body ply to deliver 3 plies of protection for superior resistance to impact breaks and bruising.

Super Traction Tread

The computer designed, non-directional tread employs a combination of features including deep buttress lugs, notched and scalloped shoulder lugs, and a unique center traction zone to create a bold, aggressive tire for tough off-road applications.

Deep Buttress Lugs

The aggressive tread design extends far down the sidewall to enhance its soft surface traction and provide additional "bite" in rock climbing applications.

M+S Rated



Item #	Tire Size, Load Range & Service Description	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	---	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

DISCOVERER STT black sidewall sizes:

W11-761

76114	LT215/85R16 E	115/112Q	(6.0) 5.5-7.0	80	2470	2680	30.63	8.08	6.10	9.9	678	17.5 13.9	43 19.5	Y760	
76104	LT235/85R16 E	120/116Q	(6.5) 6.0-7.0	80	2778	3042	31.80	9.70	7.30	10.8	652	18.0 14.3	49 22.2	Y960	
76113	LT325/80R16 D	124/121Q	(9.0) 8.5-11.0	50	3195	3525	36.78	13.10	10.80	14.8	565	20.5 16.3	85 38.6	FC68	
76103	LT245/75R16 E	120/116Q	(7.0) 6.5-7.0	80	2778	3042	30.70	9.45	7.60	11.3	675	18.0 14.3	47 21.3	W060	
76102	LT245/70R17 E	119/116Q	(7.0) 6.5-8.0	80	2755	3000	30.70	9.60	7.60	11.3	676	18.0 14.3	47 21.3	U070	
*76135	LT295/70R17 E	121/118Q	(8.5) 7.5-10.0	80	2910	3195	33.45	11.80	9.40	13.7	623	20.5 16.3		UZ70	
76101	37X12.50R17LT D	124P	(8.5) 8.5-11.0	50	----	3525	36.90	13.10	10.00	----	563	23.0 18.3	83 37.6	3778	
*76134	LT275/70R18 E	125/122Q	(8.0) 7.0-9.0	80	3305	3640	33.35	11.00	8.80	12.8	623	20.5 16.3		UY80	
76132	LT325/65R18 E	127/124N	(9.5) 9.0-12.0	65	3525	3860	34.75	13.50	10.80	14.8	598	23.0 18.3	78 35.4	SC80	
*76136	LT305/60R18 E	121/118Q	(9.0) 8.5-11.0	65	2910	3195	32.64	12.09	9.80	14.2	636	20.5 16.3		TA80	
76133	LT325/60R18 E	124/121N	(9.5) 9.0-12	65	3195	3525	33.22	13.30	10.80	14.8	625	23.0 18.3	75 34.0	TC80	
*76128	33X12.50R20LT E	114Q	(10.0) 8.5-11.0	65	----	2600	32.66	12.49	9.80	----	636	20.5 16.3		3200	
*76130	35X12.50R20LT E	121Q	(10.0) 8.5-11.0	65	----	3195	34.66	12.50	9.80	----	599	20.5 16.3		3500	
76131	35X13.50R20LT E	122N	(11.0) 8.5-11.0	65	----	3305	34.65	13.65	10.50	----	599	21.0 16.7	77 34.9	5500	

DISCOVERER STT outline white letter sizes:

WL1-761

76125	LT235/75R15 C	104/101Q	(6.5) 6.0-7.0	50	1820	1985	29.09	9.45	7.00	10.8	718	18.0 14.3	39 17.7	W956	
76107	30X9.50R15LT C	104Q	(7.5) 6.5-8.5	50	----	1985	29.70	9.80	7.80	----	708	20.0 15.9	43 19.5	3956	
76105	31X10.50R15LT C	109Q	(8.5) 7.0-9.0	50	----	2270	30.75	10.85	8.30	----	681	20.0 15.9	47 21.3	3056	
76117	32X11.50R15LT C	113Q	(9.0) 8.0-10.0	50	----	2535	31.76	11.40	9.00	----	657	20.0 15.9	49 22.2	3356	
76115	33X12.50R15LT C	108Q	(10.0) 8.5-11.0	35	----	2205	32.76	12.08	9.70	----	637	20.5 16.3	56 25.4	3256	
76118	35X12.50R15LT C	113Q	(10.0) 8.5-11.0	35	----	2535	34.76	12.20	10.00	----	600	20.5 16.3	67 30.4	3556	
76124	LT225/75R16 E	115/112Q	(6.0) 6.0-7.0	80	2470	2680	29.53	8.70	6.70	10.2	703	17.5 13.9	43 19.5	W860	
76123	LT265/75R16 D	119/116Q	(7.5) 7.0-8.0	65	2755	3000	32.00	10.61	8.25	12.2	652	18.5 14.7	51 23.1	W168	
76111	LT265/75R16 E	123/120Q	(7.5) 7.0-8.0	80	3085	3415	32.00	10.10	8.25	12.2	655	18.0 14.3	53 24.0	W160	
76112	LT285/75R16 D	122/119Q	(8.0) 7.5-9.0	65	3000	3305	33.10	11.30	8.85	13.7	646	18.0 14.3	56 25.4	W468	
76126	LT315/75R16 D	121Q	(8.5) 8.0-10.0	50	----	3195	34.47	11.92	9.80	----	620	20.0 15.9	67 30.4	WB68	
76122	LT255/70R16 C	108/104Q	(7.5) 6.5-8.0	50	1985	2205	30.31	10.56	8.00	12.3	685	17.5 13.9	46 20.9	UX66	
76120	LT265/70R16 C	110/107Q	(8.0) 7.0-8.5	50	2150	2335	30.86	10.94	8.40	12.4	673	18.5 14.7	49 22.2	U166	
76121	LT305/70R16 D	118/115Q	(9.0) 8.0-9.5	50	2680	2910	33.07	12.00	9.80	13.3	628	19.0 15.1	61 27.7	UA68	
76109	LT265/70R17 E	121/118Q	(8.0) 7.0-9.0	80	2910	3195	31.90	10.80	8.25	12.4	652	18.0 14.3	53 24.0	U170	
76110	LT285/70R17 D	121/118Q	(8.5) 7.5-9.5	65	2910	3195	33.00	11.50	8.85	13.4	646	18.0 14.3	57 25.9	U478	
76116	33X12.50R17LT D	114Q	(10.0) 8.5-11.0	50	----	2600	32.76	12.54	9.80	----	634	20.5 16.6	63 28.6	3278	
76119	35X12.50R17LT D	119Q	(10.0) 8.5-11.0	50	----	3000	34.76	12.67	9.80	----	598	20.5 16.3	68 30.8	3578	
76108	LT275/65R18 C	113/110Q	(8.0) 7.5-9.0	50	2335	2535	32.32	10.98	8.45	12.8	643	18.0 14.3	56 25.4	SY86	
+76106	35X12.50R18LT D	118Q	(10.0) 8.5-11.0	50	----	2910	34.76	12.50	10.00	----	598	20.0 15.9	69 31.3	3588	
76127	35X12.50R18LT E	123Q	(10.0) 8.5-11.0	65	----	3415	34.76	12.50	10.00	----	598	20.0 15.9	68 30.8	3580	

Notes: 2, 3, 5, 6, 7

+ Discontinued - Limited Availability

* Availability To Be Announced



SUPER ROAD SERVICE

Trailer and All-wheel Positions
Tubeless, Bias



Cap/Base Tread


Greatly increases separation resistance and offers particular resistance to internal heat build up.

Anti-Ozonant System

This system in the tread, buttress and sidewall compounds helps increase their resistance to ozone cracking.

Shock Guard Construction

Body plies are impregnated with highly resilient rubber to guard against impact shock.



Item #	Tire Size & Load Range	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Ship Weight lbs. kilo	Size Code	Price
--------	------------------------	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------------------	-----------	-------

SUPER ROAD SERVICE trailer position sizes:

411-550

T	*55005	8-14.5	F	(6.0) 6.0-6.0	100	2460	2790	28.40	8.10	5.8	8.8	746	11.0	8.7	36	16.3	0842	
T	*55006	9-14.5	F	(7.0) 7.0-7.0	100	2840	3230	28.00	9.50	6.5	10.5	742	12.0	9.5	41	18.6	0942	

SUPER ROAD SERVICE all wheel position sizes:

411-550

T	55007	7.00-15LT	C	(5.5) 5.0-6.5	45	1520	1720	30.00	8.30	6.5	9.0	715	14.5	11.5	34	15.4	7056	
T	55008	7.00-15LT	D	(5.5) 5.0-6.5	60	1800	2040	30.40	8.20	6.5	9.0	704	14.5	11.5	35	15.9	7058	
T	55009	7.50-16LT	D	(6.0) 5.5-7.0	60	2140	2440	32.30	8.90	6.9	10.0	662	14.5	11.5	45	20.4	7568	
T	55011	8.75-16.5LT	D	(6.75) 6.-6.75	60	2070	2350	29.80	9.40	7.6	9.9	720	15.0	11.9	41	18.6	8768	
T	55012	8.75-16.5LT	E	(6.75) 6.-6.75	75	2360	2680	30.00	9.40	7.6	9.9	714	15.0	11.9	41	18.6	8760	
T	55013	9.50-16.5LT	D	(6.75) 6.75-8.25	60	2445	2780	30.80	10.00	8.5	10.7	695	15.5	12.3	44	20.0	9568	
T	55014	9.50-16.5LT	E	(6.75) 6.75-8.25	75	2790	3170	31.00	10.10	8.5	10.7	690	15.5	12.3	46	20.9	9560	
T	55015	12-16.5LT	D	(9.75) 8.25-9.75	45	2640	3000	32.20	12.30	9.5	13.7	658	16.0	12.7	54	24.5	1268	

Loaded Width - The deflected cross sectional width of the tire uses the Tire and Rim Association's maximum dual tire load and corresponding inflation pressure.

Notes: 3, 5, 7

* Different Tread Design

T - Made in Taiwan



COURSER TRACTION LT



M+S Rated

**Studdable
Tubeless, Bias**

High Traction Tread

Two wide center grooves and deep shoulder lugs form an effective pattern of gripping edges for excellent off-road traction. The groove network also channels out water quickly and efficiently for sure-footed traction on rain-soaked highways.

Durable Tread Compound

Using computer technology, the tread compound is formulated to combine the materials to provide excellent performance both on the highway and in off-road use.



Item #	Tire Size & Load Range	Meas. Rim Width / Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diam.	Overall Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth 32 ^{nds} mm	Stud Size	Ship Weight lbs. kilo	Size Code	Price
--------	------------------------	--------------------------------------	-----	----------------	------------------	---------------	---------------	-------------	----------------------------	---------------	----------------------------------	-----------	-----------------------	-----------	-------

COURSER TRACTION LT sizes:

411-620

T	62005	7.00-15LT	C	(5.5) 5.0-6.5	45	1520	1720	30.03	8.20	6.70	9.0	704	18.5	14.7	17x615	35	16.0	7056	
T	62007	7.50-16LT	D	(6.0) 5.5-7.0	60	2140	2440	32.20	9.11	7.25	10.0	662	19.0	15.1	17x615	47	21.0	7568	

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Loaded Width - The deflected cross sectional width of the tire uses the Tire and Rim Association's maximum dual tire load and corresponding inflation pressure.

Rims 1/2" greater in width are approved for these tires. Overall width under load and minimum dual spacing will change .20" for each 1/2" change in rim width.

Notes: 3, 5, 7

T - Made in Taiwan



Notes & Recommendations

- 1** NOTE: Metric tires may be used in P-metric application, provided metric load index values are equal to or greater than P-metric load index values. Use inflation pressure specified on vehicle placard.
- 2** IMPORTANT: Not all rims and wheels are approved for use with radial ply tires. Use of a non-approved rim or wheel could result in rim fatigue failure and a possible accident. It is, therefore, extremely important to consult the wheel and rim manufacturer or his local distributor to determine which rims or wheels are acceptable for use with a specific radial ply tire.
- 3** Load Index differs depending on whether the tires are used in a single or dual application (Single/Dual).
- 4** When passenger tires are used in light truck service, tire and rim industry standards apply a 10% reduction in maximum rated load.
- 5** MINIMUM DUAL SPACING: The minimum dimension from the centerline of one rim to the centerline of the other rim in a dual wheel assembly is recommended to provide adequate clearance between tires.
- 6** SPEED RATINGS: Capable of sustaining indoor wheel tests at the following speeds:

L	75 MPH	R	106 MPH	V	149 MPH
M	81 MPH	S	112 MPH	W	168 MPH
N	87 MPH	T	118 MPH	Y	186 MPH
P	93 MPH	U	124 MPH	Z	150+ MPH
Q	99 MPH	H	130 MPH		
- 7** IMPORTANT: Use the information on the vehicle placard and the vehicle owner's manual to identify original equipment tire size, speed rating, air pressure and load capacity.



Australia: **419.427.4851**

Canada and Caribbean: **800.447.7316**

Mexico, South America and Central America: **419.427.4750**

Asia, China and Europe: **419.424.4314**

Visit us at **www.coopertire.com**.