



Our tires have
earned their stripes.

Product Manual

Effective January 2006



OUR PRODUCTS

Passenger

Stinger Radial GTS.....	1
Equus LSi	2 & 3
Quasar Plus Radial.....	4 & 5
Alpha 365 Radial	6

Snow

Wintercat Radial SST.....	7 & 8
---------------------------	-------

Light Truck

Wildcat Touring SLT.....	9
Wildcat Radial A/T	10 & 11
Wildcat LT All Terrain	12
Durango Radial A/T	13
Trailcat All-Season	14
Wildcat H/T.....	15
Durango Radial XTR.....	16
Mud Terrain Radial SXT	17
Wildcat EXT Radial LT	18
Super Road Service.....	19
Courser Traction LT	20
Custom Trailer Radial.....	21
Custom Trailer Plus.....	21

Warranties

Special Limited Warranty	22
NOTES, RECOMMENDATIONS & SPEED RATINGS	23

PROVEN PERFORMER



STINGER RADIAL GTS



STEEL-BELTED CONSTRUCTION

Steel cord belts provide reinforcement under the tread for superb traction and stability. Low stretch polyester cord plies create a strong, durable tire body.

PERFORMANCE TREAD COMPOUND


The tread rubber compound is formulated for an optimal balance of traction capability and treadwear. Compounds throughout the tire contribute to long life by resisting the effects of internal heat build-up and exposure to atmospheric elements.

SERIES (Size) TREADWEAR TRACTION TEMP

50 SERIES	440	A	C
ALL OTHERS	440	A	B

M + S RATED **UTQG**

PASSENGER



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Max. Load @ 44 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32nds	mm	Ship Weight (lbs.)	Size Code	F.E.T.	Price
BLACK SIDEWALL SIZES:												W11-053	
05320	P185/60R14	82T (5.5)	5.0-6.5	1047	22.80	7.15	6.00	912	10.5	8.3	17	T444	
05321	P195/60R14	85T (6.0)	5.5-7.0	1135	23.28	7.62	6.40	893	10.5	8.3	18	T544	
05322	P195/60R15	87T (6.0)	5.5-7.0	1190	24.30	7.60	6.40	856	10.5	8.3	19	T554	
05323	P205/60R15	90T (6.0)	5.5-7.5	1301	24.73	7.83	6.50	841	10.5	8.3	20	T654	
05324	P225/60R15	95T (6.5)	6.0-7.5	1521	25.67	8.63	7.20	810	10.5	8.3	23	T854	
05317	P195/50R15	81S (6.0)	5.5-7.0	1019*	22.78	7.64	6.50	913	10.5	8.3	18	Z554	
05318	P205/50R15	84S (6.5)	5.5-7.5	1113*	23.15	8.18	6.85	898	10.5	8.3	19	Z654	
05319	P225/50R15	90S (7.0)	6.0-8.0	1301*	23.90	8.94	7.45	870	10.5	8.3	22	Z854	
05350	P235/55R16	96T (7.5)	6.5-8.5	1565	26.15	9.65	7.95	793	10.5	8.3	24	C964	
RAISED WHITE LETTER SIZES:												W31-053	
05303	P205/60R13	86T (6.0)	5.5-7.5	1179	22.75	7.86	6.50	914	10.5	8.3	17	T634	
05330	P185/70R14	87T (5.5)	4.5-6.0	1201	24.27	7.35	5.90	857	10.5	8.3	18	U444	
05331	P195/70R14	90T (6.0)	5.0-6.5	1312	24.75	7.85	6.30	840	10.5	8.3	19	U544	
05332	P205/70R14	93T (6.0)	5.0-7.0	1433	25.30	8.21	6.50	822	10.5	8.3	21	U644	
05333	P215/70R14	96T (6.5)	5.5-7.0	1554	25.76	8.66	7.00	807	10.5	8.3	22	U744	
05334	P225/70R14	98T (6.5)	6.0-7.5	1675	26.27	8.92	7.20	792	10.5	8.3	24	U844	
05306	P215/60R14	91T (6.5)	6.0-7.5	1345	24.16	8.42	7.00	861	10.5	8.3	21	T744	
05308	P235/60R14	96T (7.0)	6.5-8.0	1565	25.06	9.11	7.60	830	10.5	8.3	23	T944	
05335	P215/70R15	97T (6.5)	5.5-7.0	1620	26.71	8.71	7.00	778	10.5	8.3	23	U754	
05336	P225/70R15	100T (6.5)	6.0-7.5	1753	27.37	8.71	7.20	760	10.5	8.3	25	U854	
05337	P235/70R15	102T (7.0)	6.0-8.0	1896	27.90	9.46	7.60	745	10.5	8.3	27	U954	
05338	P255/70R15	108T (7.5)	6.5-8.5	2183	28.95	10.40	8.20	718	10.5	8.3	31	UX54	
05316	P215/65R15	95T (6.5)	6.0-7.5	1510	26.00	8.38	6.80	799	10.5	8.3	22	S754	
05310	P195/60R15	87T (6.0)	5.5-7.0	1190	24.30	7.60	6.40	856	10.5	8.3	19	T554	
05311	P215/60R15	93T (6.5)	6.0-7.5	1411	25.16	8.44	7.00	827	10.5	8.3	22	T754	
05312	P235/60R15	98T (7.0)	6.5-8.0	1642	26.11	9.15	7.60	796	10.5	8.3	25	T954	
05313	P245/60R15	100T (7.0)	7.0-8.0	1753	26.55	9.47	8.00	783	10.5	8.3	26	T054	
05314	P255/60R15	102T (7.5)	7.0-9.0	1885	27.01	9.73	8.20	769	10.5	8.3	28	TX54	
05315	P275/60R15	107T (8.0)	7.5-9.0	2149	28.06	10.70	8.90	741	10.5	8.3	32	TY54	
05301	P265/50R15	99S (8.5)	7.5-9.5	1720 *	25.63	10.51	8.80	811	10.5	8.3	27	ZV54	
05302	P295/50R15	105S (9.5)	8.0-10.0	2061 *	26.80	11.77	10.10	775	10.5	8.3	32	ZZ54	

* Max. Load @ 35 PSI

Notes: 2, 8



EQUUS LSi



V/H-SPEED RATED

Capable of sustaining speeds up to 149 and 130 mph, depending on the speed rating, when tested to industry standards on an indoor test wheel.

HIGH-ANGLE SHOULDER SLOTS

Breaks up the direct sound path from the tread area, resulting in a quiet ride.

OPTIMIZED TREAD COMPOUND

Balances wear and wet/winter traction.

SERIES (Size)	TREADWEAR	TRACTION	TEMP
V-RATED	360	A	A
H-RATED	420	A	A

M + S RATED **UTQG**

PASSENGER



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Max. Load @ 44 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32nds	Tread Depth mm	Ship Weight (lbs.)	Size Code	F.E.T.	Price
V-RATED BLACK SIDEWALL SIZES:												WII-2HF	
03453	205/65R15	94V	(6.0) 5.5-7.5	1477	25.41	8.37	6.46	817	11.0	8.7	22	F654	
03456	195/55R15	85V	(6.0) 5.5-7.0	1135	23.43	7.92	6.52	887	11.0	8.7	20	G554	
03463	205/60R16	92V	(6.0) 5.5-7.5	1389	25.65	8.40	6.55	809	11.0	8.7	23	E664	
03461	215/60R16	95V	(6.5) 6.0-7.5	1521	26.10	8.95	7.13	795	11.0	8.7	25	E764	
03462	225/60R16	98V	(6.5) 6.0-8.0	1653	26.56	9.15	7.16	782	11.0	8.7	26	E864	
03464	205/55R16	91V	(6.5) 5.5-7.5	1356	24.86	8.95	7.17	836	11.0	8.7	22	G664	
03465	215/55R16	93V	(7.0) 6.0-7.5	1433	25.27	8.92	7.37	789	11.0	8.7	23	G764	
03466	225/55R16	95V	(7.0) 6.0-8.0	1521	25.77	9.36	7.59	806	11.0	8.7	26	G864	
03469	225/50R16	92V	(7.0) 6.0-8.0	1389	24.89	9.15	7.69	835	11.0	8.7	23	H864	
03470	215/55R17	94V	(7.0) 6.0-7.5	1477	26.31	9.46	7.32	789	11.0	8.7	26	G774	
03475	225/55R17	97V	(7.0) 6.0-8.0	1609	26.79	9.31	7.40	774	11.0	8.7	27	G874	
03480	215/50R17	91V	(7.0) 6.0-7.5	1356	25.46	9.34	7.41	817	11.0	8.7	25	H774	
03481	225/50R17	94V	(7.0) 6.0-8.0	1477	25.89	9.17	7.69	802	11.0	8.7	26	H874	
03482	235/50R17	96V	(7.5) 6.5-8.5	1565	26.30	9.91	8.09	790	11.0	8.7	28	H974	
H-RATED BLACK SIDEWALL SIZES:												WII-2HE	
03640	195/70R14	91H	(6.0) 5.0-6.5	1356	24.80	8.02	5.97	838	11.0	8.7	20	R544	
03641	185/65R14	86H	(5.5) 5.0-6.5	1168	23.45	7.64	5.75	885	11.0	8.7	19	F444	
03642	195/65R14	89H	(6.0) 5.5-7.0	1279	23.97	8.05	6.32	866	11.0	8.7	20	F544	
03643	185/60R14	82H	(5.5) 5.0-6.5	1047	22.73	7.48	6.10	914	11.0	8.7	18	E444	
03644	195/60R14	86H	(6.0) 5.5-7.0	1168	23.20	7.97	6.29	894	11.0	8.7	19	E544	
03651	185/65R15	88H	(5.5) 5.0-6.5	1235	24.45	7.83	5.95	849	11.0	8.7	19	F454	
03652	195/65R15	91H	(6.0) 5.5-7.0	1356	24.97	8.02	6.32	831	11.0	8.7	21	F554	
03653	205/65R15	94H	(6.0) 5.5-7.5	1477	25.41	8.34	6.46	817	11.0	8.7	22	F654	
03654	215/65R15	96H	(6.5) 6.0-7.5	1565	26.04	8.69	6.76	780	11.0	8.7	24	F754	
03655	195/60R15	88H	(6.0) 5.5-7.0	1235	24.20	8.03	6.29	858	11.0	8.7	20	E554	
03656	205/60R15	91H	(6.0) 5.5-7.5	1356	24.65	8.29	6.55	841	11.0	8.7	22	E654	
03657	215/60R15	94H	(6.5) 6.0-7.5	1477	25.10	8.82	6.93	828	11.0	8.7	24	E754	
03658	225/60R15	96H	(6.5) 6.0-8.0	1565	25.56	8.97	7.16	813	11.0	8.7	23	E854	
03661	205/60R16	92H	(6.0) 5.5-7.5	1389	25.65	8.49	6.54	809	11.0	8.7	23	E664	
03662	225/60R16	98H	(6.5) 6.0-8.0	1653	26.56	9.08	7.16	782	11.0	8.7	26	E864	
03663	235/60R16	100H	(7.0) 6.5-8.5	1764	27.10	9.52	7.55	766	11.0	8.7	28	E964	
03664	205/55R16	91H	(6.5) 5.5-7.5	1356	24.86	8.59	7.17	836	11.0	8.7	22	G664	
03665	215/55R16	93H	(7.0) 6.0-7.5	1433	25.27	8.87	7.37	822	11.0	8.7	23	G764	
03666	225/55R16	95H	(7.0) 6.0-8.0	1521	25.77	9.29	7.59	806	11.0	8.7	25	G864	
03668	205/50R16	87H	(6.5) 5.5-7.5	1201	24.09	8.32	7.05	862	11.0	8.7	21	H664	
03672	235/55R17	99H	(7.5) 6.5-8.5	1709	27.15	9.94	8.01	765	11.0	8.7	28	G974	

Note: 1, 2, 8



EQUUS LSi



T-SPEED RATED

Capable of sustaining speeds up to 118 mph when tested to industry standards on an indoor test wheel.

HIGH-ANGLE SHOULDER SLOTS

Breaks up the direct sound path from the tread area, resulting in a quiet ride.

OPTIMIZED TREAD COMPOUND

Balances wear and wet/winter traction.

PASSENGER

M + S RATED **UTQG**

SERIES (SIZE) TREADWEAR TRACTION TEMP
T-RATED 620 A B



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Max. Load @ 44 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32nds	Tread Depth mm	Ship Weight (lbs.)	Size Code	F.E.T.	Price
T-RATED BLACK SIDEWALL SIZES:												WII-2HD	
03541	185/70R14	88T	(5.5) 4.5-6.0	1235	24.25	7.44	5.51	859	11.0	8.7	18	R444	
03542	195/70R14	91T	(6.0) 5.0-6.5	1356	24.80	8.05	5.86	840	11.0	8.7	19	R544	
03532	185/65R14	86T	(5.5) 5.0-6.5	1168	23.46	7.44	5.80	888	11.0	8.7	18	F444	
03534	185/65R15	88T	(5.5) 5.0-6.5	1235	24.45	7.44	5.86	853	11.0	8.7	19	F454	
03535	195/65R15	91T	(6.0) 5.5-7.0	1356	25.00	7.91	6.17	834	11.0	8.7	20	F554	
03536	205/65R15	94T	(6.0) 5.5-7.5	1477	25.47	8.23	6.42	819	11.0	8.7	20	F654	
03537	215/65R15	96T	(6.5) 6.0-7.5	1565	26.02	8.70	6.79	801	11.0	8.7	23	F754	
03521	185/60R15	84T	(5.5) 5.0-6.5	1102	23.76	7.44	5.86	876	11.0	8.7	18	E454	
03522	195/60R15	88T	(6.0) 5.5-7.0	1235	24.21	7.91	6.25	860	11.0	8.7	19	E554	
03523	205/60R15	91T	(6.0) 5.5-7.5	1356	24.69	8.23	6.50	844	11.0	8.7	20	E654	
03524	215/60R15	94T	(6.5) 6.0-7.5	1477	25.16	8.70	6.87	829	11.0	8.7	22	E754	
03538	215/65R16	98T	(6.5) 6.0-7.5	1653	26.92	8.79	6.79	770	11.0	8.7	25	F764	
03525	215/60R16	95T	(6.5) 6.0-7.5	1521	26.07	8.92	6.87	795	11.0	8.7	24	E764	
03527	225/60R16	98T	(6.5) 6.0-8.0	1653	26.54	9.21	7.09	781	11.0	8.7	25	E864	
03528	235/60R16	100T	(7.0) 6.5-8.5	1764	27.02	9.70	7.46	767	11.0	8.7	26	E964	
03513	205/55R16	91T	(6.5) 5.5-7.5	1356	24.88	8.43	6.99	837	11.0	8.7	22	G664	
03518	225/55R17	97T	(7.0) 6.0-8.0	1609	26.79	9.31	7.40	774	11.0	8.7	27	G874	
T-RATED (.75") WHITE SIDEWALL SIZES:												WKI-2HD	
03544	205/70R15	96T	(6.0) 5.0-7.0	1565	26.34	8.23	6.10	791	11.0	8.7	22	R654	
T-RATED (.43") WHITE SIDEWALL SIZES:												W6I-2HD	
03546	215/70R15	98T	(6.5) 5.5-7.0	1653	26.89	8.70	6.45	775	11.0	8.7	23	R754	
03526	225/60R16	98T	(6.5) 6.0-8.0	1653	26.54	9.21	7.09	781	11.0	8.7	25	E864	

Note: 1, 2, 8



QUASAR PLUS RADIAL



EXCELLENT MILEAGE AND PERFORMANCE

Styled for family car use but designed for sports-car-like responsiveness. This touring tire will give you excellent mileage, yet its mud and snow designation assures you aggressive performance when needed.

ALL-WEATHER TREAD

"See-through" grooves and wide, lateral traction slots carve out a 5-rib tread design to provide excellent all-weather performance. Elongated siping in the shoulder elements enhances the tire's gripping ability in diverse weather conditions.

M + S RATED **UTQG**

SERIES (Size) TREADWEAR TRACTION TEMP
ALL 520 A B

PASSENGER

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth		Ship Weight (lbs.)	Size Code	F.E.T.	Price	
								32nds	mm					
BLACK SIDEWALL SIZES:													W11-430	
43024	175/70R13	82S	(5.0) 4.5-6.0	1047	22.68	6.89	5.10	914	10.5	8.3	14	R334		
43026	175/70R14	84S	(5.0) 4.5-6.0	1102	23.68	6.89	5.10	876	10.5	8.3	16	R344		
43027	185/70R14	88S	(5.5) 4.5-6.0	1235	24.23	7.40	5.30	856	10.5	8.3	17	R444		
43028	195/70R14	91S	(6.0) 5.0-6.5	1356	24.78	7.80	5.60	837	10.5	8.3	18	R544		
43029	205/70R14	95S	(6.0) 5.0-7.0	1521	25.28	8.11	5.80	822	10.5	8.3	19	R644		
43018	175/65R14	82S	(5.0) 5.0-6.0	1047	22.95	6.85	5.20	903	10.5	8.3	16	F344		
43019	185/65R14	86S	(5.5) 5.0-6.5	1168	23.40	7.35	5.55	886	10.5	8.3	17	F444		
43020	195/65R14	89S	(6.0) 5.5-7.0	1279	23.95	7.80	5.85	865	10.5	8.3	19	F544		
43089	P235/75R15XL	108S	(6.5) 6.0-8.0	2183**	28.85	9.40	6.95	720	11.0	8.7	30	W956		
43031	205/70R15	96S	(6.0) 5.0-7.0	1565	26.28	8.11	5.80	790	11.0	8.7	20	R654		
43032	215/70R15	98S	(6.5) 5.5-7.0	1653	26.78	8.58	6.10	774	11.0	8.7	22	R754		
43040	185/65R15	88T	(5.5) 5.0-6.5	1235*	24.40	7.35	5.55	852	10.5	8.3	18	F454		
43021	195/65R15	91S	(6.0) 5.5-7.0	1356	24.90	7.80	5.85	832	10.5	8.3	20	F554		
43022	205/65R15	94S	(6.0) 5.5-7.5	1477	25.37	8.16	6.05	817	11.0	8.7	21	F654		
43023	215/65R15	96S	(6.5) 6.0-7.5	1565	25.95	8.65	6.50	799	11.0	8.7	22	F754		
43035	P205/55R15	87S	(6.5) 5.5-7.5	1201	23.80	8.30	7.00	870	10.5	8.3	21	C654		
43042	215/65R16	98T	(6.5) 6.0-7.5	1653*	26.95	8.65	6.50	767	11.0	8.7	24	F764		
43016	P215/60R16	94S	(6.5) 6.0-7.5	1477	26.05	8.55	6.55	796	11.0	8.7	23	T764		
43017	P225/60R16	97S	(6.5) 6.0-8.0	1609	26.50	8.80	6.80	782	11.0	8.7	24	T864		
43015	205/55R16	91S	(6.5) 5.5-7.5	1356	24.80	8.30	7.00	836	10.5	8.3	22	G664		

Note: 1, 2, 8
 * Max. Load @ 44 PSI.
 ** Max. Load @ 41 PSI.



QUASAR PLUS RADIAL



EXCELLENT MILEAGE AND PERFORMANCE

Styled for family car use but designed for sports-car-like responsiveness. This touring tire will give you excellent mileage, yet its mud and snow designation assures you aggressive performance when needed.


ALL-WEATHER TREAD

"See-through" grooves and wide, lateral traction slots carve out a 5-rib tread design to provide excellent all-weather performance. Elongated siping in the shoulder elements enhances the tire's gripping ability in diverse weather conditions.

PASSENGER

M + S RATED **UTQG**

SERIES (SIZE) TREADWEAR TRACTION TEMP
ALL 520 A B



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth		Ship Weight (lbs.)	Size Code	F.E.T.	Price	
								32nds	mm					
(.65") WHITE SIDEWALL SIZES: W81-430														
43081	P185/75R14	89S	(5.0) 4.5-6.0	1290	24.97	7.40	5.35	830	11.0	8.7	19	W444		
43082	P195/75R14	92S	(5.5) 5.0-6.5	1400	25.50	7.90	5.70	815	11.0	8.7	21	W544		
43083	P205/75R14	95S	(5.5) 5.0-7.0	1532	26.15	8.15	5.95	793	11.0	8.7	21	W644		
43005	175/70R14	84S	(5.0) 4.5-6.0	1102	23.68	6.89	5.10	876	10.5	8.3	16	R344		
43006	185/70R14	88S	(5.5) 4.5-6.0	1235	24.23	7.40	5.30	856	10.5	8.3	18	R444		
43007	195/70R14	91S	(6.0) 5.0-6.5	1356	24.78	7.80	5.60	837	10.5	8.3	18	R544		
43008	205/70R14	95S	(6.0) 5.0-7.0	1521	25.28	8.11	5.80	822	10.5	8.3	20	R644		
43009	215/70R14	96S	(6.5) 5.5-7.0	1565	25.78	8.58	6.10	804	11.0	8.7	22	R744		
(.75") WHITE SIDEWALL SIZES: WK1-430														
43084	P205/75R15	97S	(5.5) 5.0-7.0	1598	27.15	8.15	5.95	763	11.0	8.7	23	W654		
43085	P215/75R15	100S	(6.0) 5.5-7.0	1742	27.80	8.70	6.35	746	11.0	8.7	25	W754		
43086	P225/75R15	102S	(6.0) 6.0-7.5	1874	28.30	8.95	6.55	732	11.0	8.7	26	W854		
43087	P235/75R15	105S	(6.5) 6.0-8.0	2028	28.85	9.40	6.95	720	11.0	8.7	28	W954		
43088	P235/75R15XL	108S	(6.5) 6.0-8.0	2183**	28.85	9.40	6.95	720	11.0	8.7	31	W956		
43010	205/70R15	96S	(6.0) 5.0-7.0	1565	26.28	8.11	5.80	790	11.0	8.7	21	R654		
43011	215/70R15	98S	(6.5) 5.5-7.0	1653	26.78	8.58	6.10	774	11.0	8.7	23	R754		

Note: 1, 2, 8

** Max Load @ 41 PSI



Alpha 365 Radial



ALL-WEATHER TREAD PATTERN

Squared-off tread elements form an effective pattern of distinct gripping edges for year-round traction. Wide circumferential grooves and lateral grooves promote excellent wet traction by channeling water out from the contact patch.

STEEL-BELTED STRENGTH

Strong, steel cord belts encircle the tire giving rigidity to the tread for low rolling resistance. The steel cord is coated with a high modulus stock which contributes to overall durability and performance.

M + S RATED UTQG SERIES (Size) TREADWEAR TRACTION TEMP
ALL 440 A B

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth		Ship Weight (lbs.)	Size Code	F.E.T.	Price
								32nds	mm				
BLACK SIDEWALL SIZES: W11-372													
37207	P175/70R13	82S	(5.0) 4.5-6.0	1036	22.68	6.89	4.90	914	10.0	7.9	14	U334	
37208	P185/70R13	85S	(5.5) 4.5-6.0	1135	23.23	7.40	5.10	893	10.0	7.9	15	U434	
37226	P175/70R14	84S	(5.0) 4.5-6.0	1102	23.18	6.89	4.90	896	10.0	7.9	16	U344	
37209	P185/70R14	87S	(5.5) 4.5-6.0	1201	24.23	7.40	5.10	856	10.0	7.9	17	U444	
37210	P195/70R14	90S	(6.0) 5.0-6.5	1312	24.78	7.80	5.40	837	10.0	7.9	17	U544	
37214	P205/70R14	93S	(6.0) 5.0-7.0	1433	25.28	8.11	5.60	822	10.0	7.9	18	U644	
37218	P175/65R14	81S	(5.0) 5.0-6.0	1019	22.90	6.85	5.00	907	10.0	7.9	15	S344	
37219	P185/65R14	85S	(5.5) 5.0-6.5	1124	23.35	7.35	5.35	889	10.0	7.9	17	S444	
37211	P205/70R15	95S	(6.0) 5.0-7.0	1499	26.28	8.11	5.60	790	10.0	7.9	19	U654	
37215	P195/65R15	89S	(6.0) 5.5-7.0	1279	24.90	7.80	5.70	839	10.0	7.9	18	S554	
37216	P205/65R15	92S	(6.0) 5.5-7.5	1400	25.25	8.16	5.85	823	10.0	7.9	20	S654	
37220	P215/65R15	95S	(6.5) 6.0-7.5	1510	25.88	8.65	6.38	807	10.0	7.9	22	S754	
37235	P215/60R16	94S	(6.5) 6.0-7.5	1477	26.10	8.55	6.40	801	10.0	7.9	23	T764	
37236	P225/60R16	97S	(6.5) 6.0-8.0	1609	26.52	8.80	6.60	788	10.0	7.9	24	T864	
37232	P205/55R16	89S	(6.5) 5.5-7.5	1279	24.75	8.30	7.10	844	10.0	7.9	22	C664	
(.50") WHITE SIDEWALL SIZES: WHI-132													
13201	P155/80R13	STD	(4.5) 4.0-5.0	959	22.75	6.10	3.90	911	9.5	7.5	12	X134	
13202	P165/80R13	STD	(4.5) 4.0-5.5	1069	23.30	6.45	4.10	890	10.0	7.9	13	X234	
13203	P175/80R13	STD	(5.0) 4.5-6.0	1179	24.00	6.85	4.40	864	10.0	7.9	14	X334	
13204	P185/80R13	STD	(5.0) 4.5-6.0	1301	24.50	7.20	4.60	846	10.0	7.9	15	X434	
(.65") WHITE SIDEWALL SIZES: W81-132													
* 46105	P175/75R14	STD	(5.0) 4.5-6.0	1168	24.20	6.85	4.40	857	10.0	7.9	15	W344	
13205	P185/75R14	STD	(5.0) 4.5-6.0	1290	24.80	7.20	4.60	836	10.0	7.9	17	W444	
13206	P195/75R14	STD	(5.5) 5.0-6.5	1400	25.40	7.60	4.90	816	10.0	7.9	18	W544	
13207	P205/75R14	95	(5.5) 5.0-7.0	1532	25.95	7.95	5.10	799	10.5	8.3	19	W644	
13208	P215/75R14	STD	(6.0) 5.5-7.0	1664	26.55	8.40	5.40	781	10.5	8.3	20	W744	
(.75") WHITE SIDEWALL SIZES: WKI-132													
13210	P205/75R15	STD	(5.5) 5.0-7.0	1598	26.95	7.95	5.10	769	10.5	8.3	20	W654	
13211	P215/75R15	100	(6.0) 5.5-7.0	1742	27.55	8.40	5.40	753	10.5	8.3	22	W754	
13212	P225/75R15	STD	(6.0) 6.0-7.5	1874	28.05	8.70	5.60	739	10.5	8.3	23	W854	
13213	P235/75R15	105	(6.5) 6.0-8.0	2028	28.65	9.10	5.90	724	11.0	8.7	24	W954	
(.65") WHITE SIDEWALL SIZES: W81-372													
37201	P185/70R14	87S	(5.5) 4.5-6.0	1201	24.23	7.40	5.10	856	10.0	7.9	17	U444	
37202	P195/70R14	90S	(6.0) 5.0-6.5	1312	24.78	7.80	5.40	837	10.0	7.9	18	U544	
37203	P205/70R14	93S	(6.0) 5.0-7.0	1433	25.28	8.11	5.60	822	10.0	7.9	19	U644	
37204	P215/70R14	96S	(6.5) 5.5-7.0	1554	25.78	8.58	5.90	804	10.0	7.9	21	U744	
(.75") WHITE SIDEWALL SIZES: WKI-372													
37205	P205/70R15	95S	(6.0) 5.0-7.0	1499	26.28	8.11	5.60	790	10.0	7.9	20	U654	
37206	P215/70R15	97S	(6.5) 5.5-7.0	1620	26.78	8.58	5.90	774	10.0	7.9	22	U754	
37217	P225/70R15	100S	(6.5) 6.0-7.5	1753	27.28	8.85	6.15	760	10.0	7.9	24	U854	

PASSENGER

Notes: 2, 8

* Supplied in Mentor All Season design (W81-461)



WINTERCAT RADIAL SST



HIGH TRACTION TREAD DESIGN

The intricate tread pattern balances winter traction and a smooth, quiet ride. The deep lateral and notched circumferential grooves provide excellent evacuation of water and slush from the tread contact patch.

PATENTED "SNOW GROOVE" DESIGN TECHNOLOGY

Provides biting edges for excellent snow and ice traction without reducing element stiffness. The snow groove enhances the retention of snow in the outer circumferential grooves to capitalize on the higher traction characteristics of "snow on snow" versus "snow on rubber".



M + S RATED



SNOW

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Pass. Max. Load @ 35 PSI	LT Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32nds	Tread Depth mm	Stud Size TSM#	EURO#	Ship Weight (lbs.)	Size Code	F.E.T.	Price
BLACK SIDEWALL SIZES: WII-3EH																
12271	225/70R14 99S	(6.5) 6.0-7.5	1709	1554	26.25	9.10	7.00	790	15.0	11.9	13	9-12	26	R844		
12244	235/75R15 105S	(6.5) 6.0-8.0	2039	1854	29.00	9.60	7.20	717	15.0	11.9	13	9-12	32	V954		
12247	265/75R15 112S	(7.5) 7.0-9.0	2469	2245	30.60	10.65	8.10	679	15.0	11.9	13	9-12	37	VV54		
12275	235/70R15 103S	(7.0) 6.0-7.5	1929	1754	28.00	9.65	7.40	746	15.0	11.9	13	9-12	29	R954		
12278	265/70R15 112S	(8.0) 7.0-9.0	2469	2245	29.43	10.45	8.00	707	15.0	11.9	13	9-12	35	RV54		
12248	225/75R16 104S	(6.0) 6.0-7.5	1984	1804	29.18	8.65	6.80	713	15.0	11.9	13	9-12	31	V864		
12249	235/75R16 108S	(6.5) 6.0-8.0	2205	2005	29.85	9.30	7.00	697	15.0	11.9	13	9-12	34	V964		
12250	245/75R16 111S	(7.0) 6.5-8.0	2403	2185	30.40	9.60	7.40	683	15.0	11.9	13	9-12	35	V064		
12251	265/75R16 116S	(7.5) 7.0-9.0	2756	2505	31.60	10.60	8.10	658	15.0	11.9	13	9-12	39	VV64		
12280	215/70R16 100S	(6.5) 5.5-7.0	1764	1604	27.75	8.80	7.20	753	15.0	11.9	13	9-12	30	R764		
12281	225/70R16 102S	(6.5) 6.0-7.5	1874	1704	28.30	9.00	7.00	733	15.0	11.9	13	9-12	30	R864		
12282	235/70R16 106S	(7.0) 6.0-7.5	2094	1904	28.85	9.40	7.40	719	15.0	11.9	13	9-12	32	R964		
12283	245/70R16 107S	(7.0) 6.5-8.0	2149	1954	29.50	9.85	7.70	705	15.0	11.9	13	9-12	34	R064		
12284	255/70R16 111S	(7.5) 6.5-8.0	2403	2185	29.90	10.30	8.00	693	15.0	11.9	13	9-12	35	RX64		
12285	265/70R16 112S	(8.0) 7.0-9.0	2469	2245	30.40	10.80	8.00	682	15.0	11.9	13	9-12	39	RV64		
12286	245/70R17 110S	(7.0) 6.5-8.0	2337*	2125*	30.50	9.85	7.70	681	14.0	11.1	13	9-12	35	R074		
12288	265/70R17 115S	(8.0) 7.0-9.0	2679	2435	31.40	10.65	8.30	660	15.0	11.9	13	9-12	41	RV74		
OUTLINE WHITE LETTER SIZES: WLI-3EH																
12290	255/65R16 109S	(7.5) 7.0-9.0	2271	2065	29.18	10.24	8.25	718	14.0	11.1	13	9-12	35	FX64		
12293	235/65R17 104S	(7.0) 6.5-8.5	1984	1804	29.11	9.45	7.65	716	14.0	11.1	13	9-12	33	F974		
12294	245/65R17 107S	(7.0) 7.0-8.5	2149	1954	29.52	9.82	9.27	708	14.0	11.1	13	9-12	35	F074		
12296	275/60R17 110S	(8.0) 7.5-9.5	2337	2125	30.10	11.20	9.02	699	14.0	11.1	13	9-12	39	EY74		

Notes: 1, 2, 4, 5, 8

* Max. Load @ 44 PSI.



WINTERCAT RADIAL SST



HIGH TRACTION TREAD DESIGN

The intricate tread pattern balances winter traction and a smooth, quiet ride. The deep lateral and notched circumferential grooves provide excellent evacuation of water and slush from the tread contact patch.

PATENTED "SNOW GROOVE" DESIGN TECHNOLOGY

Provides biting edges for excellent snow and ice traction without reducing element stiffness. The snow groove enhances the retention of snow in the outer circumferential grooves to capitalize on the higher traction characteristics of "snow on snow" versus "snow on rubber".



M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width/ Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS										Ship Wght. (lbs.)	Size Code	E.E.T.	Price
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	STUD SIZE TSM#	EURO. #				
				BLACK SIDEWALL SIZES:										W11-5BA							
12220	LT235/75R15 104/101Q C		(6.5) 6.0-7.0	50	1820	50	1985	28.82	9.00	9.7	10.8	13.4	715	17.0	13.5	15	9-13	34	W956		
12214	31X10.50R15LT 109Q C		(8.5) 7.0-9.0	-	-	50	2270	30.25	10.50	11.4	-	14.0	685	19.0	15.1	15	9-13	40	3056		
12222	LT215/85R16 115/112Q E		(6.0) 5.5-7.0	80	2470	80	2680	30.28	9.10	10.0	9.9	14.1	684	17.0	13.5	15	9-13	38	Y760		
12224	LT235/85R16 120/116Q E		(6.5) 6.0-7.0	80	2778	80	3042	31.78	9.31	10.5	10.8	14.7	654	17.0	13.5	15	9-13	42	Y960		
12231	LT225/75R16 115/112Q E		(6.0) 6.0-7.0	80	2470	80	2680	29.30	8.95	9.8	10.2	13.6	710	17.0	13.5	15	9-13	38	W860		
12234	LT245/75R16 108/104Q C		(7.0) 6.5-7.5	50	2006	50	2205	30.44	9.57	10.3	11.3	14.2	680	17.0	13.5	15	9-13	40	W066		
12232	LT245/75R16 120/116Q E		(7.0) 6.5-7.5	80	2778	80	3042	30.44	9.57	10.3	11.3	14.2	680	18.0	14.3	15	9-13	43	W060		
12235	LT265/75R16 112/109Q C		(7.5) 7.0-8.0	50	2270	50	2470	31.54	10.33	11.3	12.2	14.7	654	17.0	13.5	15	9-13	43	W166		
12237	LT265/75R16 123/120Q E		(7.5) 7.0-8.5	80	3085	80	3415	31.54	10.50	11.3	12.2	14.7	654	17.0	13.5	15	9-13	47	W160		
12219	LT235/80R17 120/117Q E		(6.5) 6.0-8.0	80	2835	80	3085	31.85	9.40	10.3	10.8	14.5	652	17.0	13.5	15	9-13	44	X970		
12216	LT245/70R17 119/116Q E		(7.0) 6.5-8.0	80	2755	80	3000	30.45	10.07	10.7	11.3	14.1	679	17.0	13.5	15	9-13	44	U070		
12217	LT265/70R17 121/118Q E		(8.0) 7.0-9.0	80	2910	80	3195	31.65	11.03	11.3	12.4	14.7	656	17.0	13.5	15	9-13	50	U170		

Notes: 2, 3, 5, 6, 7, 8

MONS



WILDCAT TOURING SLT



TABBED TREAD BLOCKS

Keeps lateral slots and grooves open during acceleration, braking and cornering.

COMPUTER GENERATED TREAD DESIGN

Computer-generated SNDQL Sound Quality tread design optimizes the tread pattern's pitch sequence for a quiet ride.

FOUR WIDE CIRCUMFERENTIAL GROOVES

Offers resistance to hydroplaning and improves wet traction.

SUV SIZES M + S RATED **UTQG** METRICS 520 A B

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Pass. Max. Load @ 35 PSI	LT Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth		Ship Weight (lbs.)	Size Code	F.E.T.	Price	
									32nds	mm					
OUTLINE WHITE LETTER SIZES:													WLI-2FK		
02813	235/75R15 105S	(6.5) 6.0-7.5	2039**	1854**	28.85	9.30	6.45	719	13.5	10.7	29	V954			
02814	235/75R15RE109S	(6.5) 6.0-8.0	2271*	2065*	29.00	9.40	6.85	717	13.5	10.7	32	V956			
02817	265/75R15 112S	(7.5) 7.0-8.5	2469	2245	30.50	10.65	7.60	680	14.0	11.1	38	VV54			
02821	225/70R15 100S	(6.5) 6.0-7.0	1764	1604	27.25	9.10	7.00	761	12.0	9.5	27	R854			
02822	235/70R15 103S	(7.0) 6.0-7.5	1929	1754	27.80	9.65	7.40	746	12.0	9.5	29	R954			
02825	225/75R16 104S	(6.0) 6.0-7.5	1984	1804	29.15	8.65	6.40	711	13.0	10.3	30	V864			
02827	245/75R16 111S	(7.0) 6.5-7.5	2403	2185	30.35	9.60	7.00	683	13.5	10.7	34	V064			
02829	265/75R16 116S	(7.5) 7.0-8.5	2756	2505	31.50	10.60	7.60	658	14.0	11.1	40	VV64			
02832	225/70R16 102S	(6.5) 6.0-7.0	1874	1704	28.30	9.00	7.00	733	13.0	10.3	30	R864			
02833	235/70R16 106S	(7.0) 6.0-7.5	2094	1904	28.85	9.40	7.40	719	13.0	10.3	33	R964			
02834	245/70R16 107S	(7.0) 6.5-8.0	2149	1954	29.40	9.90	7.70	705	13.0	10.3	33	R064			
02835	255/70R16 111S	(7.5) 6.5-8.0	2403	2185	29.95	10.30	8.00	692	13.5	10.7	36	RX64			
02836	265/70R16 112S	(8.0) 7.0-9.0	2469	2245	30.40	10.80	8.00	682	13.5	10.7	37	RV64			
02820	255/65R16 109S	(7.5) 7.0-9.0	2271	2065	29.06	10.24	8.25	715	12.0	9.5	32	FX64			
02838	265/70R17 115S	(8.0) 7.0-8.5	2679	2435	31.40	10.65	8.30	660	13.5	10.7	40	RV74			
02819	235/65R17 104S	(7.0) 6.5-8.5	1984	1804	29.06	9.45	7.65	715	12.0	9.5	31	F974			
02837	245/65R17 107S	(7.0) 7.0-8.5	2149	1954	29.45	9.62	7.85	685	12.0	9.5	33	F074			
02816	275/60R17 110S	(8.0) 7.5-9.5	2337	2125	29.88	11.00	9.00	675	12.0	9.5	37	EY74			

Notes: 1, 2, 4, 8

* Max. Load @ 41 PSI.

** Max. Load @ 44 PSI.

SUV/LIGHT TRUCK

LIGHT TRUCK SIZES

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS							Ship Wght. (lbs.)	Size Code	F.E.T.	Price	
				Inf. Press.	Max. Load Lbs.	Inf. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds					mm
BLACK SIDEWALL SIZES:													WII-759						
02894	LT215/85R16 115/112Q	E	(6.0) 5.5-7.0	80	2470	80	2680	30.26	8.21	9.7	9.9	14.1	683	16.0	12.7	38	Y760		
02897	LT235/85R16 120/116Q	E	(6.5) 6.0-7.0	80	2778	80	3042	31.65	9.31	10.5	10.8	14.7	654	16.5	13.1	43	Y960		
02876	LT225/75R16 115/112Q	E	(6.0) 6.0-7.0	80	2470	80	2680	29.39	8.95	9.8	10.2	13.6	710	16.5	13.1	38	W860		
02880	LT245/75R16 120/116Q	E	(7.0) 6.5-7.5	80	2778	80	3042	30.44	9.57	10.3	11.3	14.2	680	16.5	13.1	44	W060		
OUTLINE WHITE LETTER SIZES:													WLI-759						
02851	LT235/75R15 104/101Q	C	(6.5) 6.0-7.0	50	1820	50	1985	28.83	9.00	9.6	10.8	13.4	719	16.0	12.7	34	W956		
02864	LT245/75R16 108/104Q	C	(7.0) 6.5-7.5	50	2006	50	2205	30.44	9.57	10.3	11.3	14.2	680	16.5	13.1	41	W066		
02867	LT265/75R16 112/109Q	C	(7.5) 7.0-8.5	50	2270	50	2470	31.60	10.33	11.3	12.2	14.7	654	16.0	12.7	43	W166		
02869	LT265/75R16 123/120Q	E	(7.5) 7.0-8.0	80	3085	80	3415	31.61	10.40	11.3	12.2	14.7	654	16.0	12.7	48	W160		
02892	LT265/70R17 121/118R	E	(8.0) 7.0-9.0	80	2910	80	3195	31.60	10.65	11.3	12.4	14.7	656	16.0	12.7051	4170			

Notes: 2, 3, 6, 7, 8



WILDCAT RADIAL A/T



5-RIB, ALL-TERRAIN DESIGN

Allows tire to perform equally well on and off the road.

DUAL RADIUS TREAD ARC


Gives uniform pressure distribution across the contact patch for even wear and consistent grip.

SOLID CENTER RIB

Improves steering response while reducing noise.

M + S RATED **UTQG**

SERIES (Size) TREADWEAR TRACTION TEMP
ALL 500 A B



Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Pass. Max. Load @ 44 PSI	LT Max. Load @ 44 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth		Ship Weight (lbs.)	Size Code	F.E.T.	Price
									32nds	mm				
OUTLINE WHITE LETTER SIZES:														
WLI-4GS														
04217	225/70R14 99S	(6.5) 6.0-7.0	1709	1554	26.45	8.90	7.05	795	12.5	9.9	26	R844		
04203	205/75R15 97S	(5.5) 5.0-6.5	1609	1463	27.10	7.90	6.00	771	13.5	10.7	24	V654		
04204	215/75R15 100S	(6.0) 5.5-7.0	1764	1604	27.60	8.40	6.40	757	13.5	10.7	26	V754		
04205	225/75R15 102S	(6.0) 6.0-7.0	1874	1704	28.33	8.70	6.65	737	13.5	10.7	28	V854		
04206	235/75R15 105S	(6.5) 6.0-7.5	2039	1854	28.90	9.23	7.00	723	14.0	11.1	30	V954		
04208	265/75R15 112S	(7.5) 7.0-8.5	2469	2245	30.69	10.50	8.00	681	14.5	11.5	37	VV54		
04218	225/70R15 100S	(6.5) 6.0-7.5	1764	1604	27.45	9.00	7.05	763	12.5	9.9	27	R854		
04219	235/70R15 103S	(7.0) 6.0-8.0	1929	1754	27.99	9.45	7.40	747	12.5	9.9	29	R954		
04221	265/70R15 112S	(8.0) 7.0-9.0	2469	2245	29.60	10.60	8.45	706	14.0	11.1	36	RV54		
04214	245/75R16 111S	(7.0) 6.5-7.5	2403	2185	30.52	9.65	7.40	685	14.0	11.1	34	V064		
04216	265/75R16 116S	(7.5) 7.0-8.5	2756	2505	31.65	10.51	8.00	660	14.5	11.5	38	VV64		
04222	225/70R16 102S	(6.5) 6.0-7.0	1874	1704	28.40	8.90	7.05	736	13.5	10.7	30	R864		
04223	235/70R16 106S	(7.0) 6.0-8.0	2094	1904	28.99	9.46	7.40	721	13.5	10.7	32	R964		
04224	245/70R16 107S	(7.0) 6.5-8.0	2149	1954	29.59	9.79	7.70	707	13.5	10.7	33	R064		
04225	255/70R16 111S	(7.5) 6.5-8.5	2403	2185	30.10	10.24	8.00	695	14.0	11.1	35	RX64		
04226	265/70R16 112S	(8.0) 7.0-9.0	2469	2245	30.52	10.73	8.30	681	14.0	11.1	37	RV64		
04230	265/70R17 115S	(8.0) 7.0-9.0	2679	2435	31.60	10.70	8.45	664	14.0	11.1	40	RV74		

Notes: 1, 2, 4, 8

SUV/LIGHT TRUCK



WILDCAT RADIAL A/T



5-RIB, ALL-TERRAIN DESIGN

Allows tire to perform equally well on and off the road.


DUAL RADIUS TREAD ARC

Gives uniform pressure distribution across the contact patch for even wear and consistent grip.

SOLID CENTER RIB

Improves steering response while reducing noise.

M + S RATED



Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS										F.E.T.	Price
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	Ship Wght. (lbs.)	Size Code		
BLACK SIDEWALL SIZES:								WII-5CC											
04267	LT235/85R16 120/116Q	E	(6.5) 6.0-7.0	80	2778	80	3042	31.78	9.36	10.6	10.8	14.8	661	16.5	13.1	42	Y960		
04261	LT225/75R16 110/107Q	D	(6.0) 6.0-7.0	65	2150	65	2335	29.44	8.82	9.4	10.2	13.6	712	16.5	13.1	37	W868		
04262	LT225/75R16 115/112Q	E	(6.0) 6.0-7.0	80	2470	80	2680	29.48	8.82	9.7	10.2	13.6	712	16.5	13.1	39	W860		
04264	LT245/75R16 120/116Q	E	(7.0) 6.5-7.5	80	2778	80	3042	30.52	9.62	10.0	11.3	14.2	688	16.5	13.1	43	W060		
OUTLINE WHITE LETTER SIZES:								WLI-5CC											
04251	LT235/75R15 104/101Q	C	(6.5) 6.0-7.0	50	1820	50	1985	28.95	9.00	9.7	10.8	13.5	723	16.0	12.7	34	W956		
04252	30X9.50R15LT 104Q	C	(7.5) 6.5-8.5	-	-	50	1985	29.30	9.30	10.1	-	13.6	711	16.5	13.1	36	3956		
04253	31X10.50R15LT 109Q	C	(8.5) 7.0-9.0	-	-	50	2270	30.30	10.54	11.4	-	14.0	688	16.5	13.1	40	3056		
04256	35X12.50R15LT 113Q	C	(10.0) 8.5-11.0	-	-	35	2535	34.75	12.87	13.3	-	16.6	602	17.0	13.5	61	3556		
04276	LT245/75R16 120/116Q	E	(7.0) 6.5-7.5	80	2778	80	3042	30.52	9.62	10.4	11.3	14.2	688	16.5	13.1	43	W060		
04277	LT265/75R16 112/109Q	C	(7.5) 7.0-8.0	50	2270	50	2470	31.78	10.40	11.4	12.2	14.8	660	16.5	13.1	45	W166		
04279	LT265/75R16 123/120Q	E	(7.5) 7.0-8.0	80	3085	80	3415	31.81	10.57	11.4	12.2	14.8	660	16.5	13.1	49	W160		
04281	LT285/75R16 122/119Q	D	(8.0) 7.5-9.0	65	3000	65	3305	32.93	11.47	12.7	13.1	15.1	640	17.0	13.5	54	W468		
04283	LT315/75R16 121Q	D	(8.5) 8.0-10.0	-	-	50	3195	34.75	12.87	13.3	-	16.0	603	17.0	13.5	62	WB68		
04285	LT255/70R16 108/104Q	C	(7.5) 6.5-8.0	50	1985	50	2205	30.00	10.36	11.3	11.9	13.7	695	16.5	13.1	41	UX66		
04290	LT305/70R16 118/115Q	D	(9.0) 8.0-9.5	50	2680	50	2910	32.80	12.24	12.6	14.2	15.1	639	17.0	13.5	56	UA68		
04295	LT265/70R17 112/109Q	C	(8.0) 7.0-8.5	50	2270	50	2470	31.60	10.85	12.0	12.4	14.0	659	16.5	13.1	46	U176		

Notes: 2, 3, 5, 6, 7, 8

SUV/LIGHT TRUCK



WILDCAT LT ALL TERRAIN



WIDE FOOT PRINT

Offering a wider tread footprint than our previously designed radials, this all terrain tire is designed to wear evenly. Belt edges are supported by specially designed sidewall wedges.

STEEL-BELTED CONSTRUCTION

Steel cords help shield the tread area against penetration and impact breaks. The strength of steel and an optimized tread radius provide a big, flat treadprint for total road contact and stability.

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS										Price
				Inf. Press.	Max. Load Lbs.	Inf. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	Ship Wght. (lbs.)	Size Code	
BLACK SIDEWALL SIZES:																		
W11-615																		
61509	LT215/85R16 115/112N	E	(6.0) 5.5-7.0	80	2470	80	2680	30.30	9.10	10.0	9.9	14.1	684	16.5	13.1	38	Y760	
61511	LT235/85R16 120/116N	E	(6.5) 6.0-7.0	80	2778	80	3042	31.75	9.21	10.5	10.8	14.7	654	17.0	13.5	41	Y960	
61506	LT225/75R16 115/112N	E	(6.0) 6.0-7.0	80	2470	80	2680	29.42	8.68	9.8	10.2	13.6	710	16.5	13.1	37	W860	
61507	LT245/75R16 120/116N	E	(7.0) 6.5-7.0	80	2778	80	3042	30.65	9.35	10.3	11.3	14.2	675	16.5	13.1	41	W060	
OUTLINE WHITE LETTER SIZES:																		
WLI-615																		
61520	27X8.50R14LT 95Q	C	(7.0) 6.0-7.5	-	-	50	1520	26.50	8.70	9.5	-	12.3	782	16.5	13.1	29	2746	
61524	33X12.50R15LT 108Q	C	(10.0) 8.5-11.0	-	-	35	2205	32.40	12.40	13.5	-	15.0	640	18.0	14.3	50	3256	
61537	LT265/75R16 123/120N	E	(7.5) 7.0-8.0	80	3085	80	3415	31.70	10.45	11.3	12.2	14.7	654	16.0	12.7	48	W160	
61530	LT285/75R16 122/119N	D	(8.0) 7.5-9.0	65	3000	65	3305	32.85	11.30	12.5	13.3	15.1	628	16.5	13.1	53	W468	
61525	33X12.50R16.5L 118N	D	(9.75) 8.25-10.5	-	-	50	2910	32.30	12.70	13.8	-	15.0	642	18.0	14.3	55	3268	

Notes: 2, 3, 6, 7, 8

SUV/LIGHT TRUCK



DURANGO RADIAL A/T



ALL-WEATHER TREAD DESIGN

Nubby tread pattern combines shoulder lugs and tread cleats for deep biting traction and quiet running at high speeds.

RADIAL CONSTRUCTION

Offers performance advantages over equivalent size bias LT tires, such as low rolling resistance which improves fuel economy.

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width/ Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS										Ship Wght. (lbs.)	Size Code	F.E.T.	Price
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	STUD SIZE TSM#	EURO. #				
OUTLINE WHITE LETTER SIZES:																		WLI-533			
53326	35X12.50R15LT 113Q C	(10)	8.5-11.0	-	-	35	2535	34.75	12.87	13.3	-	16.6	615	18.0	14.3		63	3556			
53330	LT285/75R16 122/119N D	(8.0)	7.5-9.0	65	3000	65	3305	32.85	11.30	12.5	13.3	15.1	628	16.5	13.1	15	9-13	53	W468		
53336	LT315/75R16 121N D	(8.5)	8.0-10.0	-	-	50	3195	34.75	12.87	13.30	-	16.6	598	18.0	14.3			62	WB68		
53332	LT255/70R16 108/104Q C	(7.5)	6.5-8.0	50	1985	50	2205	30.00	10.36	11.3	12.3	13.7	691	16.0	12.7			41	UX66		
53338	LT305/70R16 118/115N D	(9.0)	8.0-9.5	50	2680	50	2910	32.75	11.90	12.6		15.1	626	18.0	14.3			58	UA68		
53334	LT265/70R17 112/109Q C	(8.0)	7.0-8.5	50	2270	50	2470	31.60	10.85	12.0	13.0	14.5	656	16.0	12.7			46	U176		

Notes: 2, 3, 5, 6, 7, 8

SUV/LIGHT TRUCK



TRAILCAT ALL SEASON TRAILCAT LT ALL SEASON



ALL-WEATHER TREAD

A five-rib tread design creates a pattern of gripping edges for excellent traction. Lateral grooves and shoulder slots evacuate water from the contact area for effective wet weather driving control. The arrangement of the tread elements also promotes even treadwear.

SUV/LT SIZES

A range of sizes fills the replacement requirements for the most popular pickups, vans and SUV's used for commercial or recreational purposes. Outline white letters and blackwall stylings are available.

SUV SIZES

M + S RATED **UTQG**

SERIES (Size) TREADWEAR TRACTION TEMP
METRICS 400 A B

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Pass. Max. Load @ 35 PSI	LT Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth		Ship Weight (lbs.)	Size Code	F.E.T.	Price
									32nds	mm				
OUTLINE WHITE LETTER SIZES: WLI-2FH														
12810	205/75R15 97S	(5.5) 5.0-7.0	1609	1463	26.93	8.10	5.70	772	11.0	8.7	23	V654		
12811	215/75R15 100S	(6.0) 5.5-7.0	1764	1604	27.48	8.60	6.00	757	11.0	8.7	24	V754		
12812	225/75R15 102S	(6.0) 6.0-7.5	1874	1704	28.08	8.95	6.20	740	11.0	8.7	26	V854		
12813	235/75R15 105S	(6.5) 6.0-8.0	2039	1854	28.70	9.30	6.50	724	11.0	8.7	28	V954		
12817	265/75R15 112S	(7.5) 7.0-8.5	2469	2245	30.40	10.65	7.60	680	11.0	8.7	36	VV54		
12827	245/75R16 111S	(7.0) 6.5-8.0	2403	2185	30.20	9.75	7.10	688	11.0	8.7	32	V064		
12829	265/75R16 116S	(7.5) 7.0-8.5	2756	2505	31.32	10.60	7.80	664	11.0	8.7	37	VV64		
12832	225/70R16 102S	(6.5) 6.0-7.5	1874	1704	28.20	9.14	7.10	737	11.0	8.7	29	R864		
12833	235/70R16 106S	(7.0) 6.0-7.5	2094	1904	28.73	9.40	7.40	724	11.0	8.7	31	R964		
12834	245/70R16 107S	(7.0) 6.5-8.0	2149	1954	29.38	9.85	7.70	708	11.0	8.7	32	R064		
12835	255/70R16 111S	(7.5) 6.5-8.5	2403	2185	29.80	10.30	8.00	698	11.0	8.7	34	RX64		
12837	265/70R16 112S	(8.0) 7.0-9.0	2469*	2245*	30.20	10.80	7.84	687	11.0	8.7	35	RV64		

Notes: 1, 2, 4, 8
* Max. Load @ 44 PSI.

LIGHT TRUCK SIZES

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS							Ship Wght. (lbs.)	Size Code	F.E.T.	Price
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds				
BLACK SIDEWALL SIZES: WII-769																		
76905	LT215/85R16 110/107N	D	(6.0) 5.5-7.0	65	2150	65	2335	30.20	8.40	9.7	9.9	14.1	687	14.0	11.1	34	Y768	
76906	LT235/85R16 120/116N	E	(6.5) 6.0-7.0	80	2778	80	3042	31.50	9.30	10.1	10.8	14.7	658	14.0	11.1	39	Y960	
76903	LT225/75R16 110/107N	D	(6.0) 6.0-7.0	65	2150	65	2335	29.30	8.50	9.5	10.2	13.6	713	14.0	11.1	34	W868	
76904	LT245/75R16 120/116N	E	(7.0) 6.5-7.0	80	2778	80	3042	30.40	9.40	10.3	11.3	14.2	682	14.0	11.1	39	W060	
76901	8.75R16.5LT 111/106N	D	(6.75) 6.0-6.75	65	2095	65	2405	29.50	8.60	9.7	9.9	13.7	705	14.0	11.1	34	8768	
76902	9.50R16.5LT 117/112N	D	(6.75) 6.75-8.25	65	2470	65	2835	30.30	9.20	10.4	10.7	14.2	684	14.0	11.1	38	9568	
OUTLINE WHITE LETTERS: WLI-769																		
76907	LT235/75R15 104/101Q	C	(6.5) 6.0-7.0	50	1820	50	1985	28.70	8.90	9.7	10.8	13.2	722	14.0	11.1	31	W956	
76908	30X9.50R15LT 104Q	C	(7.5) 6.5-8.5	-	-	50	1985	29.10	9.30	10.1	-	13.4	713	14.0	11.1	33	3956	
76909	31X10.50R15LT 109Q	C	(8.5) 7.0-9.0	-	-	50	2270	30.00	10.50	11.4	-	13.8	691	14.0	11.1	37	3056	
76910	LT265/75R16 112/109N	C	(7.5) 7.0-8.0	50	2270	50	2470	31.63	10.38	11.3	12.2	14.7	654	14.0	11.1	41	W166	

Notes: 2, 3, 6, 7, 8

SUV/LIGHT TRUCK



WILDCAT H/T RADIAL LT



TUBELESS CONSTRUCTION

The same innerliner used in our performance-proven passenger radials provides effective air retention. High levels of chlorobutyl rubber also diminish penetration of harmful air and moisture into the tire carcass for excellent durability.

LONG MILEAGE TREAD COMPOUND

Precision blending of synthetic rubbers and other compound ingredients creates a tire that's high on durability and long on mileage. Rubber chemistry also accounts for excellent adhesion, heat dissipation and flexibility in virtually all driving conditions.

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS										Ship Wght. (lbs.)	Size Code	F.E.T.	Price	
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm							
BLACK SIDEWALL SIZES:																			W11-760			
76011	LT215/85R16 115/112N	E	(6.0) 5.5-7.0	80	2470	80	2680	30.26	8.21	9.7	9.9	14.1	683	14.0	11.1	38	Y760					
76009	LT235/85R16 120/116N	E	(6.5) 6.0-7.0	80	2778	80	3042	31.70	9.21	10.1	10.8	14.7	656	14.0	11.1	43	Y960					
76016	LT225/75R16 115/112N	E	(6.0) 6.0-7.0	80	2470	80	2680	29.18	8.60	9.5	10.2	13.6	711	14.0	11.1	38	W860					
76007	LT245/75R16 120/116N	E	(7.0) 6.5-7.0	80	2778	80	3042	30.46	9.35	10.3	11.3	14.2	680	14.0	11.1	42	W060					
76010	LT265/75R16 123/120N	E	(7.5) 7.0-8.0	80	3085	80	3415	31.65	10.50	10.5	12.2	14.7	663	14.0	11.1	46	W160					
76001	7.50R16LT 112/107N	D	(6.0) 5.5-7.0	65	2150	65	2470	31.80	8.35	9.7	10.0	14.8	652	14.0	11.1	37	7568					
76002	8.00R16.5LT 105/101N	D	(6.0) 6.0-6.75	65	1820	65	2040	28.45	7.80	8.9	9.0	13.2	728	14.0	11.1	34	8068					
76003	8.75R16.5LT 111/106N	D	(6.75) 6.0-6.75	65	2095	65	2405	29.42	8.60	9.7	9.9	13.7	704	14.0	11.1	38	8768					

Notes: 2, 3, 6, 7, 8

SUV/LIGHT TRUCK



WILDCAT EXT RADIAL LT



HIGH VOID TRACTION TREAD

Deep shoulder lugs and a unique "chunky" center zone of contoured traction elements help the tire to rise high out of a tread void. The shoulder lugs are alternately scalloped for each section to have clear shot at fresh ground for superb traction.

STEEL CORD BELTS

Steel cord belts help shield the tread against punctures and impact breaks. The strength of steel and an optimized tread radius provide a big, flat treadprint for total road contact and stability.

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS												Ship Wght. (lbs.)	Size Code	F.E.T.	Price
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	STUD SIZE TSM#	EURO. #						
BLACK SIDEWALL SIZES:																WII-770							
77007	LT235/85R16 120/116N E	(6.5) 6.0-7.0	80	2778	80	3042	31.80	9.30	10.2	10.8	14.7	652	18.0	14.3	15	9-13	44	Y960					
OUTLINE WHITE LETTER SIZES:																WLI-770							
77009	LT235/75R15 104/101Q C	(6.5) 6.0-7.0	50	1820	50	1985	28.90	9.00	9.9	10.8	13.4	717	18.0	14.3	15	9-13	33	W956					
77014	30X9.50R15LT 104Q C	(7.5) 6.5-8.5	-	-	50	1985	29.30	10.10	11.0	-	13.4	708	19.5	15.5	17	9-16	37	3956					
77015	31X10.50R15LT 109Q C	(8.5) 7.0-9.0	-	-	50	2270	30.50	10.50	12.0	-	14.0	681	20.0	15.9	17	9-16	41	3056					
77016	31X11.50R15LT 110Q C	(9.0) 8.0-10.0	-	-	50	2335	30.60	11.80	12.5	-	14.1	677	20.0	15.9	17	9-16	44	3156					
77020	32X11.50R15LT 113Q C	(9.0) 8.0-10.0	-	-	50	2535	30.60	11.80	12.5	-	14.1	677	20.0	15.9	17	9-16	46	3356					
77017	33X12.50R15LT 108Q C	(10.0) 8.5-11.0	-	-	35	2205	32.50	12.80	13.7	-	14.9	638	21.0	16.7	17	9-16	53	3256					
77025	35X12.50R15LT 113Q C	(10.0) 8.5-11.0	-	-	35	2535	34.85	12.87	13.4	-	16.6	613	20.5	16.3	17	9-16	64	3556					
* 55513	LT255/85R16 119/116N D	(7.0) 6.5-8.0	65	2755	65	3000	33.10	9.85	10.8	11.5	15.4	677	17.0	13.5	15	9-13	46	YX68					
77011	LT245/75R16 120/116N E	(7.0) 6.5-7.0	80	2778	80	3042	30.70	9.45	10.3	11.3	14.0	675	17.0	13.5	15	9-13	42	W060					
77022	LT265/75R16 112/109N C	(7.5) 7.0-8.0	50	2270	50	2470	32.00	10.10	11.3	12.2	14.8	655	18.5	14.7	15	9-13	46	W166					
77024	LT265/75R16 123/120N E	(7.5) 7.0-8.0	80	3085	80	3415	32.00	10.10	11.3	12.2	14.8	655	18.5	14.7	15	9-13	49	W160					
77026	LT285/75R16 122/119N D	(8.0) 7.5-9.0	65	3000	65	3305	33.10	11.30	12.9	13.7	15.6	646	18.5	14.7	15	9-13	53	W468					
77028	LT315/75R16 121N D	(8.5) 8.0-10.0	-	-	50	3195	34.75	12.47	13.3	-	16.6	615	20.0	15.9	17	9-16	62	WB68					
77032	LT255/70R16 108/104Q C	(7.5) 6.5-8.0	50	1985	50	2205	30.10	10.36	11.3	12.3	13.7	689	17.0	13.5	15	9-13	41	UX66					
77018	33X12.50R16.5L 118N D	(9.75) 8.25-10.5	-	-	50	2910	32.50	12.70	13.8	-	15.0	638	20.5	16.3	17	9-16	57	3268					
77034	LT265/70R17 112/109Q C	(8.0) 7.0-8.5	50	2270	50	2470	31.75	10.60	12.0	13.0	14.5	653	18.5	14.7	15	9-13	47	U176					

Notes: 2, 3, 5, 6, 7, 8

* Supplied in Durango M/T design (WL1-555).

SUV/LIGHT TRUCK



DURANGO RADIAL XTR



LARGE, BEEFY TREAD ELEMENTS

Designed for off-road application while providing long, even wear in highway applications.

DEEP TREAD AND SCALLOPED SHOULDER DESIGN

Maximize traction on soft surfaces.

BEVELED TREADBLOCK EDGES

Fight irregular wear and improve self-cleaning capabilities.

SUV SIZES

M + S RATED

Item #	Tire Size & Service Description	Meas. Rim Width / Approved Rim Width	Pass. Max. Load @ 35 PSI	LT Max. Load @ 35 PSI	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth 32nds	mm	Stud Size TSM#	EURO#	Ship Weight (lbs.)	Size Code	F.E.T.	Price
OUTLINE WHITE LETTER SIZES: WLI-IFN																
73604	235/75R15 105S	(6.5) 6.0-8.0	2039	1854	29.00	9.40	7.40	717	15.0	11.9	13	9-12	31	V954		

Notes: 1, 2, 4, 8

LIGHT TRUCK SIZES

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS													
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	STUD SIZE TSM#	EURO. #	Ship Wght. (lbs.)	Size Code	F.E.T.	Price
BLACK SIDEWALL SIZES: WII-736																					
73632	LT235/85R16	120/116N	E (6.5) 6.0-7.0	80	2778	80	3042	31.90	9.29	10.5	10.8	14.7	654	18.0	14.3	15	9-13	45	Y960		
73633	LT225/75R16	115/112N	E (6.0) 6.0-7.0	80	2470	80	2680	29.35	8.54	9.8	10.2	13.6	710	18.0	14.3	15	9-13	39	W860		
73634	LT245/75R16	120/116N	E (7.0) 6.5-7.5	80	2778	80	3042	30.53	9.76	10.3	11.3	14.2	680	18.0	14.3	15	9-13	45	W060		
OUTLINE WHITE LETTER SIZES: WLI-736																					
73622	LT235/75R15	104/101Q	C (6.5) 6.0-7.0	50	1820	50	1985	28.62	9.14	9.7	10.8	13.4	715	18.0	14.3	15	9-13	35	W956		
73647	31X10.50R15LT	109Q	C (8.5) 7.0-9.0	-	-	50	2270	30.47	10.71	11.4	-	14.0	687	18.0	14.3	15	9-13	41	3056		
73649	35X12.50R15LT	113Q	C (10.0) 8.5-11.0	-	-	35	2535	34.88	12.87	13.3	-	16.6	613	20.0	15.9	17	9-16	65	3556		
73643	LT265/75R16	112/109N	C (7.5) 7.0-8.0	50	2270	50	2470	31.64	10.50	11.3	12.2	14.7	654	18.0	14.3	15	9-13	46	W166		
73644	LT265/75R16	123/120N	E (7.5) 7.0-8.0	80	3085	80	3415	31.76	10.59	11.3	12.2	14.7	654	18.0	14.3	15	9-13	50	W160		
73645	LT285/75R16	122/119N	D (8.0) 7.5-9.0	65	3000	65	3305	32.80	11.30	12.5	13.3	15.1	628	20.0	15.9	17	9-16	55	W468		
73655	LT315/75R16	121N	D (8.5) 8.0-10.0	50	-	50	3195	34.60	12.87	13.3	-	16.6	615	20.0	15.9	17	9-16	64	WB68		
73661	LT305/70R16	118/115N	D (9.0) 8.0-9.5	50	2680	50	2910	32.81	12.29	12.6	13.3	15.2	626	18.0	14.3	15	9-13	56	UA68		

Notes: 2, 3, 5, 6, 7, 8

SUV/LIGHT TRUCK



MUD TERRAIN RADIAL SXT



LARGE BEEFY TREAD ELEMENTS

Designed for off-road applications while providing long, even wear in highway applications

DEEP TREAD & SCALLOPED SHOULDER DESIGN

Maximizes traction in soft surfaces

STAGGERED TREAD ELEMENTS

Breaks up harmonic pitch, significantly reducing tire noise.

PINNED FOR STUDS

Self-cleaning tread features holes for metal traction studs.

M + S RATED

Item #	Tire Size & Service Description	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS											
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds mm	Stud Size TSM# EURO	Ship Wght. (lbs.)	Size Code	F.E.T.	Price
BLACK SIDEWALL SIZES:																WII-776			
05265	LT215/85R16 115/112N	E	(6.0) 5.5-7.0	80	2470	80	2680	30.48	8.41	10.0	9.9	14.1	684	18.0	14.3	15	9-13	40	Y760
05266	LT235/85R16 120/116N	E	(6.5) 6.0-7.0	80	2778	80	3042	31.90	9.29	10.5	10.8	14.7	654	18.0	14.3	15	9-13	44	Y960
05267	LT225/75R16 115/112N	E	(6.0) 6.0-7.0	80	2470	80	2680	29.35	8.54	9.8	10.2	13.6	710	18.0	14.3	15	9-13	40	W860
05268	LT245/75R16 120/116N	E	(7.0) 6.5-7.5	80	2778	80	3042	30.53	9.76	10.3	11.3	14.2	680	18.0	14.3	15	9-13	46	W060
OUTLINE WHITE LETTER SIZES:																WLI-776			
05262	LT235/75R15 104/101Q	C	(6.5) 6.0-7.0	50	1820	50	1985	28.62	9.14	9.7	10.8	13.4	715	18.0	14.3	15	9-13	36	W956
05290	30X9.50R15LT 104Q	C	(7.5) 6.5-8.5	-	-	50	1985	29.35	9.63	10.1	-	13.6	708	18.0	14.3	15	9-13	37	3956
05292	31X10.50R15LT 109Q	C	(8.5) 7.0-9.0	-	-	50	2270	30.47	10.71	11.4	-	14.0	687	18.0	14.3	15	9-13	41	3056
05293	32X11.50R15LT 113Q	C	(9.0) 8.0-10.	-	-	50	2535	31.47	11.70	12.2	-	14.4	662	20.0	15.9	17	9-16	47	3356
05291	33X9.50R15LT 113Q	C	(7.5) 6.5-8.5	-	-	50	2536	32.60	9.50	10.1	-	15.1	619	18.0	14.3	15	9-13	41	3456
05294	33X12.50R15LT 108Q	C	(10.) 8.5-11.	-	-	35	2205	32.63	12.36	13.5	-	15.0	640	20.0	15.9	17	9-16	53	3256
05296	35X12.50R15LT 113Q	C	(10.) 8.5-11.	-	-	35	2535	34.88	12.87	13.3	-	16.6	613	20.0	15.9	17	9-16	63	3556
05264	LT255/85R16 119/116N	D	(7.0) 6.5-8.0	65	2755	65	3000	33.21	10.04	10.7	11.7	15.2	628	18.0	14.3	15	9-13	48	YX68
05269	LT265/75R16 112/109N	C	(7.5) 7.0-8.0	50	2270	50	2470	31.64	10.50	11.3	12.2	14.7	654	18.0	14.3	15	9-13	46	W166
05270	LT265/75R16 119/116N	D	(7.5) 4.0-8.0	65	2755	65	3000	31.73	10.52	11.3	12.2	14.7	654	18.0	14.3	15	9-13	47	W168
05271	LT265/75R16 123/120N	E	(7.5) 7.0-8.0	80	3082	80	3415	31.76	10.59	11.3	12.2	14.7	654	18.0	14.3	15	9-13	50	W160
05272	LT285/75R16 122/119N	D	(8.0) 7.5-9.0	65	3000	65	3305	32.80	11.30	12.5	13.3	15.1	628	20.0	15.9	17	9-16	55	W468
05280	LT315/75R16 121N	D	(8.5) 8.0-10	-	-	50	3195	34.60	12.87	13.3	-	16.6	615	20.0	15.9	17	9-16	64	WB68
05284	LT305/70R16 118/115Q	D	(9.0) 8.0-9.5	50	2680	50	2910	32.81	12.29	12.6	13.3	15.2	626	18.0	14.3	15	9-13	56	UA68
05289	LT235/80R17 120/117Q	E	(6.5) 6.0-8.0	80	2835	80	3082	31.85	9.40	10.3	10.8	14.5	652	18.0	14.3	15	9-13	45	X970
05286	LT245/70R17 119/116Q	E	(7.0) 6.5-8.0	80	2755	80	3000	30.45	10.07	10.7	11.3	14.1	679	18.0	14.3	15	9-13	46	U070
05288	LT265/70R17 112/109Q	C	(8.0) 7.0-9.0	50	2270	50	2470	31.65	10.71	11.3	12.4	14.7	656	18.0	14.3	15	9-13	47	U176
05287	LT265/70R17 121/118Q	E	(8.0) 7.0-9.0	80	2910	80	3195	31.65	11.03	11.3	12.4	14.7	656	18.0	14.3	15	9-13	52	U170
05295	33X12.50R17LT 114Q	D	(10.) 8.5-11.	-	-	50	2600	32.62	12.36	13.5	-	15.0	640	20.0	15.9	17	9-16	57	3278
05297	35X12.50R17LT 119Q	D	(10.) 8.5-11.	-	-	50	3000	34.88	12.87	13.3	-	16.6	596	20.0	15.9	17	9-16	65	3578
05285	LT275/65R18 113/110R	C	(8.0) 7.0-9.0	50	2335	50	2535	32.20	10.98	12.6	12.8	15.0	645	18.0	14.3	15	9-13	51	SY86

SUV/LIGHT TRUCK



SUPER ROAD SERVICE



CAP/BASE TREAD

Greatly increases separation resistance and offers particular resistance to internal heat build up.

ANTI-OZONANT SYSTEM

This system in the tread, buttress & sidewall compounds helps increase their resistance to ozone cracking.

SHOCK-GUARD CONSTRUCTION

Body plies are impregnated with highly resilient rubber to guard against impact shock.

Item #	Tire Size	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS										
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	mm	Ship Wght. (lbs.)	Size Code	F.E.T.
BIAS TUBELESS SIZES: ALL-WHEEL POSITION																	411-550	
55007	7.00-15LT	C	(5.5) 5.0-6.5	45	1520	45	1720	30.00	8.30	8.7	9.0	13.9	715	14.5	11.5	34	7056	
55008	7.00-15LT	D	(5.5) 5.0-6.5	60	1800	60	2040	30.40	8.20	8.6	9.0	14.1	704	14.5	11.5	35	7058	
55009	7.50-16LT	D	(6.0) 5.5-7.0	60	2140	60	2440	32.30	8.90	9.4	10.0	15.0	662	14.5	11.5	45	7568	
55011	8.75-16.5LT	D	(6.75) 6.0-6.75	60	2070	60	2350	29.80	9.40	9.8	9.9	13.8	720	15.0	11.9	41	8768	
55012	8.75-16.5LT	E	(6.75) 6.0-6.75	75	2360	75	2680	30.00	9.40	9.8	9.9	13.9	714	15.0	11.9	41	8760	
55013	9.50-16.5LT	D	(6.75) 6.75-8.25	60	2445	60	2780	30.80	10.00	10.5	10.7	14.3	695	15.5	12.3	44	9568	
55014	9.50-16.5LT	E	(6.75) 6.75-8.25	75	2790	75	3170	31.00	10.10	10.6	10.7	14.4	690	15.5	12.3	46	9560	
55015	12-16.5LT	D	(9.75) 8.25-9.75	45	2640	45	3000	32.20	12.30	13.0	13.7	15.1	658	16.0	12.7	54	1268	
BIAS TUBELESS SIZES: TRAILER POSITION																	411-550	
*55005	8-14.5	F	(6.0) 6.0-6.0	100	2460	100	2790	28.40	8.10	8.7	8.8	13.3	746	11.0	8.7	36	0842	
*55006	9-14.5	F	(7.0) 7.0-7.0	100	2840	100	3230	28.00	9.50	10.1	10.5	13.2	742	12.0	9.5	41	0942	

Notes: 3, 6, 7

* Tread design is different.

SUV/LIGHT TRUCK



COURSER TRACTION LT



HIGH TRACTION TREAD

Two wide center grooves and deep shoulder lugs form an effective pattern of gripping edges for excellent off-road traction. The groove network also channels out water quickly and efficiently for sure-footed traction on rain-soaked highways. Traction elements are varied in size and shape for quiet running at legal speeds.

DURABLE TREAD COMPOUND

Using computer technology, the tread compound is formulated to combine the materials to provide excellent performance both on the highway and in off-road use.

M + S RATED

Item #	Tire Size	Load Range	Meas. Rim Width / Approved Rim Width	DUAL TIRES		SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS															
				Infl. Press.	Max. Load Lbs.	Infl. Press.	Max. Load Lbs.	Overall Diameter	Overall Width	Loaded Width	Min. Dual Spacing w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth 32nds	Tread Depth mm	Stud Size TSM#	Stud Size EURO. #	Ship Wght. (lbs.)	Size Code	F.E.T.	Price		
BIAS TUBELESS SIZES:																				411-620			
62005	7.00-15LT	C	(5.5) 5.0-6.5	45	1520	45	1720	30.03	8.20	8.5	9.0	14.1	704	18.5	14.7	17	9-16	35	7056				
62007	7.50-16LT	D	(6.0) 5.5-7.0	60	2140	60	2440	32.20	9.11	9.4	10.0	15.0	662	19.0	15.1	17	9-16	47	7568				

Notes: 3, 5, 6, 7

SUV/LIGHT TRUCK



CUSTOM TRAILER / CUSTOM TRAILER PLUS



RADIAL CONSTRUCTION

Steel belted radial construction offers performance advantages in tread life, fuel economy and handling over equivalent sized bias ply tires. The low rolling resistance of radial tires means low towing resistance for excellent miles per gallon on long hauls.

SOFT, SMOOTH RIDE

Flexible radial sidewalls provide a smooth, soft ride to help protect the precious cargo of towed trailers, boats and campers. A special arrangement of the tread elements helps keep noise levels low.

CUSTOM TRAILER PLUS (DESIGN A)

Item #	Tire Size	Load Range	Service Descp.	Meas. Rim Width / Approved Rim Width	SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS								Ship Wght. mm(lbs.)	Size Code	F.E.T.	Price
					Infl. Press.	Load Lbs.	Max. Overall Diameter	Overall Width	Loaded Width	Loaded Radius	Rev. Per Mile	Tread Depth 32nds						
BLACK SIDEWALL SIZES: W11-879																		
88000	ST225/75R15	D	113S	(6.0) 6.0-7.0	65	2540	28.26	9.05	9.5	12.8	717	9.5	7.5	32	W858			

Notes: 2

CUSTOM TRAILER (DESIGN B)

Item #	Tire Size	Load Range	Service Descp.	Meas. Rim Width / Approved Rim Width	SINGLE TIRES		INFLATED NEW TIRE DIMENSIONS								Ship Wght. mm(lbs.)	Size Code	F.E.T.	Price
					Infl. Press.	Load Lbs.	Max. Overall Diameter	Overall Width	Loaded Width	Loaded Radius	Rev. Per Mile	Tread Depth 32nds						
BLACK SIDEWALL SIZES: W11-880																		
*88002	ST205/75R14	C	100	(5.5) 5.0-6.5	50	1760	26.00	8.00	8.8	11.8	798	10.5	8.3	23	W646			
88003	ST205/75R15	C	101	(5.5) 5.0-6.5	50	1820	27.00	8.00	8.8	12.5	769	10.5	8.3	24	W656			

Notes: 2

*Different design.

SAFETY WARNING: "Serious injury or death can result from: Misapplication of these tires - These tires are designed specifically for trailer use only. They are not designed for use on wagons, motor vehicles or any other application.

Please take time to inform your sales and service personnel and users as to the proper application of these tires."

SUV/LIGHT TRUCK



LIMITED WARRANTY

STANDARD COVERAGE

If your Dean radial tire becomes unserviceable as a result of an eligible adjustable condition during the first 25% of treadwear, it will be replaced with an equivalent new Dean tire, *FREE OF CHARGE*, including mounting and balancing. When the tread is worn more than 25%, a replacement charge will be required in order to obtain a replacement tire.

The replacement charge will be determined by multiplying your original purchase price by the percentage of original tread depth worn from the tire. You must pay for mounting, balancing, and any other additional charges, such as taxes or the acceptance of a higher priced replacement tire.

EXTRA COVERAGE FOR PREMIUM TIRES

The following No-Charge Warranty covers eligible adjustable conditions only, and should not be confused with the prorated Treadwear Protection covered in the next section. If your Dean Equus LSi or Wildcat Touring SLT, or Wildcat Radial AT radial tire becomes unserviceable as a result of an eligible adjustable condition during its useable tread life, it will be replaced with an equivalent new Dean tire, *FREE OF CHARGE*, including mounting and balancing. When the tread is worn more than 25%, you must present the warranty booklet and be the original owner to obtain your replacement tire. Otherwise, you will be required to pay the replacement charge described in the above Standard Coverage in order to obtain your replacement tire.

TREADWEAR PROTECTION

The following Treadwear Warranty is a prorated warranty based on mileage received, and is separate from the No-Charge Warranty just covered. The following Dean radial tires are warranted against tread wear-out prior to applicable indicated mileage:

Tire	Miles Warranted
Equus LSi (T-Rated)	70,000
Wildcat Touring SLT	60,000
Quasar Plus	55,000
Equus LSi (H & V Rated)	50,000
Stinger GTS	50,000
Wildcat Radial A/T	50,000
Stinger GTH	45,000
Alpha 365	40,000
Celestial Metric	40,000

*Mileage warranty applies to passenger and light truck lines.

Provided that you:

1. are the original owner.
2. rotate your tires in accordance with prescribed rotation patterns at least every 8,000 miles and it is recorded in the rotation schedule in this warranty.
3. present the tire for adjustment.
4. present the warranty booklet when requesting an adjustment and the date of purchase, vehicle type, odometer reading and rotation record are properly recorded.

If the tire wears to the treadwear indicators in less than the miles warranted, a pro-rated adjustment will be made according to actual mileage delivered. Your replacement cost will be determined by dividing the actual mileage delivered by the miles warranted and multiplying the result times the current selling price of an equivalent or comparable replacement tire. You must pay for mounting and balancing and any other additional charges, such as taxes or the acceptance of a higher priced replacement tire.

TREAD LIFE

When the tread becomes worn down to 2/32" (1.6mm) (shown by treadwear indicators molded into the tread grooves) the tire is worn out.

WHAT IS NOT COVERED

Adjustments will not be made for:

- A. Tires which become unserviceable due to:
 1. Conditions resulting from road hazards, such as (A) impact damage, (B) cuts, (C) snags, or (D) punctures.
 2. Conditions resulting from (A) improper installation, (B) wheel misalignment, or (C) tire/wheel assembly imbalance.

3. Conditions resulting from consumer damage, such as: (A) improper tire and vehicle maintenance, (B) misuse, (C) abuse, (D) accident, (E) under inflation or (F) overloading.
 4. Ride complaints after the first 25% treadwear.
 5. Use in any commercial, racing, or off-road application.
 6. Ozone or weather checking on tires over four (4) years from date of manufacture.
 7. Improper storage.
- or
- B. Tires which are:
 1. Worn unevenly and/or show a difference of 2/32" (1.6mm) between the grooves.
 2. Installed on any vehicle other than the vehicle on which they were first installed.
 3. Sold or adjusted outside the 48 contiguous Continental United States and the District of Columbia.
 4. Purchased as used.
 5. Altered in any manner (additional siping, buffing, stud pin holes).
 6. Worn to 2/32" (1.6mm) or more than 72 months old (based on date of purchase).
 7. Improperly repaired.

Tires branded "MALWEAR" OR "NO-UNIF" (Non-Uniform) are not covered under the Treadwear Protection provided herein.

REPLACEMENT WARRANTY

If you receive a replacement tire under the terms of this warranty, the replacement tire will be covered by the warranty then currently given by Dean for the tire. Dean is a division of Cooper Tire & Rubber Company.

WHERE TO GO FOR WARRANTY REPLACEMENT

See your Dean dealer. They are listed in the yellow pages under Tire Dealers-Retail. In the event you are unable to locate a Dean dealer, you can obtain assistance by contacting the Consumer Relations Department at 1-800-822-8686 or by going to www.deantires.com.

CONDITIONS AND EXCLUSIONS

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Nothing in this warranty is intended to be a representation by Dean that tire failure cannot occur.

DEAN DISCLAIMS ANY LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES TO THE EXTENT PERMITTED BY LAW.

Some states do not allow exclusion of incidental or consequential damages so this limitation or exclusion may not apply to you.

USED TIRES

Never purchase used tires! Previous use may have damaged internal components. This damage could lead to sudden tire failure.

CONSUMER RIGHTS

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

OWNER'S OBLIGATION

When making a claim, you must return the tire to be replaced to your Dean dealer and sign the customer signature section of the Tire Claim Form.

Proper vehicle and tire care is necessary to obtain the expected wear from a tire. It is your obligation to properly maintain your tires and the vehicle upon which they are mounted, including: (A) operating your tires at the inflation pressures recommended by the vehicle manufacturer, (B) keeping your tire/wheel assemblies in balance, (C) proper wheel alignment, and (D) proper tire rotation.

We recommend that you have your Dean dealer inspect your tires any time you notice irregular or uneven tread wear and rotate them if necessary.

DEAN TIRES
P.O. BOX 550
FINDLAY, OH 45839



NOTES AND RECOMMENDATIONS

- 1 NOTE: Metric tires may be used in P-metric application, provided metric load index values are equal to or greater than P-metric load index values. Use inflation pressure specified on vehicle placard.
- 2 IMPORTANT: Not all rims and wheels are approved for use with radial ply tires. Use of a non-approved rim or wheel could result in rim fatigue failure and a possible accident. It is, therefore, extremely important to consult the wheel and rim manufacturer or his local distributor to determine which rims or wheels are acceptable for use with a specific radial ply tire.
- 3 Load Index differs depending on whether the tires are used in single or dual application (Single/Dual).
- 4 When passenger tires are used in light truck service, tire and rim industry standards apply a 10% reduction in maximum rated load.
- 5 MOUNTING: Due to the special high traction characteristics of these tires, it is recommended that tires be mounted in sets of four to provide the best tire performance.
- 6 MINIMUM DUAL SPACING - The minimum dimension from the centerline of one rim to the centerline of the other rim in a dual wheel assembly is recommended to provide adequate clearance between tires.
- 7 LOADED WIDTH - The deflected cross sectional width of the tire uses the Tire and Rim Association's maximum dual tire load and corresponding inflation pressure.
- 8 SPEED RATINGS: Capable of sustaining indoor wheel tests at the following speeds:

N = 87 mph

P = 93 mph

Q = 99 mph

R = 106 mph

S = 112 mph

T = 118 mph

U = 124 mph

H = 130 mph

V = 149 mph

W = 168 mph

Y = 186 mph

Z = 150+ mph



P.O. BOX 550
FINDLAY, OHIO 45839

Visit Our Web Site At: <http://www.deantires.com>